

Specifications

Eaton 044879



Eaton xEnergy Safety Ci LV systems LV switchgear. Flange, through-hole foam rubber, IP54, HxWxD=116x329x23mm

General specifications

PRODUCT NAME	Eaton xEnergy Safety Ci flange plate
CATALOG NUMBER	044879
MODEL CODE	FL4-D
EAN	4015080448792
PRODUCT LENGTH/DEPTH	116 mm
PRODUCT HEIGHT	23 mm
PRODUCT WIDTH	330 mm
PRODUCT WEIGHT	0.344 kg
COMPLIANCES	RoHS conform

Additional information

FEATURES	Pre-stamping
USED WITH	NY Y, NY M 4 x 10 mm ² - 4 x 50 mm ² NY Y, NY M 4 x 4 mm ² - 5 x 10 mm ² 375 mm (enclosure dimensions) NY Y, NY M 3 x 1.5 mm ² - 5 x 2.5 mm ² Accessory for basic enclosures Basic enclosure xEnergy Safety Ci

Technical data - mechanical

DEGREE OF PROTECTION	IP54 Other
MATERIAL	Plastic
NUMBER OF CONNECTOR HOLES	0
OUTER CABLE DIAMETER	2 x (20 - 30) mm 4 x (15 - 19) mm 42 x (10 - 13) mm
SHAPE	Straight
SUITABLE FOR CABLE DIAMETER - MAX	30 mm
SUITABLE FOR NOMINAL THREAD (PG) - MIN	10
SURFACE PROTECTION	Untreated
THICKNESS	4 mm
THREAD TYPE	None
UNIT TYPE	Modular system
SUITABLE FOR CABLE DIAMETER - MIN	10 mm
SUITABLE FOR NOMINAL THREAD (PG) - MAX	30

Delivery programme

ACCESSORY/SPARE PART TYPE	Sponge-rubber flange IP54
MODEL	Cable screw gland
TYPE	• Accessory for basic enclosures • Basic enclosure • xEnergy Safety Ci

Resources

BROCHURES	eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf
CATALOGUES	eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf
DRAWINGS	eaton-enclosures-flanges-xeffect-ci-enclosure-dimensions-003.eps eaton-enclosures-flange-xenergy-safety-ci-flange-plate-symbol.eps
INSTALLATION INSTRUCTIONS	eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf eaton-xeffect-ci-installation-instruction-awa31-566-z.pdf
MCAD MODEL	fl4 d.stp eaton-enclosure-plates-mcad-drawings-fl4-d.dwg

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

