

Specifications



Eaton 046988

Eaton Moeller® series PKZM0 Motor-protective circuit-breaker, 9 kW, 16 - 20 A, Screw terminals

General specifications

PRODUCT NAME	Eaton Moeller® series PKZM0 Motor-protective circuit-breaker
---------------------	--

CATALOG NUMBER	046988
-----------------------	--------

MODEL CODE	PKZM0-20
-------------------	----------

EAN	4015080469889
------------	---------------

PRODUCT LENGTH/DEPTH	76 mm
-----------------------------	-------

PRODUCT HEIGHT	93 mm
-----------------------	-------

PRODUCT WIDTH	45 mm
----------------------	-------

PRODUCT WEIGHT	0.296 kg
-----------------------	----------

CERTIFICATIONS	IEC/EN 60947 CSA File No.: 165628 IEC/EN 60947-4-1 CSA-C22.2 No. 60947-4-1-14 UL 60947-4-1 CE UL Category Control No.: NLRV VDE 0660 CSA Class No.: 3211-05 UL File No.: E36332 UL CSA
-----------------------	---



Powering Business Worldwide

Climatic environmental conditions

ALTITUDE	Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Design verification

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	20 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product

	standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	5.82 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.94 W

Electrical rating

RATED FREQUENCY - MAX	60 Hz
------------------------------	-------

RATED FREQUENCY - MIN	50 Hz
------------------------------	-------

RATED OPERATIONAL CURRENT (IE)	20 A
---------------------------------------	------

RATED OPERATIONAL POWER AT AC-3E, 220/230 V, 50 HZ	5.5 kW
---	--------

RATED OPERATIONAL POWER AT AC-3E, 380/400 V, 50 HZ	9 kW
---	------

RATED OPERATIONAL POWER AT AC-3E, 440 V, 50 HZ	11 kW
---	-------

RATED OPERATIONAL POWER AT AC-3E, 500 V, 50 HZ	12.5 kW
---	---------

RATED OPERATIONAL POWER AT AC-3E, 690 V, 50 HZ	15 kW
---	-------

RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
---	-------

RATED OPERATIONAL VOLTAGE (UE) - MIN	690 V
---	-------

RATED UNINTERRUPTED CURRENT (IU)	20 A
---	------

Features & functions

ACTUATOR TYPE	Turn button
----------------------	-------------

FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
-----------------	--

FUNCTIONS	Motor protection Phase failure sensitive
------------------	---

NUMBER OF POLES	Three-pole
------------------------	------------

General information

CONNECTION	Screw terminals
DEGREE OF PROTECTION	IP20 Terminals: IP00
EXPLOSION SAFETY CATEGORY FOR DUST	PTB 10, ATEX 3013 Ex II (2) G [Ex eb Gb] [Ex db Gb] [Ex pxb Gb] Ex II (2) D [Ex tb Db] [Ex pxb Db]
LIFESPAN, ELECTRICAL	100,000 operations
LIFESPAN, MECHANICAL	100,000 Operations
MOUNTING POSITION	Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.
OPERATING FREQUENCY	40 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Motor protective circuit breaker
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
SUITABLE FOR	Also motors with efficiency class IE3 Branch circuit: Manual type E if used with terminal, or suitable for group installations, (UL/CSA)
TEMPERATURE COMPENSATION	≤ 0.25 %/K, residual error for T > 40° -25 - 55 °C, Operating range -5 - 40 °C to IEC/EN 60947, VDE 0660

Motor rating

ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE 1.5 HP

ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE 5 HP

ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE 3 HP

ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE 15 HP

Short-circuit rating

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICS
AT 400 V AC** 38 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICS
AT 440 V AC** 3 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICS
AT 500 V AC** 3 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICS
AT 690 V AC** 1 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICU
AT 400 V AC** 50 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICU
AT 440 V AC** 10 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICU
AT 500 V AC** 3 kA

**RATED SHORT-CIRCUIT
BREAKING CAPACITY ICU
AT 690 V AC** 3 kA

SHORT-CIRCUIT CURRENT 40 kA DC, up to 250 V DC,
Main conducting paths

**SHORT-CIRCUIT CURRENT
RATING (GROUP
PROTECTION)**

10 kA, 600 V High Fault,
Fuse, SCCR (UL/CSA) with
150 A, 600 V High Fault,
Fuse, SCCR (UL/CSA)
10 kA, 600 V High Fault,
CB, SCCR (UL/CSA) with
125 A, 600 V High Fault,
CB, SCCR (UL/CSA)
18 kA, 600 V High Fault,
Fuse with CL, SCCR
(UL/CSA) with 600 A, 600 V
High Fault, Fuse with CL,
SCCR (UL/CSA)
18 kA, 600 V High Fault, CB
with CL, SCCR (UL/CSA)
with 600 A, 600 V High
Fault, CB with CL, SCCR
(UL/CSA)
18 kA, 480 V High Fault,
CB, SCCR (UL/CSA) with
600 A, 480 V High Fault,
CB, SCCR (UL/CSA)
18 kA, 480 V High Fault,
Fuse, SCCR (UL/CSA) with
600 A, 480 V High Fault,
Fuse, SCCR (UL/CSA)

**SHORT-CIRCUIT CURRENT
RATING (TYPE E)** 18 kA, 240 V, SCCR
(UL/CSA)

Switching capacity

SWITCHING CAPACITY 20 A (3 contacts in series),
DC-5 up to 250V
20 A, AC-3 up to 690 V

	18 kA, 480 Y/277 V, SCCR (UL/CSA) Accessories required BK25/3-PKZ0-E
SHORT-CIRCUIT RELEASE	Basic device fixed 15.5 x lu ± 20% tolerance 310 A, I _{rm}

Terminal capacities	
STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (1 - 6) mm², ferrule to DIN 46228 1 x (1 - 6) mm², ferrule to DIN 46228
TERMINAL CAPACITY (SOLID)	1 x (1 - 6) mm² 2 x (1 - 6) mm²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 10
TIGHTENING TORQUE	1.7 Nm, Screw terminals, Main cable

Trip blocks	
OVERLOAD RELEASE CURRENT SETTING - MAX	20 A
OVERLOAD RELEASE CURRENT SETTING - MIN	16 A
TRIPPING CHARACTERISTIC	Overload trigger: tripping class 10 A

Resources

BROCHURES	eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf
	eaton-push-in-technology-product-overview-brochure-br034012-en-us.pdf
CATALOGUES	Product Range Catalog Switching and protecting motors
	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-manual-motor-starters-characteristic-characteristic-curve-008.eps
	eaton-manual-motor-starters-characteristic-characteristic-curve-009.eps
DECLARATIONS OF CONFORMITY	eaton-motor-protective-circuit-breaker-declaration-of-conformity-eu251411en.pdf
	eaton-motor-protective-circuit-breaker-declaration-of-conformity-uk251167en.pdf
DRAWINGS	eaton-manual-motor-starters-pkz-dimensions.eps
	eaton-manual-motor-starters-pkzm0-dimensions-003.eps
	eaton-manual-motor-starters-pkz-dimensions-002.eps
	eaton-manual-motor-starters-mounting-3d-drawing-002.eps
	eaton-general-ie-ready-dilm-contactor-standards.eps
	eaton-manual-motor-starters-pkzm0-3d-drawing-004.eps

	eaton-manual-motor-starters-pkzm0-3d-drawing-008.eps
ECAD MODEL	ETN.046988.edz
INSTALLATION INSTRUCTIONS	IL03407011Z.pdf IL03402034Z
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MANUALS AND USER GUIDES	IL122023ZU eaton-motor-protection-pkzm0-mn03402003z-de-de-en-us.pdf
MCAD MODEL	eaton-breakers-mcad-drawings-pkzm0.dwg DA-CS-pkzm0
PEP ECO-PASSPORT	eaton-motor-protective-circuit-breakers-pep-eato-00326-v0101-en.pdf
SALES NOTES	eaton-link-module-for-motor-starters-pkz-flyer-fl034003en-en-us.pdf
WIRING DIAGRAMS	eaton-manual-motor-starters-starter-nzm-mccb-wiring-diagram.eps eaton-manual-motor-starters-transformer-pkzm0-wiring-diagram.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

