

Specifications

Eaton 058243

Eaton xEnergy Safety Ci LV systems LV switchgear. N rail with terminal for fuse enclosure tab RS27/I23, 2x 2.5-35 and 6x 0.5-6mm²

General specifications

PRODUCT NAME	Eaton xEnergy Safety Ci N + PE/N rail
CATALOG NUMBER	058243
MODEL CODE	N23RS27
EAN	4015080582434
PRODUCT LENGTH/DEPTH	30 mm
PRODUCT HEIGHT	30 mm
PRODUCT WIDTH	200 mm
PRODUCT WEIGHT	0.13 kg
COMPLIANCES	RoHS conform



Powering Business Worldwide

Additional information

FEATURES	Contact safe
SUITABLE FOR	Useful for stranded conductors
USED WITH	SE-RS-I23 RS27/I23 Prepared enclosures Ci insulated enclosure Modular busbar system

Delivery programme

ACCESSORY/SPARE PART TYPE	N bars
NOMINAL CURRENT	63 A
NUMBER OF POLES	Single-pole
TYPE	• Ci insulated enclosure • Modular busbar system • Prepared enclosures

Technical data - mechanical

CONDUCTOR CROSS SECTION, INPUT - MAX	35 mm ²
CONDUCTOR CROSS SECTION, INPUT - MIN	2.5 mm ²
CONDUCTOR CROSS SECTION, INPUT AWG - MAX	14 mm ²
CONDUCTOR CROSS SECTION, INPUT AWG - MIN	2 mm ²
CONDUCTOR CROSS SECTION, OUTPUT - MAX	6 mm ²
CONDUCTOR CROSS SECTION, OUTPUT - MIN	0.5 mm ²
CONDUCTOR CROSS SECTION, OUTPUT AWG - MAX	20 mm ²
CONDUCTOR CROSS SECTION, OUTPUT AWG - MIN	10 mm ²
NUMBER OF CONNECTIONS (LESS THAN 6 MM SQUARED)	9
NUMBER OF CONNECTIONS (LESS THAN AWG 6)	0
NUMBER OF CONNECTIONS (GREATER THAN 25 MM SQUARED)	2
NUMBER OF CONNECTIONS (GREATER THAN 250 KCMIL)	0
NUMBER OF CONNECTIONS (10 MM SQUARED)	0
NUMBER OF CONNECTIONS (16 MM SQUARED)	0
NUMBER OF CONNECTIONS (25 MM SQUARED)	0
NUMBER OF CONNECTIONS (250 KCMIL)	0
NUMBER OF CONNECTIONS (AWG 2)	0
NUMBER OF CONNECTIONS (AWG 4)	0
NUMBER OF CONNECTIONS (AWG 4/0)	0

Resources

BROCHURES	eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf
CATALOGUES	eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf
INSTALLATION INSTRUCTIONS	eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf IL0713
SYSTEM OVERVIEW	eaton-xenergy-safety-ci-sytem-overview-461n092.eps

NUMBER OF CONNECTIONS (AWG 6)	0
NUMBER OF CONNECTIONS (TOTAL)	11
NUMBER OF INPUTS	1
NUMBER OF OUTPUTS	10
TERMINAL CAPACITY (SOLID WIRE)	0.5 mm ² - 16 mm ² (9x) 2.5 mm ² - 35 mm ² (2x)
TERMINAL CAPACITY (STRANDED CABLE)	2.5 mm ² - 25 mm ² (2x) 0.5 mm ² - 4 mm ² (9x)
UNIT TYPE	Modular system
CONNECTION TYPE	Clamp Screwing
MOUNTING METHOD	Screw

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

