

Specifications



Eaton 060620

Eaton xEnergy Safety Ci LV systems LV switchgear. Busbar support, for CI enclosure 375mm, hxD=20x5(10, 15)mm

General specifications

PRODUCT NAME	Eaton xEnergy Safety Ci busbar enclosure accessory
CATALOG NUMBER	060620
MODEL CODE	SH0635/4
EAN	4015080606208
PRODUCT LENGTH/DEPTH	20 mm
PRODUCT HEIGHT	100 mm
PRODUCT WIDTH	300 mm
PRODUCT WEIGHT	0.243 kg
COMPLIANCES	RoHS conform



Powering Business Worldwide

Additional information

FUNCTIONS

For use between two enclosures
Prepared enclosure

SPECIAL FEATURES

- Component mounting possible on busbar
- Interval between busbar supports max. 375 mm

SUITABLE FOR

Use between two enclosures

USED WITH

CI43...
L1, L2, L3, PE, N, PEN: 20 x 5
CI44...
CI48...
CI45...
L1, L2, L3: 20 x 10 + 20 x 5;
PE, N, PEN: 20 x 10
L1, L2, L3: 20 x 10; PE, N, PEN: 20 x 5
xEnergy Safety Ci
Prepared enclosures
Accessory for busbar enclosures

Delivery programme

ACCESSORY/SPARE PART TYPE

Busbar support

NUMBER OF POLES

Five-pole

TYPE

- Accessory for busbar enclosures
- Prepared enclosures
- xEnergy Safety Ci

Technical data - electrical

CURRENT RATING - MAX 630 A

RATED OPERATION CURRENT (IE) 630 A
250 A
400 A

Technical data - mechanical

BUSBAR DISTANCE 50 mm

DISTANCE BETWEEN BUSBAR CENTERS 50 mm

Resources

BROCHURES

[eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf](#)

CATALOGUES

[eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf](#)

DRAWINGS

[eaton-insulated-boards-busbar-xenergy-safety-ci-busbar-support-dimensions.eps](#)

INSTALLATION INSTRUCTIONS

[eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf](#)
[IL0754](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

