

Specifications



Eaton 062655

Eaton xEffect Ci Enclosures Switch- & Controlgear Enclosure. Base, smooth sides, HxWxD=250x375x120mm

General specifications

PRODUCT NAME	Eaton xEffect Ci Enclosures Switch- & Controlgear Enclosure
CATALOG NUMBER	062655
MODEL CODE	U-CI43X
EAN	4015080626558
PRODUCT LENGTH/DEPTH	150 mm
PRODUCT HEIGHT	250 mm
PRODUCT WIDTH	375 mm
PRODUCT WEIGHT	1.692 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	EN 61439-2 EN 62208

Product specifications

SPECIAL FEATURES	Distance frame for CI45... □#110103 Flanges □#024355 Smooth sides Without knockouts
TYPE	Basic enclosure Enclosure bases xEnergy Safety Ci
FEATURES	Cover with overpressure release
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	960 °C
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Not relevant to indoor installations.
10.2.5 LIFTING	10 kg per enclosure with support frame and lifting aid met; assembled and secured as per the latest applicable instruction leaflet.
10.2.6 MECHANICAL IMPACT	IK10
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP65, with cover
10.4 CLEARANCES AND	Is the panel builder's

Resources

CERTIFICATION REPORTS	eaton-xeffect-ci-certificate-of-compliance-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-empty-enclosure-declaration-of-conformity-eu250306en.pdf
DRAWINGS	eaton-enclosures-enclosure-xenergy-safety-ci-base-dimensions-002.eps eaton-enclosures-base-xeffect-ci-3d-drawing.eps 05670392.pdf
INSTALLATION INSTRUCTIONS	eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf
INSTALLATION VIDEOS	xEffect CI stand-alone polycarbonate enclosure
MCAD MODEL	eaton-front-access-switchboard-mcad-drawings-u-ci43x.dwg u ci43x.stp

CREEPAGE DISTANCES	responsibility.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Protection class 2, therefore not applicable.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Ui = 1000 V AC
10.9.3 IMPULSE WITHSTAND VOLTAGE	8 kV
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Meets the product standard's requirements.
ACCESSORY/SPARE PART TYPE	Individual enclosure bottoms
DEGREE OF PROTECTION	IP65 IK10 Other
ENCLOSURE MATERIAL	Plastic
SURFACE PROTECTION	Other
CIRCUIT INTEGRITY	Other
BASE TYPE	Plain
UNIT TYPE	Modular system
BUILT-IN DEPTH	200 mm
HEAT DISS. AMBIENT 35°C DELTA T:20°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	19 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	17 W
HEAT DISS. AMBIENT 35°C DELTA T:20°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	18 W
HEAT DISS. AMBIENT 35°C DELTA T:35°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	38 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	34 W

HEAT DISS. AMBIENT 35°C DELTA T:35°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	36 W
COLOR	Gray
COVER/DOOR MODEL	Closed
COVER/DOOR TYPE	Optional None
NUMBER OF OPENINGS (FLANGE PLATES)	0
PLATE THICKNESS (CABINET)	9 mm
PLATE THICKNESS (COVER/DOOR)	6 mm
RAL-NUMBER	7035
WIDTH IN NUMBER OF MODULAR SPACINGS	15
CABLE ENTRY TYPE	Top and bottom Drill as required Transverse
MOUNTING METHOD	Surface mounted (plaster)
NUMBER OF ROWS	0
PROTECTION CLASS	II
NUMBER OF MODULES	1
INTERNAL DEPTH	100 mm
NOMINAL CURRENT	1600 A
NUMBER OF CONDUIT INLETS	0
SUITABLE FOR	Outdoor use Lightning protection
ENCLOSURE MATERIAL QUALITY	Other
TYPE OF COATING	Other

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

