

Specifications



Eaton 072894

Eaton Moeller® series NHI Standard auxiliary contact, 2N/O+1N/C, screw connection

General specifications

PRODUCT NAME	Eaton Moeller® series NHI Accessory Standard auxiliary contact
CATALOG NUMBER	072894
MODEL CODE	NHI21-PKZ0
EAN	4015080728948
PRODUCT LENGTH/DEPTH	68 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	15 mm
PRODUCT WEIGHT	0.038 kg
CERTIFICATIONS	CSA Class No.: 3211-05 CE UL 508 CSA-C22.2 No. 14 UL Category Control No.: NLRV IEC/EN 60947-4-1 CSA UL UL File No.: E36332 CSA File No.: 165628
CATALOG NOTES	Can be retrofitted on the right side of motor- protective circuit-breakers

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
--	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

Contacts

CONTROL CIRCUIT RELIABILITY	< 2 λ , < 1 failure at 100,000,000 Operations (at $U_e = 24$ V DC, $U_{min} =$ 17 V, $I_{min} = 5.4$ mA)
--	---

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
--	---

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
--	---

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	2
--	---

Design verification

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 3.5 A

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS 0 W

10.10 TEMPERATURE RISE The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 SHORT-CIRCUIT RATING Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 ELECTROMAGNETIC COMPATIBILITY Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 MECHANICAL FUNCTION The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 CORROSION RESISTANCE Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES Meets the product standard's requirements.

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION Meets the product standard's requirements.

10.2.5 LIFTING Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS Meets the product

Electrical rating

RATED OPERATIONAL CURRENT (IE) 1 A at AC-15, 440 V 500 V

RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V 3.5 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V 2 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V 0.5 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V 0.25 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V 2 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V 1 A

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX 500 V

RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX 250 V

SAFE ISOLATION 440 V, Between auxiliary contacts and main contacts, According to EN 61140

SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING 10 A gG/gL, Fuse, Auxiliary contacts

	standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.04 W

Features & functions

FEATURES	Interlocked opposing contacts
-----------------	-------------------------------

General information

ELECTRIC CONNECTION TYPE	Screw connection
LIFESPAN, ELECTRICAL	50,000 Operations
MODEL	Top mounting
MOUNTING METHOD	Side mounting
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Accessories
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
USED WITH	Motor protective circuit-breaker

Switching capacity

SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	5 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA)
---	--

SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	Q300, DC operated (UL/CSA) A600, AC operated (UL/CSA)
--	--

Terminal capacities

TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE)	0.75 - 1.5 mm ²
--	----------------------------

TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14, Screw terminals
---	--------------------------

Resources

BROCHURES	eaton-push-in-technology-product-overview-brochure-br034012-en-us.pdf
	eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf
CATALOGUES	Product Range Catalog Switching and protecting motors
	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-motorstarters-auxiliary-contact-nhi-accessory-characteristic-curve-005.eps
DECLARATIONS OF CONFORMITY	eaton-accessory-declaration-of-conformity-eu250671en.pdf
	eaton-accessory-declaration-of-conformity-uk251154en.pdf
DRAWINGS	eaton-manual-motor-starters-auxiliary-contact-nhi-accessory-dimensions-002.eps
	eaton-manual-motor-starters-auxiliary-contact-nhi-accessory-3d-drawing-005.eps
	eaton-manual-motor-starters-auxiliary-contact-nhi-accessory-3d-drawing-003.eps
ECAD MODEL	ETN.072894.edz
INSTALLATION INSTRUCTIONS	eaton-front-mounted-auxiliary-contact-nhi-il03801004z.pdf
	IL03407011Z.pdf
	IL03402034Z
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MCAD MODEL	eaton-contact-blocks-mcad-drawings-nhi-pkz0.dwg
	DA-CS-nhi_pkz0

PEP ECO-PASSPORT	eaton-contact-blocks-pep-eato-00347-v0101-en.pdf
SALES NOTES	eaton-link-module-for-motor-starters-pkz-flyer-fl034003en-en-us.pdf
WIRING DIAGRAMS	eaton-manual-motor-starters-contact-nhi-accessory-wiring-diagram.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

