

# Specifications



## Eaton 074440

Eaton Moeller® series T0 Changeover switch, 20 A, service distr. board mounting, 1 contact unit, Contacts: 2, 60 °, maintained, 0 (Off) position, 1-0-2, Design no. 8210

### General specifications

|                     |                                            |
|---------------------|--------------------------------------------|
| <b>PRODUCT NAME</b> | Eaton Moeller® series T0 Changeover switch |
|---------------------|--------------------------------------------|

|                       |        |
|-----------------------|--------|
| <b>CATALOG NUMBER</b> | 074440 |
|-----------------------|--------|

|                   |               |
|-------------------|---------------|
| <b>MODEL CODE</b> | T0-1-8210/IVS |
|-------------------|---------------|

|            |               |
|------------|---------------|
| <b>EAN</b> | 4015080744405 |
|------------|---------------|

|                             |       |
|-----------------------------|-------|
| <b>PRODUCT LENGTH/DEPTH</b> | 82 mm |
|-----------------------------|-------|

|                       |       |
|-----------------------|-------|
| <b>PRODUCT HEIGHT</b> | 55 mm |
|-----------------------|-------|

|                      |       |
|----------------------|-------|
| <b>PRODUCT WIDTH</b> | 54 mm |
|----------------------|-------|

|                       |          |
|-----------------------|----------|
| <b>PRODUCT WEIGHT</b> | 0.106 kg |
|-----------------------|----------|

|                       |                                                                                                                                                                                                                                                           |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>CERTIFICATIONS</b> | UL File No.: E36332<br>UL<br>IEC/EN 60204<br>CSA-C22.2 No. 60947-4-1-14<br>IEC/EN 60947<br>CSA-C22.2 No. 94<br>VDE 0660<br>CE<br>UL Category Control No.: NLRV<br>CSA File No.: 012528<br>CSA<br>UL 60947-4-1<br>CSA Class No.: 3211-05<br>IEC/EN 60947-3 |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                      |                                                                 |
|----------------------|-----------------------------------------------------------------|
| <b>CATALOG NOTES</b> | Rated Short-time Withstand Current (Icw) for a time of 1 second |
|----------------------|-----------------------------------------------------------------|

## Actuator

|                          |                                     |
|--------------------------|-------------------------------------|
| <b>ACTUATOR FUNCTION</b> | With 0 (Off) position<br>Maintained |
| <b>ACTUATOR TYPE</b>     | Short thumb-grip                    |

## Contacts

|                                                                |                                                                                                  |
|----------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| <b>CONTROL CIRCUIT RELIABILITY</b>                             | 1 failure per 100,000<br>switching operations<br>statistically determined, at<br>24 V DC, 10 mA) |
| <b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>     | 0                                                                                                |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b> | 0                                                                                                |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>   | 0                                                                                                |
| <b>NUMBER OF CONTACTS</b>                                      | 2                                                                                                |

## Climatic environmental conditions

|                                                       |                                                                                      |
|-------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>            | 50 °C                                                                                |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>            | -25 °C                                                                               |
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b> | 40 °C                                                                                |
| <b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b> | -25 °C                                                                               |
| <b>CLIMATIC PROOFING</b>                              | Damp heat, constant, to<br>IEC 60068-2-78<br>Damp heat, cyclic, to IEC<br>60068-2-30 |

## Design verification

|                                                                                         |                                                                                                                                  |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>10.10 TEMPERATURE RISE</b>                                                           | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>                                                       | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>                                              | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>                                                        | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                                                                                       |

|                                                                      |                                                                    |
|----------------------------------------------------------------------|--------------------------------------------------------------------|
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>              | Meets the product standard's requirements.                         |
| <b>10.2.5 LIFTING</b>                                                | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.2.6 MECHANICAL IMPACT</b>                                      | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.2.7 INSCRIPTIONS</b>                                           | Meets the product standard's requirements.                         |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                       | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                        | Meets the product standard's requirements.                         |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                        | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>        | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>             | Is the panel builder's responsibility.                             |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                      | Is the panel builder's responsibility.                             |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                      | Is the panel builder's responsibility.                             |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                              | Is the panel builder's responsibility.                             |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>      | Is the panel builder's responsibility.                             |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>            | 0 W                                                                |
| <b>HEAT DISSIPATION CAPACITY PDISS</b>                               | 0 W                                                                |
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>             | 0.6 W                                                              |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 20 A                                                               |
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>            | 0 W                                                                |

## Electrical rating

|                                                                              |       |
|------------------------------------------------------------------------------|-------|
| <b>RATED BREAKING<br/>CAPACITY AT 220/230 V<br/>(COS PHI TO IEC 60947-3)</b> | 100 A |
|------------------------------------------------------------------------------|-------|

|                                                                              |       |
|------------------------------------------------------------------------------|-------|
| <b>RATED BREAKING<br/>CAPACITY AT 400/415 V<br/>(COS PHI TO IEC 60947-3)</b> | 110 A |
|------------------------------------------------------------------------------|-------|

|                                                                          |      |
|--------------------------------------------------------------------------|------|
| <b>RATED BREAKING<br/>CAPACITY AT 500 V (COS<br/>PHI TO IEC 60947-3)</b> | 80 A |
|--------------------------------------------------------------------------|------|

|                                                                              |      |
|------------------------------------------------------------------------------|------|
| <b>RATED BREAKING<br/>CAPACITY AT 660/690 V<br/>(COS PHI TO IEC 60947-3)</b> | 60 A |
|------------------------------------------------------------------------------|------|

|                                           |                                                                                                                                                         |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE)</b> | 20 A at AC-3, 230 V star-<br>delta<br>8.5 A at AC-3, 690 V star-<br>delta<br>20 A at AC-3, 400 V star-<br>delta<br>15.6 A at AC-3, 500 V star-<br>delta |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                                               |      |
|---------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-21,<br/>440 V</b> | 20 A |
|---------------------------------------------------------------|------|

|                                                                |        |
|----------------------------------------------------------------|--------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-23A,<br/>230 V</b> | 13.3 A |
|----------------------------------------------------------------|--------|

|                                                                       |        |
|-----------------------------------------------------------------------|--------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-23A,<br/>400 V, 415 V</b> | 13.3 A |
|-----------------------------------------------------------------------|--------|

|                                                                |        |
|----------------------------------------------------------------|--------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-23A,<br/>500 V</b> | 13.3 A |
|----------------------------------------------------------------|--------|

|                                                                |       |
|----------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-23A,<br/>690 V</b> | 7.6 A |
|----------------------------------------------------------------|-------|

|                                                                            |        |
|----------------------------------------------------------------------------|--------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-3,<br/>220 V, 230 V, 240 V</b> | 11.5 A |
|----------------------------------------------------------------------------|--------|

|                                                                            |        |
|----------------------------------------------------------------------------|--------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-3,<br/>380 V, 400 V, 415 V</b> | 11.5 A |
|----------------------------------------------------------------------------|--------|

|                                                              |     |
|--------------------------------------------------------------|-----|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-3,<br/>500 V</b> | 9 A |
|--------------------------------------------------------------|-----|

|                                                                     |       |
|---------------------------------------------------------------------|-------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT AC-3,<br/>660 V, 690 V</b> | 4.9 A |
|---------------------------------------------------------------------|-------|

|                                                                                           |      |
|-------------------------------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-1,<br/>LOAD-BREAK SWITCHES<br/>L/R = 1 MS</b> | 10 A |
|-------------------------------------------------------------------------------------------|------|

|                          |      |
|--------------------------|------|
| <b>RATED OPERATIONAL</b> | 10 A |
|--------------------------|------|

## Features & functions

|                           |         |
|---------------------------|---------|
| <b>ENCLOSURE MATERIAL</b> | Plastic |
|---------------------------|---------|

|                     |                                                         |
|---------------------|---------------------------------------------------------|
| <b>FITTED WITH:</b> | 0 (off) position<br>Black thumb grip and<br>front plate |
|---------------------|---------------------------------------------------------|

|                    |       |
|--------------------|-------|
| <b>INSCRIPTION</b> | 1-0-2 |
|--------------------|-------|

|                        |   |
|------------------------|---|
| <b>NUMBER OF POLES</b> | 1 |
|------------------------|---|

|                                                                       |        |
|-----------------------------------------------------------------------|--------|
| <b>CURRENT (IE) AT DC-13,<br/>CONTROL SWITCHES L/R<br/>= 50 MS</b>    |        |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-21,<br/>240 V</b>         | 1 A    |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>120 V</b>        | 5 A    |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>24 V</b>         | 10 A   |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>240 V</b>        | 5 A    |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>48 V</b>         | 10 A   |
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-23A,<br/>60 V</b>         | 10 A   |
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A,<br/>220/230 V, 50 HZ</b>    | 3 kW   |
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 400 V,<br/>50 HZ</b>        | 5.5 kW |
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 500 V,<br/>50 HZ</b>        | 7.5 kW |
| <b>RATED OPERATIONAL<br/>POWER AT AC-23A, 690 V,<br/>50 HZ</b>        | 5.5 kW |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 380/400<br/>V, 50 HZ</b>      | 4 kW   |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 415 V, 50<br/>HZ</b>          | 5.5 kW |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 690 V, 50<br/>HZ</b>          | 4 kW   |
| <b>RATED OPERATIONAL<br/>POWER STAR-DELTA AT<br/>220/230 V, 50 HZ</b> | 5.5 kW |
| <b>RATED OPERATIONAL<br/>POWER STAR-DELTA AT<br/>380/400 V, 50 HZ</b> | 7.5 kW |
| <b>RATED OPERATIONAL<br/>POWER STAR-DELTA AT<br/>500 V, 50 HZ</b>     | 7.5 kW |
| <b>RATED OPERATIONAL<br/>POWER STAR-DELTA AT</b>                      | 5.5 kW |

|                                                   |                                                                     |
|---------------------------------------------------|---------------------------------------------------------------------|
| <b>690 V, 50 HZ</b>                               |                                                                     |
| <b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b> | 690 V                                                               |
| <b>RATED UNINTERRUPTED CURRENT (IU)</b>           | 20 A                                                                |
| <b>UNINTERRUPTED CURRENT</b>                      | Rated uninterrupted current Iu is specified for max. cross-section. |

| General information                           |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>DEGREE OF PROTECTION</b>                   | IP30                                                                                                                            |
| <b>DEGREE OF PROTECTION (FRONT SIDE)</b>      | IP30<br>NEMA 2                                                                                                                  |
| <b>LIFESPAN, MECHANICAL</b>                   | 400,000 Operations                                                                                                              |
| <b>MODEL</b>                                  | Reverser                                                                                                                        |
| <b>MOUNTING METHOD</b>                        | Service distribution board mounting                                                                                             |
| <b>MOUNTING POSITION</b>                      | As required                                                                                                                     |
| <b>NUMBER OF CONTACT UNITS</b>                | 1                                                                                                                               |
| <b>OPERATING FREQUENCY</b>                    | 1200 Operations/h                                                                                                               |
| <b>OVERVOLTAGE CATEGORY</b>                   | III                                                                                                                             |
| <b>POLLUTION DEGREE</b>                       | 3                                                                                                                               |
| <b>PRODUCT CATEGORY</b>                       | Control switches                                                                                                                |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b> | 6000 V AC                                                                                                                       |
| <b>SAFE ISOLATION</b>                         | 440 V AC, Between the contacts, According to EN 61140                                                                           |
| <b>SAFETY PARAMETER (EN ISO 13849-1)</b>      | B10d values as per EN ISO 13849-1, table C.1                                                                                    |
| <b>SHOCK RESISTANCE</b>                       | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms                                                   |
| <b>SUITABLE FOR</b>                           | Branch circuits, suitable as motor disconnect, (UL/CSA)<br>Ground mounting<br>Distribution board installation<br>Front mounting |
| <b>SWITCHING ANGLE</b>                        | 60 °                                                                                                                            |
| <b>TYPE</b>                                   | Changeover switch                                                                                                               |

| Motor rating                                             |        |
|----------------------------------------------------------|--------|
| <b>ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE</b> | 0.5 HP |
| <b>ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 1-PHASE</b> | 1 HP   |
| <b>ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE</b> | 3 HP   |
| <b>ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE</b> | 1.5 HP |
| <b>ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE</b> | 3 HP   |
| <b>ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE</b> | 7.5 HP |
| <b>ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE</b> | 7.5 HP |

## Short-circuit rating

**RATED CONDITIONAL  
SHORT-CIRCUIT CURRENT (IQ)** 6 kA

**RATED SHORT-TIME  
WITHSTAND CURRENT (ICW)** 320 A, Contacts, 1 second

**SHORT-CIRCUIT CURRENT  
RATING (BASIC RATING)** 5 kA, SCCR (UL/CSA)  
50A, max. Fuse, SCCR  
(UL/CSA)

**SHORT-CIRCUIT CURRENT  
RATING (HIGH FAULT)** 20 A, Class J, max. Fuse,  
SCCR (UL/CSA)  
10 kA, SCCR (UL/CSA)

**SHORT-CIRCUIT  
PROTECTION RATING** 20 A gG/gL, Fuse, Contacts

## Switching capacity

**LOAD RATING** 1.3 x I<sub>e</sub> (with intermittent  
operation class 12, 60 %  
duty factor)  
2 x I<sub>e</sub> (with intermittent  
operation class 12, 25 %  
duty factor)  
1.6 x I<sub>e</sub> (with intermittent  
operation class 12, 40 %  
duty factor)

**NUMBER OF CONTACTS  
IN SERIES AT DC-21A, 240  
V** 1

**NUMBER OF CONTACTS  
IN SERIES AT DC-23A, 120  
V** 3

**NUMBER OF CONTACTS  
IN SERIES AT DC-23A, 24 V** 1

**NUMBER OF CONTACTS  
IN SERIES AT DC-23A, 240  
V** 5

**NUMBER OF CONTACTS  
IN SERIES AT DC-23A, 48 V** 2

**NUMBER OF CONTACTS  
IN SERIES AT DC-23A, 60 V** 3

**RATED MAKING  
CAPACITY UP TO 690 V  
(COS PHI TO IEC/EN  
60947-3)** 130 A

**SWITCHING CAPACITY  
(AUXILIARY CONTACTS,  
GENERAL USE)** 10A, IU, (UL/CSA)

**SWITCHING CAPACITY  
(AUXILIARY CONTACTS,  
PILOT DUTY)** A600 (UL/CSA)  
P300 (UL/CSA)

**SWITCHING CAPACITY  
(MAIN CONTACTS,  
GENERAL USE)** 16 A, Rated uninterrupted  
current max. (UL/CSA)

**VOLTAGE PER CONTACT  
PAIR IN SERIES** 60 V

## Terminal capacities

|                                                                    |                                                                                                                            |
|--------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| <b>SCREW SIZE</b>                                                  | M3.5, Terminal screw                                                                                                       |
| <b>TERMINAL CAPACITY<br/>(FLEXIBLE WITH<br/>FERRULE)</b>           | 2 x (0.75 - 2.5) mm <sup>2</sup> ,<br>ferrules to DIN 46228<br>1 x (0.75 - 2.5) mm <sup>2</sup> ,<br>ferrules to DIN 46228 |
| <b>TERMINAL CAPACITY<br/>(SOLID/FLEXIBLE WITH<br/>FERRULE AWG)</b> | 18 - 14                                                                                                                    |
| <b>TERMINAL CAPACITY<br/>(SOLID/STRANDED)</b>                      | 2 x (1 - 2.5) mm <sup>2</sup><br>1 x (1 - 2.5) mm <sup>2</sup>                                                             |
| <b>TIGHTENING TORQUE</b>                                           | 1 Nm, Screw terminals<br>8.8 lb-in, Screw terminals                                                                        |

## Resources

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BROCHURES                        | <a href="#">Brochure - T Rotary Cam switch and P Switch-disconnector</a>                                                                                                                                                                                                                                                                                                                                                     |
| CATALOGUES                       | <a href="#">P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN</a>                                                                                                                                                                                                                                                                                                                                        |
| DECLARATIONS<br>OF<br>CONFORMITY | <a href="#">eaton-step-switch-declaration-of-conformity-eu250844en.pdf</a><br><a href="#">eaton-step-switch-declaration-of-conformity-uk251327en.pdf</a>                                                                                                                                                                                                                                                                     |
| DRAWINGS                         | <a href="#">eaton-rotary-switches-mounting-t0-step-switch-dimensions.eps</a><br><a href="#">eaton-rotary-switches-mounting-t0-step-switch-dimensions-002.eps</a><br><a href="#">eaton-rotary-switches-front-plate-t0-changeover-switch-symbol-009.eps</a><br><a href="#">eaton-rotary-switches-mounting-t0-changeover-switch-3d-drawing.eps</a><br><a href="#">eaton-general-rotary-switch-t0-step-switch-symbol-005.eps</a> |
| ECAD MODEL                       | <a href="#">ETN.074440.edz</a>                                                                                                                                                                                                                                                                                                                                                                                               |
| INSTALLATION<br>INSTRUCTIONS     | <a href="#">IL03801006Z</a>                                                                                                                                                                                                                                                                                                                                                                                                  |
| INSTALLATION<br>VIDEOS           | <a href="#">Eaton's P Switch-disconnectors used in a factory</a>                                                                                                                                                                                                                                                                                                                                                             |
| MCAD MODEL                       | <a href="#">DA-CS-t0_1_ivs</a><br><a href="#">eaton-universal-control-switches-mcad-drawings-t0-1-ivs.dwg</a>                                                                                                                                                                                                                                                                                                                |
| PRODUCT<br>NOTIFICATIONS         | <a href="#">MZ008005ZU_Orderform_Customized_Switch.pdf</a><br><a href="#">MZ008006ZU_Orderform_Customized_Switch.pdf</a>                                                                                                                                                                                                                                                                                                     |
| WIRING<br>DIAGRAMS               | <a href="#">eaton-rotary-switches-changeover-switch-t0-changeover-switch-wiring-diagram.eps</a>                                                                                                                                                                                                                                                                                                                              |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

