

Specifications

Eaton 077227

Eaton xEnergy Safety Ci LV systems LV switchgear. Space unit rail with terminal for fuse enclosure tab RS33/I23, 2x 2.5-35 and 2x 1.5-16mm²

General specifications

PRODUCT NAME	Eaton xEnergy Safety Ci N + PE/N rail
CATALOG NUMBER	077227
MODEL CODE	PEN23RS33
EAN	4015080772279
PRODUCT LENGTH/DEPTH	50 mm
PRODUCT HEIGHT	50 mm
PRODUCT WIDTH	190 mm
PRODUCT WEIGHT	0.102 kg
COMPLIANCES	RoHS conform



Powering Business Worldwide

Additional information

FEATURES	Contact safe
SUITABLE FOR	Useful for stranded conductors
USED WITH	RS33/I23 SE-RS-I23 Modular busbar system Ci insulated enclosure Prepared enclosures

Delivery programme

ACCESSORY/SPARE PART TYPE	PE (PEN) busbars
NOMINAL CURRENT	63 A
NUMBER OF POLES	Single-pole
TYPE	• Ci insulated enclosure • Modular busbar system • Prepared enclosures

Technical data - mechanical

CONDUCTOR CROSS SECTION, INPUT - MAX	35 mm ²
CONDUCTOR CROSS SECTION, INPUT - MIN	2.5 mm ²
CONDUCTOR CROSS SECTION, INPUT AWG - MAX	2 mm ²
CONDUCTOR CROSS SECTION, INPUT AWG - MIN	14 mm ²
CONDUCTOR CROSS SECTION, OUTPUT - MAX	16 mm ²
CONDUCTOR CROSS SECTION, OUTPUT - MIN	1.5 mm ²
CONDUCTOR CROSS SECTION, OUTPUT AWG - MAX	6 mm ²
CONDUCTOR CROSS SECTION, OUTPUT AWG - MIN	16 mm ²
NUMBER OF CONNECTIONS (LESS THAN 6 MM SQUARED)	0
NUMBER OF CONNECTIONS (LESS THAN AWG 6)	0
NUMBER OF CONNECTIONS (GREATER THAN 25 MM SQUARED)	2
NUMBER OF CONNECTIONS (GREATER THAN 250 KCMIL)	0
NUMBER OF CONNECTIONS (10 MM SQUARED)	0
NUMBER OF CONNECTIONS (16 MM SQUARED)	2
NUMBER OF CONNECTIONS (25 MM SQUARED)	0
NUMBER OF CONNECTIONS (250 KCMIL)	0
NUMBER OF CONNECTIONS (AWG 2)	0
NUMBER OF CONNECTIONS (AWG 4)	0
NUMBER OF CONNECTIONS (AWG 4/0)	0

Resources

BROCHURES	eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf
CATALOGUES	eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf IL0713
INSTALLATION INSTRUCTIONS	eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf
SYSTEM OVERVIEW	eaton-xenergy-safety-ci-sytem-overview-461n099.eps

NUMBER OF CONNECTIONS (AWG 6)	0
NUMBER OF CONNECTIONS (TOTAL)	0
NUMBER OF INPUTS	1
NUMBER OF OUTPUTS	3
TERMINAL CAPACITY (SOLID WIRE)	1.5 mm ² - 16 mm ² (2x) 2.5 mm ² - 35 mm ² (2x)
TERMINAL CAPACITY (STRANDED CABLE)	1.5 mm ² - 16 mm ² (2x) 2.5 mm ² - 25 mm ² (2x)
UNIT TYPE	Modular system
CONNECTION TYPE	Clamp Screwing
MOUNTING METHOD	Screw

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

