

Specifications



Photo is representative

Eaton 081167

Eaton xEffect Multi-Layer Copper Band Enclosures Switch- & Controlgear Enclosure. Copper strip, tinned, 100A, 3x9x0.8mm, black

General specifications

PRODUCT NAME	Eaton xEffect Multi-Layer Copper Band Enclosures Switch- & Controlgear Enclosure
CATALOG NUMBER	081167
MODEL CODE	CU-BAND3X9X0,8-BK
EAN	4015080811671
PRODUCT LENGTH/DEPTH	2000 mm
PRODUCT HEIGHT	6 mm
PRODUCT WIDTH	15 mm
PRODUCT WEIGHT	0.518 kg
COMPLIANCES	EN 60439-1 UL CSA09 (max. 105 °C) UL 758 CE marking EN 60439-3 RoHS conform
CERTIFICATIONS	UL (File No. E248096) UL (Category Control Number AVL2) North America (UL listed, certified by UL for use in Canada)



Powering Business Worldwide

Product specifications

USED WITH	Appliance wiring material Copper band isolated
SPECIAL FEATURES	- E-Cu laminated conductor, tin-plated - UL approved up to max. 600 V AC - Insulating material heat resistant up to +105 °C
TYPE	General switchboard accessory
FEATURES	Laminated Self-extinguishing acc. UL 94 V0
ACCESSORY/SPARE PART TYPE	Copper band insulated
VOLTAGE RATING	1000 V AC, 1500 V DC
VOLTAGE RATING (UL CSA 13)	Max. 600 V AC, 750 V DC
BUSBAR THICKNESS	6.4 mm
CROSS SECTION	21.6 mm ²
LAMELLA THICKNESS	0.8 mm
NUMBER OF FUSE HOLDERS (KNIFE BLADE)	3
AMPERAGE RATING	100 A
COLOR	Black, similar to RAL 9005
DIELECTRIC STRENGTH	20 kV/mm
DIMENSIONS - BAND SPECIFICATION	3 mm x 9 mm x 0.8 mm
RATED OPERATION CURRENT (IE)	100 A

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Resources

CATALOGUES	eaton-panel-building-accessories-catalog-ca008008en-en-us.pdf
DRAWINGS	eaton-distribution-boards-xeffect-multi-layer-copper-band-3d-drawing.eps
TECHNICAL DATA SHEETS	eaton-xeffect-sasy-60i-fk4300-1167gb-en-us.pdf



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

