

Specifications

Eaton 082884



Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, Can be fitted to the front, Screw terminals



General specifications

PRODUCT NAME	Eaton Moeller® series NHI Accessory Standard auxiliary contact
CATALOG NUMBER	082884
MODEL CODE	NHI-E-10-PKZ0
EAN	4015080828846
PRODUCT LENGTH/DEPTH	12 mm
PRODUCT HEIGHT	35 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.011 kg
CERTIFICATIONS	CE CSA File No.: 165628 CSA IEC/EN 60947-4-1 UL Category Control No.: NLRV CSA Class No.: 3211-05 CSA-C22.2 No. 14 UL File No.: E36332 UL UL 508
CATALOG NOTES	Can be fitted to the front. Terminal designation differs to that of an auxiliary contact that can be fitted to the side

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	55 °C
--	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

Contacts

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
---	---

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	0
---	---

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
---	---

Design verification

**RATED OPERATIONAL
CURRENT FOR SPECIFIED
HEAT DISSIPATION (IN)** 1 A

**STATIC HEAT
DISSIPATION, NON-
CURRENT-DEPENDENT
PVS** 0 W

10.10 TEMPERATURE RISE The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

**10.11 SHORT-CIRCUIT
RATING** Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC
COMPATIBILITY** Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL
FUNCTION** The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

**10.2.2 CORROSION
RESISTANCE** Meets the product standard's requirements.

**10.2.3.1 VERIFICATION OF
THERMAL STABILITY OF
ENCLOSURES** Meets the product standard's requirements.

**10.2.3.2 VERIFICATION OF
RESISTANCE OF
INSULATING MATERIALS
TO NORMAL HEAT** Meets the product standard's requirements.

**10.2.3.3 RESIST. OF
INSUL. MAT. TO
ABNORMAL HEAT/FIRE
BY INTERNAL ELECT.
EFFECTS** Meets the product standard's requirements.

**10.2.4 RESISTANCE TO
ULTRA-VIOLET (UV)
RADIATION** Meets the product standard's requirements.

10.2.5 LIFTING Does not apply, since the entire switchgear needs to be evaluated.

**10.2.6 MECHANICAL
IMPACT** Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS Meets the product

Electrical rating

**RATED OPERATIONAL
CURRENT (IE) AT AC-15,
220 V, 230 V, 240 V** 1 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-13,
24 V** 2 A

**RATED OPERATIONAL
VOLTAGE (UE) AT AC -
MAX** 440 V

**RATED OPERATIONAL
VOLTAGE (UE) AT DC -
MAX** 250 V

SAFE ISOLATION 440 V, Between auxiliary contacts and main contacts, According to EN 61140

**SHORT-CIRCUIT
PROTECTION RATING
WITHOUT WELDING** 10 A gG/gL, Fuse, Auxiliary contacts

	standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.01 W

General information

ELECTRIC CONNECTION TYPE	Screw connection
LIFESPAN, ELECTRICAL	50,000 Operations
LIFESPAN, MECHANICAL	50,000 operations
MODEL	Top mounting
MOUNTING METHOD	Front fastening
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Accessories
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
USED WITH	Motor protective circuit-breaker

Terminal capacities

TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE)	0.75 - 1.5 mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 16, Screw terminals

Switching capacity

SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	0.5 A, 250 V DC, (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	E150, AC operated (UL/CSA)

Resources

	eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf
BROCHURES	eaton-push-in-technology-product-overview-brochure-br034012-en-us.pdf
CATALOGUES	Product Range Catalog Switching and protecting motors eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-motorstarters-auxiliary-contact-nhi-accessory-characteristic-curve-007.eps
DECLARATIONS OF CONFORMITY	eaton-accessory-declaration-of-conformity-uk251154en.pdf eaton-accessory-declaration-of-conformity-eu250671en.pdf
DRAWINGS	eaton-manual-motor-starters-pkz-dimensions-003.eps eaton-manual-motor-starters-pkz0-accessory-dimensions.eps

	eaton-manual-motor-starters-auxiliary-contact-nhi-accessory-3d-drawing-002.eps
	eaton-manual-motor-starters-auxiliary-contact-nhi-accessory-3d-drawing-005.eps
ECAD MODEL	ETN.082884.edz
INSTALLATION INSTRUCTIONS	eaton-front-mounted-auxiliary-contact-nhi-il03801004z.pdf
INSTALLATION VIDEOS	WIN-WIN with push-in technology
	nhi_e_1.stp
MCAD MODEL	eaton-contact-blocks-mcad-drawings-nhi-e.dwg
PEP ECO-PASSPORT	eaton-contact-blocks-pep-eato-00406-v0101-en.pdf
SALES NOTES	eaton-link-module-for-motor-starters-pkz-flyer-fl034003en-en-us.pdf
WIRING DIAGRAMS	eaton-manual-motor-starters-auxiliary-contact-nhi-accessory-wiring-diagram-004.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

