

Specifications



Eaton 101440

Eaton Moeller® series DILM Timer module, 24VAC/DC, 0.1-100s, on-delayed

General specifications

PRODUCT NAME	Eaton Moeller® series DILM timer module
CATALOG NUMBER	101440
MODEL CODE	DILM32-XTEE11(RA24)
EAN	4015081013609
PRODUCT LENGTH/DEPTH	86 mm
PRODUCT HEIGHT	38 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.073 kg
CERTIFICATIONS	CSA File No.: 012528 IEC/EN 60947 IEC/EN 60947-4-1 UL UL Category Control No.: NKCR UL File No.: E29184 CSA CSA-C22.2 No. 14-05 UL 508 VDE 0660 CE DIN EN 61812 CSA Class No.: 3211-03
CATALOG NOTES	Cannot be combined with top mounting auxiliary contacts

Ambient conditions, mechanical

MOUNTING POSITION	As required (except suspended)
SHOCK RESISTANCE	6 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 6 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Contacts

CONTACT CHANGEOVER TIME	50 ms
NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1

Conventional thermal current I_{th}

CONVENTIONAL THERMAL CURRENT I_{TH} OF AUXILIARY CONTACTS (1-POLE, OPEN)	4 A
---	-----

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Electrical rating

RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL CURRENT (IE)	0.2 A at 110 V, DC-13 L/R - 50 ms (with 1 contact in series) 1 A at 24 V, DC-13 L/R - 300 ms (with 1 contact in series) 0.2 A at 60 V, DC-13 L/R - 300 ms (with 1 contact in series) 1 A at 24 V, DC-13 L/R - 50 ms (with 1 contact in series) 0.2 A at 110 V, DC-13 L/R - 300 ms (with 1 contact in series) 0.2 A at 60 V, DC-13 L/R - 50 ms (with 1 contact in series) 0.1 A at 220 V, DC-13 L/R - 50 ms (with 1 contact in series) 3 A at AC-15, 220 V 230 V 240 V 0.1 A at 220 V, DC-13 L/R - 300 ms (with 1 contact in series)
RATED OPERATIONAL VOLTAGE (UE) - MAX	250 V

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	1.8 W

Features & functions

FITTED WITH:	Suppressor circuits
OPERATING MODE	Electronic
SWITCH FUNCTION TYPE	Operating delayed

General information

DEGREE OF PROTECTION	IP20
DELAY TIME	200 ms, Off-delayed 50 ms, On-delayed
LIFESPAN, MECHANICAL	3,000,000 Operations (AC operated) 3,000,000 Operations (DC operated)
OPERATING FREQUENCY	3600 Operations/h 360 mechanical Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Accessories
PROTECTION	Finger and back-of-hand

	proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
RECOVERY TIME	70 ms (after 100 % time delay)
REPETITION ACCURACY	< 5 % (deviation)
TIME RANGE - MAX	100 s
TIME RANGE - MIN	0.05 s

Magnet system

DUTY FACTOR	100 %
PICK-UP VOLTAGE	0.85 - 1.1 V AC x Uc 0.7 - 1.2 V DC x Uc
POWER CONSUMPTION (SEALING) AT DC	1.8 W
POWER CONSUMPTION, SEALING, 50 HZ	2 VA, Coil in a cold state and 1.0 x Us
POWER CONSUMPTION, SEALING, 60 HZ	2 VA, Coil in a cold state and 1.0 x Us
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	24 V

Safety

SAFE ISOLATION	250 V AC, Between auxiliary contacts, According to EN 61140 250 V AC, Between coil and auxiliary contacts, According to EN 61140
-----------------------	---

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (BASIC RATING)	125 A, max. CB, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA) 125 A, max. Fuse, SCCR (UL/CSA)
--	---

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 480 V)	50/32 A, max. CB, SCCR (UL/CSA) 10/65 kA, CB, SCCR (UL/CSA) 125/70 A, Class J, max. Fuse, SCCR (UL/CSA) 10/100 kA, Fuse, SCCR (UL/CSA)
---	---

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	10/22 kA, CB, SCCR (UL/CSA) 10/100 kA, Fuse, SCCR (UL/CSA) 125/125 A, Class J, max. Fuse, SCCR (UL/CSA) 50/32 A, max. CB, SCCR (UL/CSA)
---	--

SHORT-CIRCUIT PROTECTION RATING	Max. 4 A gG/gL, fuse, Without welding, Auxiliary and control circuits
--	---

Terminal capacities

SCREW SIZE	M3.5, Terminal screw, Control circuit cables
SCREWDRIVER SIZE	2, Terminal screw, Pozidriv screwdriver 0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver
TERMINAL CAPACITY (SOLID)	2 x (0.75 - 1.5) mm ² 1 x (0.75 - 2.5) mm ²
TIGHTENING TORQUE	1.2 Nm, Screw terminals
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.75 - 1.5) mm ² 2 x (0.75 - 1.5) mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14

Switching capacity

SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	5 A, 240 V AC, (UL/CSA) 5 A, 24 V DC, (UL/CSA)
---	---

SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	R300, DC operated (UL/CSA) B300, AC operated (UL/CSA)
--	--

Resources

	Product Range Catalog Switching and protecting motors
CATALOGUES	SmartWire-DT Catalog eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-accessory-declaration-of-conformity-uk251284en.pdf eaton-accessory-declaration-of-conformity-eu250801en.pdf
DRAWINGS	eaton-electronic-timers-module-dilm-timer-module-dimensions.eps eaton-electronic-timers-module-dilm-timer-module-3d-drawing.eps
ECAD MODEL	ETN.101440.edz
INSTALLATION INSTRUCTIONS	IL04910004Z2021_07.pdf

INSTALLATION VIDEOS	WIN-WIN with push-in technology dilm32_xte11.stp
MCAD MODEL	eaton-electronic-timers-mcad-drawings-dilm32-xte11.dwg
WIRING DIAGRAMS	eaton-electronic-timers-module-dilm-timer-module-wiring-diagram.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

