

# Specifications



## Eaton 102382

Eaton xEnergy Basic LV systems Low voltage switchgear. White floor standing distribution board with locking rotary lever, W = 1000 mm, H = 2060 mm, D = 300 mm

### General specifications

|                             |                                     |
|-----------------------------|-------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton xEnergy Basic empty enclosure |
| <b>CATALOG NUMBER</b>       | 102382                              |
| <b>MODEL CODE</b>           | BP-F-1000/20/3-P-W                  |
| <b>EAN</b>                  | 4015081022700                       |
| <b>PRODUCT LENGTH/DEPTH</b> | 300 mm                              |
| <b>PRODUCT HEIGHT</b>       | 2060 mm                             |
| <b>PRODUCT WIDTH</b>        | 1000 mm                             |
| <b>PRODUCT WEIGHT</b>       | 68.5 kg                             |
| <b>COMPLIANCES</b>          | RoHS conform                        |



Powering Business Worldwide

## Additional information

|                     |                                                |
|---------------------|------------------------------------------------|
| <b>FEATURES</b>     | Mounting plate depth-adjustable<br>EMC-version |
| <b>FITTED WITH:</b> | Door                                           |
| <b>FUNCTIONS</b>    | Basic device                                   |
| <b>RAL-NUMBER</b>   | 9016                                           |
| <b>SUITABLE FOR</b> | Metrical mounting                              |

## Delivery programme

|                    |                                   |
|--------------------|-----------------------------------|
| <b>APPLICATION</b> | Indoor (installation site)        |
| <b>COLOR</b>       | White<br>Traffic white (RAL 9016) |
| <b>TYPE</b>        | Basic device                      |

## Design verification to IEC/EN 61439

|                                                                                         |                                                                                                                                  |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>10.10 TEMPERATURE RISE</b>                                                           | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>                                                       | Is the panel builder's responsibility.                                                                                           |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>                                              | Is the panel builder's responsibility.                                                                                           |
| <b>10.13 MECHANICAL FUNCTION</b>                                                        | Meets the product standard's requirements.                                                                                       |
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                                                                                       |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Not relevant to indoor installations.                                                                                            |
| <b>10.2.5 LIFTING</b>                                                                   | Met; assembled and secured as per the latest applicable instruction leaflet.                                                     |
| <b>10.2.6 MECHANICAL IMPACT</b>                                                         | IK08                                                                                                                             |
| <b>10.2.7 INSCRIPTIONS</b>                                                              | Meets the product standard's requirements.                                                                                       |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                                          | IP30                                                                                                                             |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                                           | Is the panel builder's responsibility.                                                                                           |
| <b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>                                           | < 0.1 Ω; meets the product standard's requirements.                                                                              |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>                           | Is the panel builder's responsibility.                                                                                           |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>                                | Is the panel builder's responsibility.                                                                                           |

## Technical data - mechanical

|                                  |                                                   |
|----------------------------------|---------------------------------------------------|
| <b>COVER/DOOR TYPE</b>           | Rotary lever                                      |
| <b>GRADE MATERIAL</b>            | Sheet steel                                       |
| <b>INSTALLATION TYPE</b>         | Floor installation possible                       |
| <b>MATERIAL</b>                  | Sheet steel<br>Steel                              |
| <b>MOUNTING METHOD</b>           | Floor standing distribution board<br>Detached     |
| <b>NUMBER OF CONNECTOR HOLES</b> | 0                                                 |
| <b>NUMBER OF COVERS/DOORS</b>    | 2                                                 |
| <b>NUMBER OF LOCKS</b>           | 0                                                 |
| <b>SURFACE FINISHING</b>         | Powder coating<br>With powder coating             |
| <b>DEGREE OF PROTECTION</b>      | IP30<br>IK08 (impact resistance)<br>Other<br>IK08 |

|                                                                 |                                        |
|-----------------------------------------------------------------|----------------------------------------|
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility. |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Ui = 440 V AC                          |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | 4 kV                                   |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Does not apply to metal enclosures.    |

## Temperature-rise verification as per IEC 60890

HEAT DISS. AMBIENT  
35°C DELTA T: 20°C FREE  
STAND MIDDLE ENCL.  
TOP (IEC 60890) 237 W

HEAT DISS. AMBIENT  
35°C DELTA T: 20°C WALL  
MOUNT MIDDLE ENCL.  
TOP (IEC 60890) 214 W

HEAT DISS. AMBIENT  
35°C DELTA T: 35°C FREE  
STAND MIDDLE ENCL.  
TOP (IEC 60890) 475 W

HEAT DISS. AMBIENT  
35°C DELTA T: 35°C WALL  
MOUNT MIDDLE ENCL.  
TOP (IEC 60890) 428 W

HEAT DISS. AMBIENT  
35°C DELTA T: 20°C FREE  
STAND INDIVID. ENCL.  
TOP (IEC 60890) 255 W

HEAT DISS. AMBIENT  
35°C DELTA T: 20°C FREE  
STAND STARTING ENCL.  
TOP (IEC 60890) 245 W

HEAT DISS. AMBIENT  
35°C DELTA T: 20°C WALL  
MOUNT INDIVID. ENCL.  
TOP (IEC 60890) 222 W

HEAT DISS. AMBIENT  
35°C DELTA T: 20°C WALL  
MOUNT STARTING ENCL.  
TOP (IEC 60890) 217 W

HEAT DISS. AMBIENT  
35°C DELTA T: 35°C FREE  
STAND INDIVID. ENCL.  
TOP (IEC 60890) 511 W

HEAT DISS. AMBIENT  
35°C DELTA T: 35°C FREE  
STAND STARTING ENCL.  
TOP (IEC 60890) 492 W

HEAT DISS. AMBIENT  
35°C DELTA T: 35°C WALL  
MOUNT INDIVID. ENCL.  
TOP (IEC 60890) 445 W

HEAT DISS. AMBIENT  
35°C DELTA T: 35°C WALL  
MOUNT STARTING ENCL.  
TOP (IEC 60890) 435 W

## Resources

|                            |                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------|
| BROCHURES                  | <a href="#">eaton-xenergy-basic-light-brochure-br014024-en-us.pdf</a>                   |
| CATALOGUES                 | <a href="#">eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf</a>    |
| DECLARATIONS OF CONFORMITY | <a href="#">eaton-small-distribution-board-declaration-of-conformity-eu250305en.pdf</a> |
| DRAWINGS                   | <a href="#">eaton-low-voltage-switch-gear-dimensions-1230dim-438.eps</a>                |
| FLYERS                     | <a href="#">eaton-xenergy-basic-profnap-flyer-fl019008en-en-us.pdf</a>                  |
| MANUALS AND USER GUIDES    | <a href="#">DA-MN-170900093</a><br><a href="#">DA-CS-bp_f_p_8</a>                       |
| MCAD MODEL                 | <a href="#">eaton-front-access-switchboard-mcad-drawings-bp-f-p-8.dwg</a>               |
| PEP ECO-PASSPORT           | <a href="#">eaton-front-access-switchboard-pep-eato-00342-v0101-en.pdf</a>              |
| SALES NOTES                | <a href="#">eaton-f3a-flange-flyer-fl019005en-en-us.pdf</a>                             |

|                 |
|-----------------|
| PROJECT NAME:   |
| PROJECT NUMBER: |
| PREPARED BY:    |
| DATE:           |



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

