

Specifications



Eaton 102464

Eaton xEnergy Basic LV systems Low voltage switchgear. Glass door, for HxW=2060x600mm, Clip-down handle, white

General specifications

PRODUCT NAME	Eaton xEnergy Basic door
CATALOG NUMBER	102464
MODEL CODE	BPZ-DT-600/20-P-W
EAN	4015081023523
PRODUCT LENGTH/DEPTH	65 mm
PRODUCT HEIGHT	2020 mm
PRODUCT WIDTH	592 mm
PRODUCT WEIGHT	7.3 kg
COMPLIANCES	RoHS conform

Additional information

FEATURES	Version as glazed door EMC-version
FUNCTIONS	Floor-standing enclosure Additional equipment
SPECIAL FEATURES	• Can be used as left door for two-leaf versions • Transparent doors • Single wing door • Mounting from front, fast mounting, hinges on left or right possible • Door opening angle 167° • 3-point turn lock with roller lever lock • Transparent panels from 4 mm safety glass (EN 12150-1, DIN 1249) • Left door for two-section design with 1200 mm enclosure widths

Technical data - mechanical

COVER/DOOR COLOR	Transparent
COVER/DOOR TYPE	Rotary lever
HOUSING MATERIAL	Sheet steel/glass
MATERIAL	Steel Sheet steel/glass
MOUNTING METHOD	Floor standing distribution board
SUITABLE FOR HEIGHT	2060 mm
SUITABLE FOR WIDTH	600 mm
SURFACE FINISHING	With powder coating Powder coating
UNIT TYPE	Modular system
DEGREE OF PROTECTION	IP30 NEMA Other

Delivery programme

ACCESSORY/SPARE PART TYPE	Doors
COLOR	White Traffic white (RAL 9016)
MODEL	Stop door
TYPE	Additional equipment for floor-standing service distribution board IVS

Resources

BROCHURES	eaton-xenergy-basic-light-brochure-br014024-en-us.pdf
CATALOGUES	eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf
FLYERS	eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf
SALES NOTES	eaton-f3a-flange-flyer-fl019005en-en-us.pdf

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

