

Specifications



Eaton 110140

Eaton Moeller® series DILA Auxiliary contact module, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, DILA, DILM7 - DILM38, XHIR

General specifications

PRODUCT NAME	Eaton Moeller® series DILA Accessory Auxiliary contact module
---------------------	---

CATALOG NUMBER	110140
-----------------------	--------

MODEL CODE	DILA-XHIR11
-------------------	-------------

EAN	4015081096862
------------	---------------

PRODUCT LENGTH/DEPTH	45 mm
---------------------------------	-------

PRODUCT HEIGHT	41 mm
-----------------------	-------

PRODUCT WIDTH	36 mm
----------------------	-------

PRODUCT WEIGHT	0.053 kg
-----------------------	----------

CERTIFICATIONS	CSA File No.: 012528 UL File No.: E29184 IEC/EN 60947-4-1 CSA CSA Class No.: 3211-03 IEC/EN 60947 CE UL Category Control No.: NKCR CSA-C22.2 No. 14-05 UL 508 UL VDE 0660
-----------------------	---



Powering Business Worldwide

Climatic environmental conditions

**AMBIENT OPERATING
TEMPERATURE - MAX** 60 °C

**AMBIENT STORAGE
TEMPERATURE - MAX** 80 °C

**AMBIENT OPERATING
TEMPERATURE - MIN** -25 °C

**AMBIENT OPERATING
TEMPERATURE
(ENCLOSED) - MAX** 40 °C

**AMBIENT OPERATING
TEMPERATURE
(ENCLOSED) - MIN** -25 °C

**AMBIENT STORAGE
TEMPERATURE - MIN** -40 °C

CLIMATIC PROOFING Damp heat, constant, to
IEC 60068-2-78
Damp heat, cyclic, to IEC
60068-2-30

Contacts

CODE NUMBER 33 in combination with
DILA(C)-22
42 in combination with
DILA(C)-31
51E in combination with
DILA(C)-40

**CONTROL CIRCUIT
RELIABILITY** $\lambda < 1/10^8$ (1 failure at
100,000,000 operations
for $U_e = 24$ V DC, $U_{min} =$
17 V, $I_{min} = 5.4$ mA)
 $\lambda < 5.3 \times 1/10^8$ (1 failure at
19,000,000 operations for
 $U_e = 24$ V DC, $U_{min} = 17$ V,
 $I_{min} = 1$ mA)

**NUMBER OF CONTACTS
(CHANGE-OVER
CONTACTS)** 0

**NUMBER OF CONTACTS
(NORMALLY CLOSED
CONTACTS)** 1

**NUMBER OF CONTACTS
(NORMALLY OPEN
CONTACTS)** 1

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH AT 60°C (3-POLE, OPEN)

16 A

RATED INSULATION VOLTAGE (UI)

690 V

RATED OPERATIONAL CURRENT (IE)

6 A at 110 V, DC L/R ≤ 15 ms (with 3 contacts in series)
 1 A at 220 V, DC L/R ≤ 15 ms (with 1 contact in series)
 2.5 A at 24 V, DC L/R ≤ 50 ms (with 3 contacts in series)
 1 A at 60 V, DC L/R ≤ 50 ms (with 3 contacts in series)
 0.5 A at 110 V, DC L/R ≤ 50 ms (with 3 contacts in series)
 10 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series)
 5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series)
 6 A at 60 V, DC L/R ≤ 15 ms (with 1 contact in series)
 3 A at 110 V, DC L/R ≤ 15 ms (with 1 contact in series)
 0.25 A at 220 V, DC L/R ≤ 50 ms (with 3 contacts in series)
 10 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series)

RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V

4 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V

4 A

RATED OPERATIONAL CURRENT (IE) AT AC-15, 500 V

1.5 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V

0.5 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V

0.25 A

RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V

2.5 A

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.16 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	4 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Features & functions	
ELECTRIC CONNECTION TYPE	Screw connection
FEATURES	Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L)
FITTED WITH:	Interlocked opposing contacts Switching elements according to EN 50005
FUNCTIONS	For electronic applications
NUMBER OF POLES	Two-pole

RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	1 A
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	500 V
SAFE ISOLATION	400 V AC, Between coil and auxiliary contacts, According to EN 61140 400 V AC, Between auxiliary contacts, According to EN 61140
SHORT-CIRCUIT PROTECTION RATING	Max. 10 A gG/gL, Fuse, Without welding, Auxiliary contacts
SHORT-CIRCUIT PROTECTION RATING WITHOUT WELDING	10 A gG/gL, 500 V, Max. Fuse, Contacts
SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	10 A, 600 V AC, (UL/CSA) 1 A, 250 V DC, (UL/CSA)
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	P300, DC operated (UL/CSA) A600, AC operated (UL/CSA)

General information	
CONNECTION	Screw terminals
DEGREE OF PROTECTION	IP20
LIFESPAN, ELECTRICAL	1,300,000 Operations (at 230 V, AC-15, 3 A)
LIFESPAN, MECHANICAL	10,000,000 Operations (AC operated) 10,000,000 Operations (DC operated)
MODEL	Top mounting
MOUNTING METHOD	Front fastening
OPERATING FREQUENCY	9000 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3

PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SHOCK RESISTANCE	7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
TYPE	Front mounting auxiliary contact

Terminal capacities

SCREW SIZE	M3.5, Terminal screw
SCREWDRIVER SIZE	0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.75 - 1.5) mm ² , Screw terminals 2 x (0.75 - 1.5) mm ² , Screw terminals
TERMINAL CAPACITY (SOLID)	2 x (0.75 - 2.5) mm ² , Screw terminals 1 x (0.75 - 2.5) mm ² , Screw terminals
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14, Screw terminals
TIGHTENING TORQUE	1.2 Nm, Screw terminals

Resources

CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-accessory-declaration-of-conformity-eu250793en.pdf eaton-accessory-declaration-of-conformity-uk251276en.pdf
	eaton-contactors-frame-dilm-dimensions.eps eaton-contactors-mounting-dilm-dimensions.eps eaton-contactors-mounting-dilm-dimensions-002.eps eaton-contactors-dimensions-2100dim-71.eps eaton-contactors-dimensions-2100dim-70.eps 2100DRW-181
DRAWINGS	
ECAD MODEL	ETN.110140.edz

INSTALLATION INSTRUCTIONS	eaton-contactors-dila-dilm7-15-dilmp20-il03407013z.pdf
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MCAD MODEL	eaton-contact-blocks-mcad-drawings-dil-a-xhir11.dwg DA-CS-dil a xhir11
WIRING DIAGRAMS	eaton-contactors-contact-dila-accessory-wiring-diagram-009.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

