

# Specifications



## Eaton 111101

Eaton xEnergy Basic LV systems Low voltage switchgear. Wall box for 3-step system  
HxWxD=460x600x180mm

### General specifications

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| <b>PRODUCT NAME</b>             | Eaton xEnergy Basic<br>installation component |
| <b>CATALOG NUMBER</b>           | 111101                                        |
| <b>MODEL CODE</b>               | BPZ-WB3S-600/4/1                              |
| <b>EAN</b>                      | 4015081106622                                 |
| <b>PRODUCT<br/>LENGTH/DEPTH</b> | 180 mm                                        |
| <b>PRODUCT HEIGHT</b>           | 433 mm                                        |
| <b>PRODUCT WIDTH</b>            | 606 mm                                        |
| <b>PRODUCT WEIGHT</b>           | 4.32 kg                                       |
| <b>COMPLIANCES</b>              | RoHS conform                                  |

## Additional information

|                   |                      |
|-------------------|----------------------|
| <b>FUNCTIONS</b>  | Additional equipment |
| <b>RAL-NUMBER</b> | 0                    |

## Technical data - mechanical

|                                                     |                |
|-----------------------------------------------------|----------------|
| <b>HOUSING MATERIAL</b>                             | Sheet steel    |
| <b>MATERIAL</b>                                     | Metal          |
| <b>MOUNTING METHOD</b>                              | Flush mounting |
| <b>SUITABLE FOR ENCLOSURE BUILDING LENGTH/DEPTH</b> | 180 mm         |
| <b>SUITABLE FOR ENCLOSURE BUILDING WIDTH</b>        | 600 mm         |
| <b>SUITABLE FOR HEIGHT</b>                          | 460 mm         |
| <b>SUITABLE FOR LENGTH/DEPTH</b>                    | 180 mm         |
| <b>SUITABLE FOR WIDTH</b>                           | 600 mm         |
| <b>SURFACE FINISHING</b>                            | Galvanized     |
| <b>SUITABLE FOR ENCLOSURE BUILDING HEIGHT</b>       | 460 mm         |

## Delivery programme

|                    |                      |
|--------------------|----------------------|
| <b>APPLICATION</b> | Three steps system   |
| <b>COLOR</b>       | Stainless steel      |
| <b>MODEL</b>       | Other                |
| <b>TYPE</b>        | Additional equipment |

## Resources

|                    |                                                                                      |
|--------------------|--------------------------------------------------------------------------------------|
| <b>BROCHURES</b>   | <a href="#">eaton-xenergy-basic-light-brochure-br014024-en-us.pdf</a>                |
| <b>CATALOGUES</b>  | <a href="#">eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf</a> |
| <b>FLYERS</b>      | <a href="#">eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf</a>             |
| <b>SALES NOTES</b> | <a href="#">eaton-f3a-flange-flyer-fl019005en-en-us.pdf</a>                          |

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

