

# Specifications



## Eaton 111114

Eaton xEnergy Basic LV systems Low voltage switchgear. Wall trough for three-component system  
HxWxD=1060x1000x180mm

### General specifications

|                             |                                            |
|-----------------------------|--------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton xEnergy Basic installation component |
| <b>CATALOG NUMBER</b>       | 111114                                     |
| <b>MODEL CODE</b>           | BPZ-WB3S-1000/10/1                         |
| <b>EAN</b>                  | 4015081106752                              |
| <b>PRODUCT LENGTH/DEPTH</b> | 180 mm                                     |
| <b>PRODUCT HEIGHT</b>       | 1033 mm                                    |
| <b>PRODUCT WIDTH</b>        | 1006 mm                                    |
| <b>PRODUCT WEIGHT</b>       | 7.64 kg                                    |
| <b>COMPLIANCES</b>          | RoHS conform                               |

## Additional information

|                   |                      |
|-------------------|----------------------|
| <b>FUNCTIONS</b>  | Additional equipment |
| <b>RAL-NUMBER</b> | 0                    |

## Technical data - mechanical

|                                                     |                |
|-----------------------------------------------------|----------------|
| <b>HOUSING MATERIAL</b>                             | Sheet steel    |
| <b>MATERIAL</b>                                     | Metal          |
| <b>MOUNTING METHOD</b>                              | Flush mounting |
| <b>SUITABLE FOR ENCLOSURE BUILDING LENGTH/DEPTH</b> | 180 mm         |
| <b>SUITABLE FOR ENCLOSURE BUILDING WIDTH</b>        | 1000 mm        |
| <b>SUITABLE FOR HEIGHT</b>                          | 1060 mm        |
| <b>SUITABLE FOR LENGTH/DEPTH</b>                    | 180 mm         |
| <b>SUITABLE FOR WIDTH</b>                           | 1000 mm        |
| <b>SURFACE FINISHING</b>                            | Galvanized     |
| <b>SUITABLE FOR ENCLOSURE BUILDING HEIGHT</b>       | 1060 mm        |

## Delivery programme

|                    |                      |
|--------------------|----------------------|
| <b>APPLICATION</b> | Three steps system   |
| <b>COLOR</b>       | Stainless steel      |
| <b>MODEL</b>       | Other                |
| <b>TYPE</b>        | Additional equipment |

## Resources

|             |                                                                                      |
|-------------|--------------------------------------------------------------------------------------|
| BROCHURES   | <a href="#">eaton-xenergy-basic-light-brochure-br014024-en-us.pdf</a>                |
| CATALOGUES  | <a href="#">eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf</a> |
| FLYERS      | <a href="#">eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf</a>             |
| SALES NOTES | <a href="#">eaton-f3a-flange-flyer-fl019005en-en-us.pdf</a>                          |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

