

Specifications



Eaton 111697

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=600x500x250mm

General specifications

PRODUCT NAME	Eaton xEffect CS enclosure single door
CATALOG NUMBER	111697
MODEL CODE	CS-65/250
EAN	4015081112562
PRODUCT LENGTH/DEPTH	250 mm
PRODUCT HEIGHT	600 mm
PRODUCT WIDTH	500 mm
PRODUCT WEIGHT	17.86 kg

COMPLIANCES

UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure)
UL 508A; CSA-C22.2 No.14;
IEC/EN 62208; CE marking
RoHS conform

CERTIFICATIONS

UL CSA08 (request filed)
UL (Category Control Number NITW)
In accordance with Directive 2015/863/EU of the European Parliament and Council
IEC/EN 62208
UL (File No. E336299)

CATALOG NOTES

Foamed polyurethane sealing throughout.
Impact resistance category IK10 to EN 62262. Sheet steel mounting plate.
Bottom plate with foamed gasket. Single door, door stop on the right, door opening angle 120°. Door hinge pins with quick chang



Powering Business Worldwide

Additional information

FEATURES

Pole fastening
Wall build in

FITTED WITH:

Mounting plate
Including M6 threaded
welded studs for earth
conductor connections in
the door:
Cover
Door

FUNCTIONS

Floor standing enclosure

RAL-NUMBER

7035

SPECIAL FEATURES

- Bottom plate enclosed, foamed gasket, can be unscrewed for F3A-... flanges or for assembly by user
- Foamed polyurethane sealing throughout.
- Impact resistance category IK10 to EN 62262.
- Sheet steel mounting plate
- Bottom plate with foamed gasket.
- Lock, 3 mm double ward key
- Including M6 threaded welded studs for earth conductor connections in the door
- Side plates without apertures
- Single door, door stop on the right, door opening angle 120°
- Door hinge pins with quick change technology.
- Standardized locking system with sash fastener.
- Powder coating RAL 7035 inside and outside
- Top plate without apertures

SUITABLE FOR

Metrical mounting

USED WITH

Industrial control panels

Delivery programme

COLOR

Light gray (RAL 7035)
Gray

TYPE

- Wall-mounting housing CS
- Wall-mounting housing with mounting plate

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply to enclosures without lifting aids.
10.2.6 MECHANICAL IMPACT	IK10
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP66
10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	< 0.1 Ω ; meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR	Is the panel builder's

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE DETAILS	-25 °C - 40 °C
--	----------------

EXTERNAL CONDUCTORS	responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Ui = 1000 V AC
10.9.3 IMPULSE WITHSTAND VOLTAGE	Does not apply to basic enclosures as defined in EN 62208.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Does not apply to metal enclosures.

Technical data - mechanical

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78; Damp heat, cyclical, to IEC 60068-2-30
COVER/DOOR ANGLE	120° door opening angle
COVER/DOOR PROFILE	2 door profiles
COVER/DOOR TYPE	Closed Door hinges on the right, can be converted by user Standard closure 3 mm double-ward key (door interlock)
DESIGN TYPE	Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure.
FLANGE PLATE DIMENSIONS	172 mm x 432 mm
INSTALLATION SITE	Indoor installation
INSTALLATION TYPE	Floor standing wall model
LOAD CAPACITY (DOOR)	25 kg
LOAD CAPACITY (MOUNTING PLATE)	250 kg 500 kg payload, when brackets fitted in all four enclosure corners (vertically or horizontally) and the weights are symmetrically distributed within the enclosure.
MATERIAL	Steel plate Steel
MATERIAL QUALITY	Other
MATERIAL THICKNESS (BODY)	1.2 mm
MATERIAL THICKNESS (BOTTOM PLATE)	2 mm
MATERIAL THICKNESS (DOOR)	1.5 mm
MOUNTING METHOD	9 mm drilling dimensions for wall mounting (Back plate) Wall fastening Intermediate mounting
MOUNTING PLATE HEIGHT	570 mm
MOUNTING PLATE MATERIAL	Sheet steel, hot-galvanized
MOUNTING PLATE WIDTH	450 mm

Temperature-rise verification as per IEC 60890

HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	45 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	91 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	55 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	49 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	105 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	98 W
HEAT DISS. WALL MOUNT INDIVIDUAL ENCL. TOP	55 W
HEAT DISS. WALL MOUNT MIDDLE ENCL. TOP	45 W
HEAT DISS. WALL MOUNT STARTING ENCL. TOP	49 W
THERMAL DISSIPATION (DELTA T = 20 K) ACCORDING TO IEC/TR 60890	55 W

NUMBER OF CONNECTOR HOLES	0
NUMBER OF COVERS/DOORS	1
NUMBER OF F3A FLANGES	1
NUMBER OF HINGES	2
NUMBER OF LOCKS	2
PERMISSIBLE LOAD OF THE DOOR(S) ACCORDING TO IEC 62208 - MAX	250 N
PERMISSIBLE LOAD OF THE ENCLOSURE ACCORDING TO IEC 62208 - MAX	2750 N
PERMISSIBLE LOAD OF THE MOUNTING PLATE ACCORDING TO IEC 62208 - MAX	2500 N
SURFACE FINISHING	Semi-textured Structured powder spray polyester based paint finish Powder coating Gloss
SURFACE TREATMENT	Structured powder spray polyester based paint finish
THICKNESS OF MOUNTING PLATE	2 mm
WEIGHT OF MOUNTED COMPONENTS - MAX	275 kg
DEGREE OF PROTECTION	IP66 IEC: IP66, indoor; UL/CSA Types 1, 12, indoor only. IP23 (with ventilating plates) 12 (NEMA) IK10 (impact resistance) IK10

Resources

BROCHURES	eaton-xeffect-cs-new-features-fl015002zu.pdf
CATALOGUES	eaton-xeffect-cs-enclosure-catalog-fk4300-1178gb-en-us.pdf
CERTIFICATION REPORTS	eaton-xeffect-cs-enclosure-declaration-of-conformity-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-enclosure-declaration-of-conformity-eu250381en.pdf
INSTALLATION INSTRUCTIONS	IL2521
MCAD MODEL	eaton-front-access-switchboard-mcad-drawings-cs88-200.dwg DA-CS-cs88_200_111697

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

