

Specifications

Eaton 111761

Eaton Moeller series xPole - PDIM RCCB.
Earth Leakage Monitoring Device, 100A, 4p,
0mA, AC-Char

General specifications

PRODUCT NAME	Eaton Moeller series xPole - PDIM RCCB
CATALOG NUMBER	111761
MODEL CODE	PDIM-100/4
EAN	4015081113118
PRODUCT LENGTH/DEPTH	76 mm
PRODUCT HEIGHT	80 mm
PRODUCT WIDTH	70 mm
PRODUCT WEIGHT	0.404 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	DIN/EN 62020



Powering Business Worldwide

Product specifications

USED WITH	Leakage current monitor PDIM
AMPERAGE RATING	100 A
FEATURES	Additional equipment possible Leakage current monitor Selective protection
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product

Resources

DECLARATIONS OF CONFORMITY	eaton-rccb-declaration-of-conformity-eu250386en.pdf
DRAWINGS	eaton-dimensions-mas-pdim.jpg
ECAD MODEL	DA-CE-ETN.PDIM-100_4
INSTALLATION INSTRUCTIONS	IL019009ZU
MCAD MODEL	eaton-fi9400-3-d-model.stp eaton-rccb-mcad-drawings-fi9400.dwg
WIRING DIAGRAMS	PDIM

	standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	Interlocking device
FRAME	45 mm
FREQUENCY RATING	60 Hz
POLLUTION DEGREE	2
LIFESPAN, MECHANICAL	20000 operations
MOUNTING METHOD	Quick attachment with 2 latch positions on top-hat rail IEC/EN 60715 DIN rail
CLIMATIC PROOFING	25-55 °C / 90-95% relative humidity according to IEC 60068-2
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	18.8 W
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	10 kA
ADMISSIBLE BACK-UP FUSE OVERLOAD - MAX	63 A gG/gL
BUILT-IN WIDTH (NUMBER OF UNITS)	70 mm (4 SU)
BUSBAR MATERIAL	0.8 mm - 2 mm

THICKNESS	
SHORT-CIRCUIT RATING	100 A (max. admissible back-up fuse)
TERMINAL PROTECTION	Finger and hand touch safe, DGUV VS3, EN 50274
TERMINALS (TOP AND BOTTOM)	Twin-purpose terminals
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
BUILT-IN DEPTH	60 mm
CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX	16 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN	1.5 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX	35 mm ²
CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN	1.5 mm ²
FAULT CURRENT RATING	1000 mA
HEAT DISSIPATION CAPACITY	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	0 W
PERMITTED STORAGE AND TRANSPORT TEMPERATURE - MAX	60 °C
PERMITTED STORAGE AND TRANSPORT TEMPERATURE - MIN	-35 °C
DEGREE OF PROTECTION	IP20 IP20, IP40 with suitable enclosure
NUMBER OF POLES	Four-pole
LEAKAGE CURRENT TYPE	AC
LIFESPAN, ELECTRICAL	4000 operations
TYPE	• Leakage current monitor • PDIM

SPECIAL FEATURES	• Current test marks as per inscription • Maximum operating temperature is 60 °C: Starting at 40 °C, the max. permissible continuous current decreases by 1.2% for every 1 °C • Switching contact (potential-free) 10 A / 240 V~
-------------------------	--

APPLICATION	• Switchgear for industrial and advanced commercial applications • xEffect - Switchgear for industrial and advanced commercial applications
--------------------	--

FUNCTIONS	Short-time delayed tripping Fault current adjustable: 0.03 A/0.1 A/0.3 A/0.5 A/1 A
------------------	--

SENSITIVITY TYPE	AC and pulsating DC current sensitive
-------------------------	---------------------------------------

RATED FAULT CURRENT - MAX	1 A
----------------------------------	-----

RATED FAULT CURRENT - MIN	0.03 A
----------------------------------	--------

RATED INSULATION VOLTAGE (UI)	440 V
--------------------------------------	-------

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	100 A
--	-------

RATED OPERATIONAL VOLTAGE (UE) - MAX	415 V
---	-------

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0 W
---	-----

SURGE CURRENT CAPACITY	0.25 kA
-------------------------------	---------

WIDTH IN NUMBER OF MODULAR SPACINGS	4
--	---

VOLTAGE RATING (IEC/EN 60947-2)	• 230/400 V, 50/60
--	--

	Hz • 240/415 V, 50/60 Hz
VOLTAGE TYPE	AC
TERMINAL CAPACITY (SOLID WIRE)	1.5 mm ² - 35 mm ²
TRIPPING TIME	Non-delayed, adjustable Selective switch off, adjustable 40 ms delayed, selective (type S) 10 ms delayed (Type G) Short time-delayed, adjustable
TERMINAL CAPACITY (CONTROL CABLE)	0.25 mm ² - 1.5 mm ² at switching contacts
RATED SHORT-CIRCUIT STRENGTH	10 kA
RESPONSE BEHAVIOR (ADJUSTABLE)	Undelayed
RESPONSE BEHAVIOR OF CONTACTS	1: 30 - 50 % I _{Δn} ; 2: > 50 % I _{Δn}
TERMINAL CAPACITY (STRANDED CABLE)	16 mm ² (2x)
RAL-NUMBER	7035
COLOR	Gray

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE: