

# Specifications



## Eaton 112442

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 18.5 kW, 1 N/O, RDC 24: 24 - 27 V DC, DC operation, Screw terminals DILM38-10(RDC24)

### General specifications

|                             |                                                                                                                                                                                                                                                                                                                |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller® series DILM contactor                                                                                                                                                                                                                                                                           |
| <b>CATALOG NUMBER</b>       | 112442                                                                                                                                                                                                                                                                                                         |
| <b>MODEL CODE</b>           | DILM38-10(RDC24)                                                                                                                                                                                                                                                                                               |
| <b>EAN</b>                  | 4015081119981                                                                                                                                                                                                                                                                                                  |
| <b>PRODUCT LENGTH/DEPTH</b> | 97 mm                                                                                                                                                                                                                                                                                                          |
| <b>PRODUCT HEIGHT</b>       | 85 mm                                                                                                                                                                                                                                                                                                          |
| <b>PRODUCT WIDTH</b>        | 45 mm                                                                                                                                                                                                                                                                                                          |
| <b>PRODUCT WEIGHT</b>       | 0.534 kg                                                                                                                                                                                                                                                                                                       |
| <b>COMPLIANCES</b>          | CE Marked                                                                                                                                                                                                                                                                                                      |
| <b>CERTIFICATIONS</b>       | UL 508<br>IEC 60947-4-1<br>EN 60947-4-1<br>CSA Std. C22.2 No. 14-05<br>VDE<br>CSA-C22.2 No. 60947-4-1-14<br>CE<br>UL 60947-4-1<br>CSA File No.: 012528<br>IEC/EN 60947<br>UL Category Control No.: NLDX<br>CSA<br>IEC/EN 60947-4-1<br>UL File No.: E29096<br>CSA Class No.: 2411-03, 3211-04<br>VDE 0660<br>UL |
| <b>CATALOG NOTES</b>        | Contacts according to EN 50012                                                                                                                                                                                                                                                                                 |

## Ambient conditions, mechanical

### SHOCK RESISTANCE

3.5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms  
10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms  
6.9 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms  
5.3 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

## Communication

### CONNECTION TO SMARTWIRE-DT

Yes  
In conjunction with DIL-SWD SmartWire DT contactor module

## Climatic environmental conditions

**ALTITUDE** Max. 2000 m

**AMBIENT OPERATING TEMPERATURE - MAX** 60 °C

**AMBIENT STORAGE TEMPERATURE - MAX** 80 °C

**AMBIENT OPERATING TEMPERATURE - MIN** -25 °C

**AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX** 40 °C

**AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN** -25 °C

**AMBIENT STORAGE TEMPERATURE - MIN** -40 °C

**CLIMATIC PROOFING** Damp heat, cyclic, to IEC 60068-2-30  
Damp heat, constant, to IEC 60068-2-78

## Contacts

**NUMBER OF MAIN CONTACTS (NORMALLY OPEN CONTACT)** 3

**NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)** 0

**NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)** 1

**NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)** 1

**NUMBER OF CONTACTS (NORMALLY CLOSED) AS MAIN CONTACT** 0

## Conventional thermal current I<sub>th</sub>

**CONVENTIONAL  
THERMAL CURRENT I<sub>TH</sub>  
(1-POLE, ENCLOSED)** 90 A

**CONVENTIONAL  
THERMAL CURRENT I<sub>TH</sub>  
(3-POLE, ENCLOSED)** 36 A

**CONVENTIONAL  
THERMAL CURRENT I<sub>TH</sub>  
AT 55°C (3-POLE, OPEN)** 42 A

**CONVENTIONAL  
THERMAL CURRENT I<sub>TH</sub>  
AT 60°C (3-POLE, OPEN)** 40 A

**CONVENTIONAL  
THERMAL CURRENT I<sub>TH</sub>  
OF MAIN CONTACTS (1-  
POLE, OPEN)** 100 A

## Design verification

### 10.10 TEMPERATURE RISE

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 MECHANICAL FUNCTION

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### 10.2.2 CORROSION RESISTANCE

Meets the product standard's requirements.

### 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES

Meets the product standard's requirements.

### 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT

Meets the product standard's requirements.

### 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS

Meets the product standard's requirements.

### 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION

Meets the product standard's requirements.

### 10.2.5 LIFTING

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 MECHANICAL IMPACT

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 INSCRIPTIONS

Meets the product standard's requirements.

### 10.3 DEGREE OF PROTECTION OF ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

### 10.4 CLEARANCES AND CREEPAGE DISTANCES

Meets the product standard's requirements.

### 10.5 PROTECTION

Does not apply, since the

|                                                                      |                                                                    |
|----------------------------------------------------------------------|--------------------------------------------------------------------|
| <b>AGAINST ELECTRIC SHOCK</b>                                        | entire switchgear needs to be evaluated.                           |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>        | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>             | Is the panel builder's responsibility.                             |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                      | Is the panel builder's responsibility.                             |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                      | Is the panel builder's responsibility.                             |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                              | Is the panel builder's responsibility.                             |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>      | Is the panel builder's responsibility.                             |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>            | 9.3 W                                                              |
| <b>HEAT DISSIPATION CAPACITY PDISS</b>                               | 0 W                                                                |
| <b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>             | 3.1 W                                                              |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 38 A                                                               |
| <b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>            | 0.9 W                                                              |

## Electrical rating

|                                             |       |
|---------------------------------------------|-------|
| <b>RATED BREAKING CAPACITY AT 220/230 V</b> | 320 A |
|---------------------------------------------|-------|

|                                             |       |
|---------------------------------------------|-------|
| <b>RATED BREAKING CAPACITY AT 380/400 V</b> | 320 A |
|---------------------------------------------|-------|

|                                         |       |
|-----------------------------------------|-------|
| <b>RATED BREAKING CAPACITY AT 500 V</b> | 320 A |
|-----------------------------------------|-------|

|                                             |       |
|---------------------------------------------|-------|
| <b>RATED BREAKING CAPACITY AT 660/690 V</b> | 180 A |
|---------------------------------------------|-------|

|                                      |       |
|--------------------------------------|-------|
| <b>RATED INSULATION VOLTAGE (UI)</b> | 690 V |
|--------------------------------------|-------|

|                                                                    |       |
|--------------------------------------------------------------------|-------|
| <b>RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947)</b> | 384 A |
|--------------------------------------------------------------------|-------|

|                                                                    |      |
|--------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-1, 380 V, 400 V, 415 V</b> | 45 A |
|--------------------------------------------------------------------|------|

|                                                                    |      |
|--------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V</b> | 38 A |
|--------------------------------------------------------------------|------|

|                                                                    |      |
|--------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V</b> | 38 A |
|--------------------------------------------------------------------|------|

|                                                      |      |
|------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 440 V</b> | 38 A |
|------------------------------------------------------|------|

|                                                      |      |
|------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V</b> | 38 A |
|------------------------------------------------------|------|

|                                                             |        |
|-------------------------------------------------------------|--------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V</b> | 22.5 A |
|-------------------------------------------------------------|--------|

|                                                                    |      |
|--------------------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 220 V, 230 V, 240 V</b> | 15 A |
|--------------------------------------------------------------------|------|

|                                                      |      |
|------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 440 V</b> | 15 A |
|------------------------------------------------------|------|

|                                                      |      |
|------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 500 V</b> | 15 A |
|------------------------------------------------------|------|

|                                                             |      |
|-------------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT AC-4, 660 V, 690 V</b> | 12 A |
|-------------------------------------------------------------|------|

|                                                      |      |
|------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-1, 110 V</b> | 40 A |
|------------------------------------------------------|------|

|                                                      |      |
|------------------------------------------------------|------|
| <b>RATED OPERATIONAL CURRENT (IE) AT DC-1, 220 V</b> | 40 A |
|------------------------------------------------------|------|

## Electro magnetic compatibility

|                             |                         |
|-----------------------------|-------------------------|
| <b>EMITTED INTERFERENCE</b> | According to EN 60947-1 |
|-----------------------------|-------------------------|

|                              |                         |
|------------------------------|-------------------------|
| <b>INTERFERENCE IMMUNITY</b> | According to EN 60947-1 |
|------------------------------|-------------------------|

|                                                                  |         |
|------------------------------------------------------------------|---------|
| <b>RATED OPERATIONAL<br/>CURRENT (IE) AT DC-1, 60<br/>V</b>      | 40 A    |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 240 V, 50<br/>HZ</b>     | 12 kW   |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 380/400<br/>V, 50 HZ</b> | 18.5 kW |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 415 V, 50<br/>HZ</b>     | 20 kW   |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 440 V, 50<br/>HZ</b>     | 21 kW   |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 500 V, 50<br/>HZ</b>     | 24 kW   |
| <b>RATED OPERATIONAL<br/>POWER AT AC-3, 690 V, 50<br/>HZ</b>     | 21 kW   |
| <b>RATED OPERATIONAL<br/>POWER AT AC-4, 220/230<br/>V, 50 HZ</b> | 4 kW    |
| <b>RATED OPERATIONAL<br/>POWER AT AC-4, 240 V, 50<br/>HZ</b>     | 4.5 kW  |
| <b>RATED OPERATIONAL<br/>POWER AT AC-4, 415 V, 50<br/>HZ</b>     | 7.5 kW  |
| <b>RATED OPERATIONAL<br/>POWER AT AC-4, 440 V, 50<br/>HZ</b>     | 8 kW    |
| <b>RATED OPERATIONAL<br/>POWER AT AC-4, 500 V, 50<br/>HZ</b>     | 9 kW    |
| <b>RATED OPERATIONAL<br/>POWER AT AC-4, 660/690<br/>V, 50 HZ</b> | 10 kW   |
| <b>RATED OPERATIONAL<br/>VOLTAGE (UE) AT AC -<br/>MAX</b>        | 690 V   |

| Features & functions   |                                             |
|------------------------|---------------------------------------------|
| <b>FITTED WITH:</b>    | Suppressor circuit in actuating electronics |
| <b>NUMBER OF POLES</b> | Three-pole                                  |

| General information         |                                     |
|-----------------------------|-------------------------------------|
| <b>APPLICATION</b>          | Contactors for Motors               |
| <b>CONNECTION</b>           | Screw terminals                     |
| <b>DEGREE OF PROTECTION</b> | IP00                                |
| <b>LIFESPAN, MECHANICAL</b> | 10,000,000 Operations (DC operated) |
| <b>OPERATING FREQUENCY</b>  | 5000 mechanical                     |

|                                               |                                                                                                                                                                                                                           |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                               | Operations/h (DC operated)                                                                                                                                                                                                |
| <b>OVERVOLTAGE CATEGORY</b>                   | III                                                                                                                                                                                                                       |
| <b>POLLUTION DEGREE</b>                       | 3                                                                                                                                                                                                                         |
| <b>PRODUCT CATEGORY</b>                       | Contactors                                                                                                                                                                                                                |
| <b>PROTECTION</b>                             | Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)                                                                                                                      |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b> | 8000 V AC                                                                                                                                                                                                                 |
| <b>RESISTANCE PER POLE</b>                    | 2.7 mΩ                                                                                                                                                                                                                    |
| <b>UTILIZATION CATEGORY</b>                   | AC-1: Non-inductive or slightly inductive loads, resistance furnaces<br>AC-3: Normal AC induction motors: starting, switch off during running<br>AC-4: Normal AC induction motors: starting, plugging, reversing, inching |
| <b>VOLTAGE TYPE</b>                           | DC                                                                                                                                                                                                                        |
| <b>FRAME SIZE</b>                             | FS2                                                                                                                                                                                                                       |

## Magnet system

|                                                                         |                                                                                                       |
|-------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| <b>ARCING TIME</b>                                                      | 10 ms                                                                                                 |
| <b>DROP-OUT VOLTAGE</b>                                                 | At least smoothed two-phase bridge rectifier or three-phase rectifier<br>0.6 - 0.15 x UC, DC operated |
| <b>DUTY FACTOR</b>                                                      | 100 %                                                                                                 |
| <b>PICK-UP VOLTAGE</b>                                                  | 24 - 27 V DC (RDC 24)<br>0.7 - 1.2 V DC x Uc                                                          |
| <b>POWER CONSUMPTION (PICK-UP) AT DC</b>                                | 12 W                                                                                                  |
| <b>POWER CONSUMPTION (SEALING) AT DC</b>                                | 0.9 W                                                                                                 |
| <b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX</b>                    | 27 V                                                                                                  |
| <b>RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN</b>                    | 24 V                                                                                                  |
| <b>SWITCHING TIME (DC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX</b> | 47 ms                                                                                                 |
| <b>SWITCHING TIME (DC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX</b> | 30 ms                                                                                                 |

## Safety

|                       |                                                                                                                     |
|-----------------------|---------------------------------------------------------------------------------------------------------------------|
| <b>SAFE ISOLATION</b> | 440 V AC, Between coil and contacts, According to EN 61140<br>440 V AC, Between the contacts, According to EN 61140 |
|-----------------------|---------------------------------------------------------------------------------------------------------------------|

## Motor rating

**ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE** 2 HP

**ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE** 10 HP

**ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE** 5 HP

**ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE** 10 HP

**ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE** 20 HP

**ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE** 25 HP

## Short-circuit rating

**SHORT-CIRCUIT CURRENT RATING (BASIC RATING)** 125 A, max. CB, SCCR (UL/CSA)  
125 A, max. Fuse, SCCR (UL/CSA)  
5 kA, SCCR (UL/CSA)

**SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 480 V)** 125/70 A, Class J, max. Fuse, SCCR (UL/CSA)  
10/100 kA, Fuse, SCCR (UL/CSA)  
50/32 A, max. CB, SCCR (UL/CSA)  
10/65 kA, CB, SCCR (UL/CSA)

**SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)** 10/22 kA, CB, SCCR (UL/CSA)  
50/32 A, max. CB, SCCR (UL/CSA)  
10/100 kA, Fuse, SCCR (UL/CSA)  
125/125 A, Class J, max. Fuse, SCCR (UL/CSA)

|                                                                                   |             |
|-----------------------------------------------------------------------------------|-------------|
| <b>SHORT-CIRCUIT<br/>PROTECTION RATING<br/>(TYPE 1 COORDINATION)<br/>AT 400 V</b> | 125 A gG/gL |
|-----------------------------------------------------------------------------------|-------------|

|                                                                                   |            |
|-----------------------------------------------------------------------------------|------------|
| <b>SHORT-CIRCUIT<br/>PROTECTION RATING<br/>(TYPE 1 COORDINATION)<br/>AT 690 V</b> | 63 A gG/gL |
|-----------------------------------------------------------------------------------|------------|

|                                                                                   |            |
|-----------------------------------------------------------------------------------|------------|
| <b>SHORT-CIRCUIT<br/>PROTECTION RATING<br/>(TYPE 2 COORDINATION)<br/>AT 400 V</b> | 63 A gG/gL |
|-----------------------------------------------------------------------------------|------------|

|                                                                                   |            |
|-----------------------------------------------------------------------------------|------------|
| <b>SHORT-CIRCUIT<br/>PROTECTION RATING<br/>(TYPE 2 COORDINATION)<br/>AT 690 V</b> | 35 A gG/gL |
|-----------------------------------------------------------------------------------|------------|

## Special purpose ratings

### SPECIAL PURPOSE RATING OF DEFINITE PURPOSE RATING

192 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)  
32 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

### SPECIAL PURPOSE RATING OF ELEVATOR CONTROL

20 HP, 600 V 60 Hz 3-ph, (UL/CSA)  
7.5 HP, 240 V 60 Hz 3-ph, (UL/CSA)  
27 A, 480 V 60 Hz 3-ph, (UL/CSA)  
22 A, 240 V 60 Hz 3-ph, (UL/CSA)  
7.5 HP, 200 V 60 Hz 3-ph, (UL/CSA)  
22 A, 600 V 60 Hz 3-ph, (UL/CSA)  
25.3 A, 200 V 60 Hz 3-ph, (UL/CSA)  
20 HP, 480 V 60 Hz 3-ph, (UL/CSA)

### SPECIAL PURPOSE RATING OF REFRIGERATION CONTROL (CSA ONLY)

30 A, FLA 600 V 60 Hz 3phase; (CSA)  
40 A, FLA 480 V 60 Hz 3phase; (CSA)  
180 A, LRA 600 V 60 Hz 3phase; (CSA)  
240 A, LRA 480 V 60 Hz 3phase; (CSA)

### SPECIAL PURPOSE RATING OF RESISTANCE AIR HEATING

40 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)  
40 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

### SPECIAL PURPOSE RATING OF TUNGSTEN INCANDESCENT LAMPS

40 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)  
40 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

### SPECIAL PURPOSE RATING OF BALLAST ELECTRICAL DISCHARGE LAMPS

40 A (600V 60Hz 3phase, 347V 60Hz 1phase)  
40 A (480V 60Hz 3phase, 277V 60Hz 1phase)

## Switching capacity

### SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)

1 A, 250 V DC, (UL/CSA)  
10 A, 600 V AC, (UL/CSA)

### SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)

P300, DC operated (UL/CSA)  
A600, AC operated (UL/CSA)

### SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)

40 A, Maximum motor rating (UL/CSA)

## Terminal capacities

|                                                  |                                                                                                                                                                                                                          |
|--------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>SCREW SIZE</b>                                | M5, Terminal screw, Main cables<br>M3.5, Terminal screw, Control circuit cables                                                                                                                                          |
| <b>SCREWDRIVER SIZE</b>                          | 0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver<br>2, Terminal screw, Pozidriv screwdriver                                                                                                                      |
| <b>STRIPPING LENGTH (CONTROL CIRCUIT CABLE)</b>  | 10 mm                                                                                                                                                                                                                    |
| <b>STRIPPING LENGTH (MAIN CABLE)</b>             | 10 mm                                                                                                                                                                                                                    |
| <b>TERMINAL CAPACITY (SOLID)</b>                 | 1 x (0.75 - 4) mm <sup>2</sup> , Control circuit cables<br>2 x (0.75 - 10) mm <sup>2</sup> , Main cables<br>1 x (0.75 - 16) mm <sup>2</sup> , Main cables<br>2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables   |
| <b>TERMINAL CAPACITY (STRANDED)</b>              | 1 x 16 mm <sup>2</sup> , Main cables                                                                                                                                                                                     |
| <b>TIGHTENING TORQUE</b>                         | 3.2 Nm, Screw terminals, Main cables<br>1.2 Nm, Screw terminals, Control circuit cables                                                                                                                                  |
| <b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b> | 2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables<br>1 x (0.75 - 16) mm <sup>2</sup> , Main cables<br>2 x (0.75 - 10) mm <sup>2</sup> , Main cables<br>1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables |
| <b>TERMINAL CAPACITY (SOLID/STRANDED AWG)</b>    | Single 18 - 6, double 18 - 8, Main cables<br>18 - 14, Control circuit cables                                                                                                                                             |

## Resources

|                            |                                                                                                                                                                                                                                                                                                                              |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CATALOGUES                 | <a href="#">eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf</a>                                                                                                                                                                                                                                       |
| CHARACTERISTIC CURVE       | <a href="#">eaton-contactors-component-dilm-characteristic-curve-003.eps</a><br><a href="#">eaton-contactors-switch-dilm-characteristic-curve-002.eps</a><br><a href="#">eaton-contactors-switch-dilm-characteristic-curve.eps</a><br><a href="#">eaton-contactors-short-time-loading-dilm-characteristic-curve.eps</a>      |
| DECLARATIONS OF CONFORMITY | <a href="#">eaton-contactor-declaration-of-conformity-uk251219en.pdf</a><br><a href="#">eaton-contactor-declaration-of-conformity-eu250736en.pdf</a>                                                                                                                                                                         |
| DRAWINGS                   | <a href="#">eaton-contactors-dimensions-210t014.eps</a><br><a href="#">eaton-contactors-contact-dimensions-210x202.eps</a><br><a href="#">eaton-contactors-mounting-dilm-dimensions.eps</a><br><a href="#">eaton-contactors-mounting-dilm-dimensions-002.eps</a><br><a href="#">eaton-contactors-dilm-3d-drawing-009.eps</a> |
| ECAD MODEL                 | <a href="#">ETN.112442.edz</a>                                                                                                                                                                                                                                                                                               |
| INSTALLATION INSTRUCTIONS  | <a href="#">IL03407014Z2021_09.pdf</a>                                                                                                                                                                                                                                                                                       |
| INSTALLATION VIDEOS        | <a href="#">WIN-WIN with push-in technology</a>                                                                                                                                                                                                                                                                              |
| MCAD MODEL                 | <a href="#">eaton-iec-contactors-mcad-drawings-dil-m17-38.dwg</a><br><a href="#">DA-CS-dil_m17_38</a>                                                                                                                                                                                                                        |
| PEP ECO-PASSPORT           | <a href="#">eaton-iec-contactors-pep-eato-00026-v0101-en.pdf</a><br><a href="#">eaton-iec-contactors-pep-eato-00134-v0101-en.pdf</a>                                                                                                                                                                                         |

|                 |                                                                     |
|-----------------|---------------------------------------------------------------------|
| SYSTEM OVERVIEW | <a href="#">eaton-contactors-dilm-contactor-system-overview.eps</a> |
| WIRING DIAGRAMS | <a href="#">eaton-contactors-contact-dilm-wiring-diagram.eps</a>    |

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

