

# Specifications



Photo is representative



## Eaton 112706

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 80A, plug-in module, B, frame 1, A80-SVE

### General specifications

|                             |                                                                      |
|-----------------------------|----------------------------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Moeller series NZM molded case circuit breaker thermo-magnetic |
| <b>CATALOG NUMBER</b>       | 112706                                                               |
| <b>MODEL CODE</b>           | NZMB1-A80-SVE                                                        |
| <b>EAN</b>                  | 4015081122561                                                        |
| <b>PRODUCT LENGTH/DEPTH</b> | 90 mm                                                                |
| <b>PRODUCT HEIGHT</b>       | 201 mm                                                               |
| <b>PRODUCT WIDTH</b>        | 95 mm                                                                |
| <b>PRODUCT WEIGHT</b>       | 1.201 kg                                                             |
| <b>COMPLIANCES</b>          | RoHS conform                                                         |
| <b>CERTIFICATIONS</b>       | IEC/EN 60947<br>IEC                                                  |

## Additional information

|                  |                             |
|------------------|-----------------------------|
| <b>FUNCTIONS</b> | System and cable protection |
|------------------|-----------------------------|

## Delivery programme

|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>ACCESSORIES REQUIRED</b>       | NZM1-XSVS                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>AMPERAGE RATING</b>            | 80 A                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>APPLICATION</b>                | Use in unearthed supply systems at 440 V                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>CIRCUIT BREAKER FRAME TYPE</b> | NZM1                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>FEATURES</b>                   | Protection unit                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>NUMBER OF POLES</b>            | Three-pole                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>RELEASE SYSTEM</b>             | Thermomagnetic release                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>SPECIAL FEATURES</b>           | <ul style="list-style-type: none"><li>• Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity <math>I_{cn}</math>)</li><li>• Rated current = rated uninterrupted current: 80 A</li><li>• Terminal capacity hint: Up to 95 mm<sup>2</sup> can be connected depending on the cable manufacturer.</li></ul> |
| <b>TYPE</b>                       | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                          |

## Design verification to IEC/EN 61439

|                                                                                         |                                                                                                                                  |
|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>10.10 TEMPERATURE RISE</b>                                                           | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| <b>10.11 SHORT-CIRCUIT RATING</b>                                                       | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>                                              | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| <b>10.13 MECHANICAL FUNCTION</b>                                                        | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |
| <b>10.2.2 CORROSION RESISTANCE</b>                                                      | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>                         | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>       | Meets the product standard's requirements.                                                                                       |
| <b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b> | Meets the product standard's requirements.                                                                                       |
| <b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>                                 | Meets the product standard's requirements.                                                                                       |
| <b>10.2.5 LIFTING</b>                                                                   | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.2.6 MECHANICAL IMPACT</b>                                                         | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.2.7 INSCRIPTIONS</b>                                                              | Meets the product standard's requirements.                                                                                       |
| <b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>                                          | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| <b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>                                           | Meets the product standard's requirements.                                                                                       |
| <b>10.5 PROTECTION</b>                                                                  | Does not apply, since the                                                                                                        |

## Design verification to IEC/EN 61439 - technical data

|                                                                      |         |
|----------------------------------------------------------------------|---------|
| <b>AMBIENT OPERATING TEMPERATURE - MAX</b>                           | 70 °C   |
| <b>AMBIENT STORAGE TEMPERATURE - MAX</b>                             | 70 °C   |
| <b>AMBIENT OPERATING TEMPERATURE - MIN</b>                           | -25 °C  |
| <b>AMBIENT STORAGE TEMPERATURE - MIN</b>                             | 40 °C   |
| <b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT</b>                 | 16.32 W |
| <b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b> | 80 A    |

|                                                                 |                                                                    |
|-----------------------------------------------------------------|--------------------------------------------------------------------|
| <b>AGAINST ELECTRIC SHOCK</b>                                   | entire switchgear needs to be evaluated.                           |
| <b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>   | Does not apply, since the entire switchgear needs to be evaluated. |
| <b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>        | Is the panel builder's responsibility.                             |
| <b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>                 | Is the panel builder's responsibility.                             |
| <b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>                 | Is the panel builder's responsibility.                             |
| <b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>                         | Is the panel builder's responsibility.                             |
| <b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b> | Is the panel builder's responsibility.                             |

## Technical data - electrical

|                                                                                        |                                                                                                      |
|----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>AMPERAGE RATING</b>                                                                 | 80 A                                                                                                 |
| <b>DIRECTION OF INCOMING SUPPLY</b>                                                    | As required                                                                                          |
| <b>ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT</b>                                      | Frame clamp                                                                                          |
| <b>HANDLE TYPE</b>                                                                     | Rocker lever                                                                                         |
| <b>INSTANTANEOUS CURRENT SETTING (II) - MAX</b>                                        | 800 A                                                                                                |
| <b>INSTANTANEOUS CURRENT SETTING (II) - MIN</b>                                        | 480 A                                                                                                |
| <b>ISOLATION</b>                                                                       | 300 V AC (between the auxiliary contacts)<br>500 V AC (between auxiliary contacts and main contacts) |
| <b>LIFESPAN, ELECTRICAL</b>                                                            | 7500 operations at 400 V AC-1<br>7500 operations at 415 V AC-1                                       |
| <b>NUMBER OF OPERATIONS PER HOUR - MAX</b>                                             | 120                                                                                                  |
| <b>OVERLOAD CURRENT SETTING (IR) - MAX</b>                                             | 80 A                                                                                                 |
| <b>OVERLOAD CURRENT SETTING (IR) - MIN</b>                                             | 63 A                                                                                                 |
| <b>OVERVOLTAGE CATEGORY</b>                                                            | III                                                                                                  |
| <b>POLLUTION DEGREE</b>                                                                | 3                                                                                                    |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT AUXILIARY CONTACTS</b>                    | 6000 V                                                                                               |
| <b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP) AT MAIN CONTACTS</b>                         | 6000 V                                                                                               |
| <b>RATED INSULATION VOLTAGE (UI)</b>                                                   | 690 V AC                                                                                             |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 230 V, 50/60 HZ</b>     | 30 kA                                                                                                |
| <b>RATED SHORT-CIRCUIT BREAKING CAPACITY ICS (IEC/EN 60947) AT 400/415 V, 50/60 HZ</b> | 25 kA                                                                                                |

## Technical data - mechanical

|                                                                |                                                                                                                                                                                                                                         |
|----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>CLIMATIC PROOFING</b>                                       | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30                                                                                                                                                          |
| <b>DEGREE OF PROTECTION</b>                                    | IP20 (basic degree of protection, in the operating controls area)<br>IP20                                                                                                                                                               |
| <b>DEGREE OF PROTECTION (IP), FRONT SIDE</b>                   | IP66 (with door coupling rotary handle)<br>IP40 (with insulating surround)                                                                                                                                                              |
| <b>DEGREE OF PROTECTION (TERMINATIONS)</b>                     | IP00 (terminations, phase isolator and strip terminal)<br>IP10 (tunnel terminal)                                                                                                                                                        |
| <b>LIFESPAN, MECHANICAL</b>                                    | 20000 operations                                                                                                                                                                                                                        |
| <b>MOUNTING METHOD</b>                                         | Plug-in unit<br>Built-in device plug-in technique<br>DIN rail (top hat rail)<br>mounting optional                                                                                                                                       |
| <b>NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)</b>     | 0                                                                                                                                                                                                                                       |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)</b> | 0                                                                                                                                                                                                                                       |
| <b>NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)</b>   | 0                                                                                                                                                                                                                                       |
| <b>POSITION OF CONNECTION FOR MAIN CURRENT CIRCUIT</b>         | Front side                                                                                                                                                                                                                              |
| <b>PROTECTION AGAINST DIRECT CONTACT</b>                       | Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110                                                                                                                                                                         |
| <b>SHOCK RESISTANCE</b>                                        | 20 g (half-sinusoidal shock 20 ms)                                                                                                                                                                                                      |
| <b>SPECIAL FEATURES</b>                                        | <ul style="list-style-type: none"> <li>Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity</li> </ul> |

|                                                                                                |                    |
|------------------------------------------------------------------------------------------------|--------------------|
| <b>RATED SHORT-CIRCUIT<br/>BREAKING CAPACITY ICS<br/>(IEC/EN 60947) AT 440 V,<br/>50/60 HZ</b> | 18.5 kA            |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 240 V, 50/60 HZ</b>                      | 63 kA              |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 400/415 V, 50/60 HZ</b>                  | 53 kA              |
| <b>RATED SHORT-CIRCUIT<br/>MAKING CAPACITY ICM<br/>AT 440 V, 50/60 HZ</b>                      | 53 kA              |
| <b>SHORT-CIRCUIT RELEASE<br/>NON-DELAYED SETTING -<br/>MAX</b>                                 | 800 A              |
| <b>SHORT-CIRCUIT RELEASE<br/>NON-DELAYED SETTING -<br/>MIN</b>                                 | 480 A              |
| <b>SHORT-CIRCUIT TOTAL<br/>BREAKTIME</b>                                                       | < 10 ms            |
| <b>UTILIZATION CATEGORY</b>                                                                    | A (IEC/EN 60947-2) |
| <b>VOLTAGE RATING</b>                                                                          | 440 V - 440 V      |

- 
- Icn)
- Rated current = rated uninterrupted current: 80 A
  - Terminal capacity hint: Up to 95 mm<sup>2</sup> can be connected depending on the cable manufacturer.
-

## Technical data - mechanical - terminals

|                                                              |                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>OPTIONAL TERMINALS</b>                                    | Connection on rear. Screw terminal. Tunnel terminal                                                                                                                                                                                                                                                                                                          |
| <b>STANDARD TERMINALS</b>                                    | Box terminal                                                                                                                                                                                                                                                                                                                                                 |
| <b>TERMINAL CAPACITY (ALUMINUM SOLID CONDUCTOR/CABLE)</b>    | 10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>10 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>16 mm <sup>2</sup> (1x) at tunnel terminal                                                                                                                                       |
| <b>TERMINAL CAPACITY (ALUMINUM STRANDED CONDUCTOR/CABLE)</b> | 25 mm <sup>2</sup> - 95 mm <sup>2</sup> (1x) at tunnel terminal<br>25 mm <sup>2</sup> - 35 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>25 mm <sup>2</sup> - 35 mm <sup>2</sup> (1x) direct at switch rear-side connection                                                                                                                  |
| <b>TERMINAL CAPACITY (CONTROL CABLE)</b>                     | 0.75 mm <sup>2</sup> - 1.5 mm <sup>2</sup> (2x)<br>0.75 mm <sup>2</sup> - 2.5 mm <sup>2</sup> (1x)                                                                                                                                                                                                                                                           |
| <b>TERMINAL CAPACITY (COPPER BUSBAR)</b>                     | Max. 16 mm x 5 mm direct at switch rear-side connection<br>Min. 12 mm x 5 mm direct at switch rear-side connection<br>M6 at rear-side screw connection                                                                                                                                                                                                       |
| <b>TERMINAL CAPACITY (COPPER SOLID CONDUCTOR/CABLE)</b>      | 10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>6 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>10 mm <sup>2</sup> - 16 mm <sup>2</sup> (1x) at box terminal<br>6 mm <sup>2</sup> - 16 mm <sup>2</sup> (2x) at box terminal<br>16 mm <sup>2</sup> (1x) at tunnel terminal         |
| <b>TERMINAL CAPACITY (COPPER STRANDED CONDUCTOR/CABLE)</b>   | 25 mm <sup>2</sup> - 95 mm <sup>2</sup> (1x) at 1-hole tunnel terminal<br>6 mm <sup>2</sup> - 25 mm <sup>2</sup> (2x) at box terminal<br>25 mm <sup>2</sup> (2x) direct at switch rear-side connection<br>10 mm <sup>2</sup> - 70 mm <sup>2</sup> (1x) direct at switch rear-side connection<br>10 mm <sup>2</sup> - 70 mm <sup>2</sup> (1x) at box terminal |
| <b>TERMINAL CAPACITY (COPPER STRIP)</b>                      | Max. 9 segments of 9 mm x 0.8 mm at box terminal                                                                                                                                                                                                                                                                                                             |

## Resources

|                                   |                                                                                                                                                                                                                        |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>BROCHURES</b>                  | <a href="#">eaton-digital-nzm-brochure-br013003en-en-us.pdf</a><br><a href="#">eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf</a>                                                                       |
| <b>CATALOGUES</b>                 | <a href="#">eaton-digital-nzm-catalog-ca013003en-en-us.pdf</a><br><a href="#">eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-038.eps</a>                                                 |
| <b>CHARACTERISTIC CURVE</b>       | <a href="#">eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-032.eps</a><br><a href="#">eaton-circuit-breaker-nzm-mccb-characteristic-curve-051.eps</a>                                    |
| <b>DECLARATIONS OF CONFORMITY</b> | <a href="#">eaton-molded-case-circuit-breaker-declaration-of-conformity-eu250289en.pdf</a><br><a href="#">eaton-molded-case-circuit-breaker-declaration-of-conformity-uk251450en.pdf</a>                               |
| <b>DRAWINGS</b>                   | <a href="#">eaton-circuit-breaker-nzm-mccb-dimensions-017.eps</a><br><a href="#">eaton-circuit-breaker-adapter-nzm-mccb-dimensions.eps</a><br><a href="#">eaton-circuit-breaker-switch-nzm-mccb-dimensions-014.eps</a> |
| <b>ECAD MODEL</b>                 | <a href="#">ETN.112706.edz</a>                                                                                                                                                                                         |
| <b>INSTALLATION INSTRUCTIONS</b>  | <a href="#">eaton-circuit-breaker-switch-disconnector-nzmb-il01203004z.pdf</a>                                                                                                                                         |
| <b>INSTALLATION VIDEOS</b>        | <a href="#">Introduction of the new digital circuit breaker NZM</a><br><a href="#">The new digital NZM Range</a>                                                                                                       |
| <b>MCAD MODEL</b>                 | <a href="#">eaton-molded-case-switches-mcad-3d-models-nzm1-xsve.stp</a><br><a href="#">DA-CD-nzm1_xsve</a>                                                                                                             |

---

Min. 2 segments of 9 mm  
x 0.8 mm at box terminal

---

---

[eaton-molded-case-  
switches-mcad-drawings-  
nzm1-xsve.dwg](#)

---

TECHNICAL DATA SHEETS

[eaton-nzm-technical-  
information-sheet](#)

---

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

