

Specifications



Photo is representative

Eaton 115391

Eaton Moeller series NZM - Molded Case Circuit Breaker. Remote operator, 208-240VAC, standard

General specifications

PRODUCT NAME	Eaton Moeller series NZM remote operator
CATALOG NUMBER	115391
MODEL CODE	NZM2-XRD208-240AC
EAN	4015081151233
PRODUCT LENGTH/DEPTH	150 mm
PRODUCT HEIGHT	105 mm
PRODUCT WIDTH	105 mm
PRODUCT WEIGHT	1.25 kg
COMPLIANCES	CE Marked UL/CSA IEC RoHS conform
CERTIFICATIONS	IEC 60947 UL 489 UL listed CSA-C22.2 No. 5-09 CE marking CSA (File No. 22086) UL489 CSA certified UL (Category Control Number DIHS) CSA (Class No. 1437-01) UL (File No. E140305)



Powering Business Worldwide

Delivery programme

FRAME	NZM2
NUMBER OF POLES	Three-pole/Four-pole
SPECIAL FEATURES	• Sliding switch for "Auto" or "Manual" • Max. number auxiliary contacts: 2 standard auxiliary contacts, 1 trip-indicating auxiliary switches • Cannot be combined with switch-disconnector PN... • Cannot be combined with mechanical interlock • Do not install M22-CK11(20/02) dual auxiliary contacts in the center auxiliary contact slot in NZM2-XRD
TYPE	• Accessory • Remote operator, standard
USED WITH	N(S)2(-4) NZM2(-4)

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

BREAKING TIME	110 ms - 170 ms
CLOSING DELAY	110 ms - 170 ms
NUMBER OF OPERATIONS PER HOUR - MAX	120
OPERATING VOLTAGE - MAX	1.1 x Us
OPERATING VOLTAGE - MIN	0.85 x Us
POWER CONSUMPTION	550 VA (110 - 130 V AC)
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	208 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	208 V
RATED OPERATING FREQUENCY	50 Hz
SIGNAL DURATION OF REMOTE OPERATOR AT SWITCH OFF - MIN	100 ms
SIGNAL DURATION OF REMOTE OPERATOR AT SWITCH ON - MIN	100 ms
VOLTAGE RATING	208 - 240 V 50/60 Hz
VOLTAGE TOLERANCE - MAX	1.1
VOLTAGE TOLERANCE - MIN	0.85
VOLTAGE TYPE	AC

Technical data - mechanical - terminals

TERMINAL CAPACITY (SOLID/FLEXIBLE CONDUCTOR)	0.75 mm ² - 2.5 mm ² with ferrule 18 - 14 AWG
---	--

Technical data - mechanical

LIFESPAN, MECHANICAL	20000 operations
-----------------------------	------------------

SPECIAL FEATURES

- Sliding switch for "Auto" or "Manual"
- Max. number auxiliary contacts: 2 standard auxiliary contacts, 1 trip-indicating auxiliary switches
- Cannot be combined with switch-disconnector PN...
- Cannot be combined with mechanical interlock
- Do not install M22-CK11(20/02) dual auxiliary contacts in the center auxiliary contact slot in NZM2-XRD

SWITCH DRIVE TYPE	Motor drive
--------------------------	-------------

Resources

BROCHURES

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

CATALOGUES

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

DECLARATIONS OF CONFORMITY	eaton-accessories-declaration-of-conformity-eu250143en.pdf eaton-accessories-declaration-of-conformity-uk251459en.pdf
DRAWINGS	eaton-circuit-breaker-remote-operator-nzm-remote-operator-dimensions.eps eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps
ECAD MODEL	ETN.115391.edz
INSTALLATION INSTRUCTIONS	eaton-remote-operation-directly-nzm2-xrd-il01219025z.pdf
INSTALLATION VIDEOS	The new digital NZM Range Introduction of the new digital circuit breaker NZM
MCAD MODEL	eaton-remote-operators-mcad-drawings-nzm2-xr.dwg DA-CS-nzm2_xr
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

