

Specifications

Eaton 116632

Eaton xEnergy Basic LV systems Low voltage switchgear. Surface-mount service distribution board with three-point turn-lock, fire-resistant, W 400 mm H 460 mm, white

General specifications

PRODUCT NAME	Eaton xEnergy Basic small distribution board
CATALOG NUMBER	116632
MODEL CODE	BP-O-400/4-EW-W
EAN	4015081163779
PRODUCT LENGTH/DEPTH	262 mm
PRODUCT HEIGHT	460 mm
PRODUCT WIDTH	400 mm
PRODUCT WEIGHT	15 kg
COMPLIANCES	RoHS conform



Powering Business Worldwide

Additional information

FEATURES	EMC-version
FIRE RESISTANCE GRADE	Fire-resistant (E60/EW60)
FUNCTIONS	Basic device Extension possible Sealable
RAL-NUMBER	9016

Delivery programme

APPLICATION	Indoor (installation site)
COLOR	White Traffic white (RAL 9016)
TYPE	Basic device

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Not relevant to indoor installations.
10.2.5 LIFTING	Does not apply to enclosures without lifting aids.
10.2.6 MECHANICAL IMPACT	IK08
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP30
10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	< 0.1 Ω; meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR	Is the panel builder's

Technical data - mechanical

BUILT-IN HEIGHT	490 mm
BUILT-IN WIDTH	430 mm
CLOSURE TYPE	Other
COVER/DOOR MODEL	Closed
COVER/DOOR TYPE	Three-point turn-lock Door Single
ENCLOSURE MATERIAL	Steel
INTERNAL DEPTH	257.5 mm
MATERIAL	Sheet steel
MOUNTING METHOD	Surface mounting Surface mounted (plaster)
NUMBER OF ROWS	2
SURFACE FINISHING	With powder coating
WIDTH IN NUMBER OF MODULAR SPACINGS	13
BUILT-IN DEPTH	300 mm
DEGREE OF PROTECTION	IP30

EXTERNAL CONDUCTORS	responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Ui = 440 V AC
10.9.3 IMPULSE WITHSTAND VOLTAGE	4 kV
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Does not apply to metal enclosures.

Temperature-rise verification as per IEC 60890

HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	33 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	67 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	39 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	36 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	78 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	73 W

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:

Resources

BROCHURES	eaton-xenergy-basic-light-brochure-br014024-en-us.pdf
CATALOGUES	eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-small-distribution-board-declaration-of-conformity-eu250305en.pdf
DRAWINGS	eaton-low-voltage-switch-gear-dimensions-1230dim-434.eps
FLYERS	eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf
MANUALS AND USER GUIDES	DA-MN-170900094
MCAD MODEL	eaton-empty-consumer-units-mcad-3d-models-bp-o-400-4-ew-w.stp
SALES NOTES	eaton-f3a-flange-flyer-fl019005en-en-us.pdf



Eaton Corporation plc Eaton House
 30 Pembroke Road
 Dublin 4, Ireland
 Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

