

Specifications

Eaton 118855



Eaton Moeller® series DILM Cover,
connection opening DILM17-38, (8unit)

General specifications

PRODUCT NAME	Eaton Moeller® series DILM terminal cover
CATALOG NUMBER	118855
MODEL CODE	DILM32-XIP2X
EAN	4015081170043
PRODUCT LENGTH/DEPTH	7 mm
PRODUCT HEIGHT	36 mm
PRODUCT WIDTH	34 mm
PRODUCT WEIGHT	0.006 kg
CERTIFICATIONS	UL/CSA certification not required

Climatic environmental conditions

**AMBIENT OPERATING
TEMPERATURE - MAX** 60 °C

**AMBIENT OPERATING
TEMPERATURE - MIN** -25 °C

Design verification

10.10 TEMPERATURE RISE Not applicable.

**10.11 SHORT-CIRCUIT
RATING** Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC
COMPATIBILITY** Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL
FUNCTION** The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

**10.2.2 CORROSION
RESISTANCE** Meets the product standard's requirements.

**10.2.3.1 VERIFICATION OF
THERMAL STABILITY OF
ENCLOSURES** Meets the product standard's requirements.

**10.2.3.2 VERIFICATION OF
RESISTANCE OF
INSULATING MATERIALS
TO NORMAL HEAT** Meets the product standard's requirements.

**10.2.3.3 RESIST. OF
INSUL. MAT. TO
ABNORMAL HEAT/FIRE
BY INTERNAL ELECT.
EFFECTS** Meets the product standard's requirements.

**10.2.4 RESISTANCE TO
ULTRA-VIOLET (UV)
RADIATION** Meets the product standard's requirements.

10.2.5 LIFTING Does not apply, since the entire switchgear needs to be evaluated.

**10.2.6 MECHANICAL
IMPACT** Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS Meets the product standard's requirements.

**10.3 DEGREE OF
PROTECTION OF
ASSEMBLIES** Does not apply, since the entire switchgear needs to be evaluated.

**10.4 CLEARANCES AND
CREEPAGE DISTANCES** Meets the product standard's requirements.

**10.5 PROTECTION
AGAINST ELECTRIC
SHOCK** Does not apply, since the entire switchgear needs to be evaluated.

**10.6 INCORPORATION OF
SWITCHING DEVICES AND
COMPONENTS** Does not apply, since the entire switchgear needs to be evaluated.

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

General information

ACCESSORY/SPARE PART TYPE

Cover

PRODUCT CATEGORY

Accessories

USED WITH

DILM17
DILM25
DILM32
DILM38
DILMP32
DILMP45
DILL...
DILMF8
DILMF11
DILMF14
DILMF17
DILMF25
DILMF32

Resources

CATALOGUES

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](https://www.eaton.com/content/dam/eaton/products/machinery-catalogue-ca08103003zen-en-us.pdf)

[Product Range Catalog Switching and protecting motors](#)

[SmartWire-DT Catalog](#)

DRAWINGS

[eaton-contactors-dilm-terminal-cover-3d-drawing-002.eps](#)

ECAD MODEL

[ETN.118855.edz](#)

INSTALLATION INSTRUCTIONS

[IL03406008Z](#)

INSTALLATION VIDEOS

[WIN-WIN with push-in technology](#)

MCAD MODEL

[eaton-accessories-mcad-drawings-dilm32-xip2x.dwg](#)

[DA-CS-dilm32_xip2x](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

