

# Specifications



## Eaton 119321

Eaton xEnergy Basic LV systems Low voltage switchgear. Mounting insert with steel front plates HxW=1949x800mm, 9 rows

### General specifications

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| <b>PRODUCT NAME</b>             | Eaton xEnergy Basic<br>installation component |
| <b>CATALOG NUMBER</b>           | 119321                                        |
| <b>MODEL CODE</b>               | BPZ-MES-800/20-ST                             |
| <b>EAN</b>                      | 4015081174584                                 |
| <b>PRODUCT<br/>LENGTH/DEPTH</b> | 130 mm                                        |
| <b>PRODUCT HEIGHT</b>           | 1949 mm                                       |
| <b>PRODUCT WIDTH</b>            | 720 mm                                        |
| <b>PRODUCT WEIGHT</b>           | 21 kg                                         |
| <b>COMPLIANCES</b>              | RoHS conform                                  |

## Additional information

|                   |                      |
|-------------------|----------------------|
| <b>FUNCTIONS</b>  | Additional equipment |
| <b>RAL-NUMBER</b> | 7035                 |

## Technical data - mechanical

|                                               |                                   |
|-----------------------------------------------|-----------------------------------|
| <b>HOUSING MATERIAL</b>                       | Sheet steel                       |
| <b>MATERIAL</b>                               | Metal                             |
| <b>MOUNTING METHOD</b>                        | Floor standing distribution board |
| <b>NUMBER OF ROWS</b>                         | 9                                 |
| <b>SUITABLE FOR ENCLOSURE BUILDING WIDTH</b>  | 800 mm                            |
| <b>SUITABLE FOR HEIGHT</b>                    | 2060 mm                           |
| <b>SUITABLE FOR WIDTH</b>                     | 800 mm                            |
| <b>SUITABLE FOR ENCLOSURE BUILDING HEIGHT</b> | 1949 mm                           |

## Delivery programme

|              |                      |
|--------------|----------------------|
| <b>COLOR</b> | Gray                 |
| <b>MODEL</b> | Swing frame          |
| <b>TYPE</b>  | Additional equipment |

## Resources

|                    |                                                                                      |
|--------------------|--------------------------------------------------------------------------------------|
| <b>BROCHURES</b>   | <a href="#">eaton-xenergy-basic-light-brochure-br014024-en-us.pdf</a>                |
| <b>CATALOGUES</b>  | <a href="#">eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf</a> |
| <b>FLYERS</b>      | <a href="#">eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf</a>             |
| <b>SALES NOTES</b> | <a href="#">eaton-f3a-flange-flyer-fl019005en-en-us.pdf</a>                          |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

