

Specifications



Eaton 119868

Eaton Moeller series NZM - Molded Case Circuit Breaker. Cover, 3p, for cable lugs, size 2

General specifications

PRODUCT NAME	Eaton Moeller series NZM connection type NA
CATALOG NUMBER	119868
MODEL CODE	NZM2-XKSAE
EAN	4015081177196
PRODUCT LENGTH/DEPTH	93 mm
PRODUCT HEIGHT	62 mm
PRODUCT WIDTH	62 mm
PRODUCT WEIGHT	0.102 kg
COMPLIANCES	IEC UL/CSA RoHS conform

Additional information

PHASE SEPARATOR TYPE	Other
-----------------------------	-------

Delivery programme

FRAME	NZM2
NUMBER OF POLES	Three-pole
TYPE	Terminal cover
USED WITH	NZM2, PN2, NS2

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Technical data - mechanical - terminals

TERMINAL CAPACITY (ALUMINUM CONDUCTOR)	10 mm ² - 50 mm ² (1x) 10 mm ² - 50 mm ² (2x)
TERMINAL CAPACITY (COPPER CONDUCTOR)	4 mm ² - 70 mm ² (2x) 10 mm ² - 185 mm ² (1x)

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker-cover-nzm-cable-lug-cover-dimensions.eps eaton-circuit-breaker-cable-nzm-cable-lug-cover-3d-drawing.eps
INSTALLATION INSTRUCTIONS	eaton-circuit-breakers-nzm2-3-xksae-cable-lug-cover-instruction-leaflet-il01219044z.pdf
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range
MCAD MODEL	DA-CS-nzm2_xksae eaton-mccb-terminal-accessories-mcad-drawings-nzm2-xksae.dwg
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

