

Specifications



Eaton 121721

Eaton Moeller® series PKE12 Circuit-breaker, Basic device with standard knob, 12 A, Without overload releases, Screw terminals

General specifications

PRODUCT NAME	Eaton Moeller® series PKE Motor-protective circuit-breaker
CATALOG NUMBER	121721
MODEL CODE	PKE12
EAN	4015081195312
PRODUCT LENGTH/DEPTH	101 mm
PRODUCT HEIGHT	102.5 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.33 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	UL 508 IEC 60947-4-1 EN 60947-4-1 CSA Std. C22.2 No. 14-10 VDE CE CSA Class No.: 3211-05 VDE 0660 CSA CSA-C22.2 No. 60947-4-1-14 UL 60947-4-1 UL File No.: E36332 IEC/EN 60947-4-1 UL UL Category Control No.: NLRV CSA File No.: 165628 IEC/EN 60947



Powering Business Worldwide

Ambient conditions, mechanical

SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms
-------------------------	---

Communication

CONNECTION	Screw terminals
-------------------	-----------------

Climatic environmental conditions

ALTITUDE	Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS	Meets the product standard's requirements.

TO NORMAL HEAT	
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	2.7 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0.9 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	12 A

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
---	-----

Electrical rating

RATED FREQUENCY - MAX	60 Hz
RATED FREQUENCY - MIN	50 Hz
RATED OPERATIONAL CURRENT (IE)	12 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
RATED OPERATIONAL VOLTAGE (UE) - MIN	690 V
RATED UNINTERRUPTED CURRENT (IU)	12 A

Features & functions

ACTUATOR TYPE	Turn button
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FITTED WITH:	Standard knob
FUNCTIONS	Motor protection Motor protection for heavy starting duty
NUMBER OF POLES	Three-pole

General information

DEGREE OF PROTECTION	IP20 Terminals: IP00
LIFESPAN, ELECTRICAL	50,000 operations (at 400V, AC-3)
LIFESPAN, MECHANICAL	50,000 Operations (Main conducting paths)
OPERATING FREQUENCY	60 Operations/h
OVERLOAD RELEASE CURRENT SETTING - MAX	0 A
OVERLOAD RELEASE CURRENT SETTING - MIN	0 A
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Motor protective circuit breaker
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SUITABLE FOR	Also motors with efficiency class IE3
TEMPERATURE COMPENSATION	-5 - 40 °C to IEC/EN 60947, VDE 0660 -25 - 55 °C, Operating range

Switching capacity

SWITCHING CAPACITY	12 A, AC-3 up to 690 V
---------------------------	------------------------

Short-circuit rating

SHORT-CIRCUIT RELEASE	Basic device fixed 15.5 x lu, Trip Blocks ± 20% tolerance, Trip blocks
------------------------------	---

Terminal capacities

STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (1 - 6) mm ² , ferrule to DIN 46228 2 x (1 - 6) mm ² , ferrule to DIN 46228
TERMINAL CAPACITY (SOLID)	1 x (1 - 6) mm ² 2 x (1 - 6) mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	14 - 10
TIGHTENING TORQUE	1 Nm, Screw terminals, Control circuit cables 1.7 Nm, Screw terminals, Main cable

Resources

BROCHURES	eaton-motor-protective-circuit-breaker-pke-and-communication-modul-pke-brochure-w12107613en-en-us.pdf
	eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf
CATALOGUES	Product Range Catalog Switching and protecting motors
	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-manual-motor-starters-pke65-characteristic-curve.eps
	eaton-manual-motor-starters-pke65-characteristic-curve-005.eps
	eaton-manual-motor-starters-pke65-characteristic-curve-003.eps
DECLARATIONS OF CONFORMITY	eaton-motor-protective-circuit-breaker-declaration-of-conformity-uk251179en.pdf
	eaton-motor-protective-circuit-breaker-declaration-of-conformity-eu250696en.pdf
DRAWINGS	eaton-manual-motor-starters-dimensions-002.eps
	eaton-manual-motor-starters-pke32-mccb-3d-drawing.eps
	eaton-general-ie-ready-dilm-contactor-standards.eps
	eaton-manual-motor-starters-mounting-3d-drawing.eps
ECAD MODEL	ETN.121721.edz
INSTALLATION INSTRUCTIONS	eaton-trip-block-pke-xtu-for-pke12-pke32-il034011zu.pdf

	IL034003ZU
	eaton-motor-protective-circuit-breaker-pke-il03402019z.pdf
INSTALLATION VIDEOS	WIN-WIN with push-in technology Video Motor Protective Circuit Breaker PKE
MANUALS AND USER GUIDES	eaton-motor-protection-pke12-32-65-mn03402004z-de-de-en-us.pdf
MCAD MODEL	eaton-breakers-mcad-drawings-pke12.dwg pke12.stp
SALES NOTES	eaton-pke-modbus-rtu-modul-flyer-fl034008en-en-us.pdf

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

