

Specifications



Photo is representative

Eaton 121734

Eaton Moeller® series PKE32 Motor-protective circuit-breaker, Complete device with standard knob, Electronic, 8 - 32 A, 32 A, With overload release, Screw terminals

General specifications

PRODUCT NAME	Eaton Moeller® series PKE System-protective circuit-breaker
CATALOG NUMBER	121734
MODEL CODE	PKE32/XTU-32
EAN	4015081195442
PRODUCT LENGTH/DEPTH	101 mm
PRODUCT HEIGHT	102.5 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.436 kg
CERTIFICATIONS	CE CSA IEC/EN 60947-4-1 IEC/EN 60947 CSA Class No.: 3211-05 CSA File No.: 165628 CSA-C22.2 No. 60947-4-1-14 UL UL File No.: E36332 UL Category Control No.: NLRV VDE 0660 UL 60947-4-1
CATALOG NOTES	This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures.

Ambient conditions, mechanical

SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27, Half- sinusoidal shock 10 ms
-------------------------	---

Communication

CONNECTION	Screw terminals
-------------------	-----------------

Climatic environmental conditions

ALTITUDE	Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS	Meets the product standard's requirements.

TO NORMAL HEAT	
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	11.4 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	3.8 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	32 A

STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
--	-----

Electrical rating

RATED FREQUENCY - MAX	60 Hz
RATED FREQUENCY - MIN	50 Hz
RATED OPERATIONAL CURRENT (IE)	32 A
RATED OPERATIONAL POWER AT AC-3E, 220/230 V, 50 HZ	7.5 kW
RATED OPERATIONAL POWER AT AC-3E, 380/400 V, 50 HZ	15 kW
RATED OPERATIONAL POWER AT AC-3E, 440 V, 50 HZ	15 kW
RATED OPERATIONAL POWER AT AC-3E, 500 V, 50 HZ	18.5 kW
RATED OPERATIONAL POWER AT AC-3E, 690 V, 50 HZ	30 kW
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
RATED OPERATIONAL VOLTAGE (UE) - MIN	690 V
RATED UNINTERRUPTED CURRENT (IU)	32 A

Features & functions

ACTUATOR TYPE	Turn button
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FITTED WITH:	Standard knob
FUNCTIONS	Motor protection for heavy starting duty Motor protection Overload release
NUMBER OF POLES	Three-pole

General information

CURRENT FLOW TIMES - MIN

700 (Class 10) AC-4 cycle operation, Main conducting paths
900 (Class 15) AC-4 cycle operation, Main conducting paths
For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.
500 (Class 5) AC-4 cycle operation, Main conducting paths
1000 (Class 20) AC-4 cycle operation, Main conducting paths
Note: Going below the minimum current flow time can cause overheating of the load (motor).

CUT-OUT PERIODS - MIN

≤ 500 ms, main conducting paths, AC-4 cycle operation

DEGREE OF PROTECTION

Terminals: IP00
IP20

LIFESPAN, ELECTRICAL

50,000 operations (at 400V, AC-3)

LIFESPAN, MECHANICAL

50,000 Operations (Main conducting paths)

OPERATING FREQUENCY

60 Operations/h

OVERLOAD RELEASE CURRENT SETTING - MAX

32 A

OVERLOAD RELEASE CURRENT SETTING - MIN

32 A

OVERVOLTAGE CATEGORY

III

POLLUTION DEGREE

3

PRODUCT CATEGORY

Motor protective circuit breaker

PROTECTION

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)

6000 V AC

RESISTANCE PER POLE

2.5 mΩ

SUITABLE FOR

Also motors with efficiency

Motor rating

ASSIGNED MOTOR

POWER AT 115/120 V, 60 HZ, 1-PHASE 1.5 HP

ASSIGNED MOTOR

POWER AT 200/208 V, 60 HZ, 3-PHASE 5 HP

ASSIGNED MOTOR

POWER AT 230/240 V, 60 HZ, 1-PHASE 3 HP

ASSIGNED MOTOR

POWER AT 230/240 V, 60 HZ, 3-PHASE 7.5 HP

ASSIGNED MOTOR

POWER AT 460/480 V, 60 HZ, 3-PHASE 15 HP

ASSIGNED MOTOR

POWER AT 575/600 V, 60 HZ, 3-PHASE 20 HP

	class IE3
TEMPERATURE COMPENSATION	-25 - 55 °C, Operating range -5 - 40 °C to IEC/EN 60947, VDE 0660

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (GROUP PROTECTION)	100 kA, 600 V High Fault, Fuse, SCCR (UL/CSA) 100 A, Class J, 600 V High Fault, max. Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT RELEASE	Trip block fixed 15.5 x Ir Delayed approx. 60 ms, Trip blocks Basic device fixed 15.5 x Iu, Trip Blocks ± 20% tolerance, Trip blocks

Terminal capacities

STRIPPING LENGTH (MAIN CABLE)	10 mm
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (1 - 6) mm ² , ferrule to DIN 46228 2 x (1 - 6) mm ² , ferrule to DIN 46228
TERMINAL CAPACITY (SOLID)	2 x (1 - 6) mm ² 1 x (1 - 6) mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	14 - 10
TIGHTENING TORQUE	1.7 Nm, Screw terminals, Main cable 1 Nm, Screw terminals, Control circuit cables

Switching capacity

SWITCHING CAPACITY	32 A, General use UL/CSA 32 A, AC-3 up to 690 V
---------------------------	--

Resources

BROCHURES	eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf
	eaton-motor-protective-circuit-breaker-pke-and-communication-modul-pke-brochure-w12107613en-en-us.pdf
CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-manual-motor-starters-pke65-characteristic-curve-003.eps
	eaton-manual-motor-starters-pke65-characteristic-curve.eps
	eaton-manual-motor-starters-pke65-characteristic-curve-005.eps
DECLARATIONS OF CONFORMITY	eaton-system-protective-circuit-breaker-declaration-of-conformity-eu250694en.pdf
	eaton-system-protective-circuit-breaker-declaration-of-conformity-uk251177en.pdf

DRAWINGS	eaton-manual-motor-starters-dimensions-002.eps
	eaton-general-ie-ready-dilm-contactor-standards.eps
	eaton-manual-motor-starters-3d-drawing-002.eps
	eaton-manual-motor-starters-mounting-3d-drawing.eps
ECAD MODEL	ETN.121734.edz
INSTALLATION INSTRUCTIONS	eaton-motor-protective-circuit-breaker-pke-il03402019z.pdf
	eaton-trip-block-pke-xtu-for-pke12-pke32-il034011zu.pdf
	IL034003ZU
INSTALLATION VIDEOS	WIN-WIN with push-in technology
	Video Motor Protective Circuit Breaker PKE
MANUALS AND USER GUIDES	eaton-motor-protection-pke12-32-65-mn03402004z-de-de-en-us.pdf
MCAD MODEL	DA-CS-pke12_xtu
	eaton-breakers-mcad-drawings-pke12-xtu.dwg
SALES NOTES	eaton-pke-modbus-rtu-modul-flyer-fl034008en-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

