

Specifications



Eaton 121743

Eaton Moeller® series MSC-DE DOL starter, 380 V 400 V 415 V: 5.5 kW, I_q= 100 kA, I_r= 3 - 12 A, 230 V 50 Hz, 240 V 60 Hz, AC voltage, Screw terminals MSC-DE-12-M12(230V50HZ)

General specifications

PRODUCT NAME	Eaton Moeller® series MSC-DE DOL starter
CATALOG NUMBER	121743
MODEL CODE	MSC-DE-12-M12(230V50HZ)
EAN	4015081195534
PRODUCT LENGTH/DEPTH	102 mm
PRODUCT HEIGHT	198 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.724 kg
CERTIFICATIONS	VDE 0660 IEC/EN 60947-4-1

Climatic environmental conditions

ALTITUDE	Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	4.2 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.4 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	12 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	1.4 W

Electrical rating

RATED OPERATIONAL CURRENT (IE) 11.3 A

RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V 12 A

RATED OPERATIONAL POWER AT AC-3, 220/230 V, 50 HZ 3 kW

RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ 5.5 kW

RATED OPERATIONAL VOLTAGE 230 - 415 V AC

Features & functions

FITTED WITH: Short-circuit release

FUNCTIONS Temperature compensated overload protection

General information

CLASS	Adjustable
CONNECTION	Screw terminals
CONNECTION TO SMARTWIRE-DT	No
COORDINATION TYPE	1
CURRENT FLOW TIMES - MIN	1000 (Class 20) AC-4 cycle operation, Main conducting paths Note: Going below the minimum current flow time can cause overheating of the load (motor). 900 (Class 15) AC-4 cycle operation, Main conducting paths For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods. 500 (Class 5) AC-4 cycle operation, Main conducting paths 700 (Class 10) AC-4 cycle operation, Main conducting paths
CUT-OUT PERIODS - MIN	≤ 500 ms, main conducting paths, AC-4 cycle operation
DEGREE OF PROTECTION	IP20 NEMA Other
MODEL	IEC starter
MOUNTING METHOD	DIN rail
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	1
OVERLOAD RELEASE CURRENT SETTING - MAX	12 A
OVERLOAD RELEASE CURRENT SETTING - MIN	3 A
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC

Magnet system

POWER CONSUMPTION, SEALING, 50 HZ	1.4 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz
--	---

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	230 V
---	-------

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	230 V
---	-------

SUITABLE FOR	Also motors with efficiency class IE3
TYPE	Starter with electronic trip unit
VOLTAGE TYPE	AC

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	35 A, Class J, max. Fuse, SCCR (UL/CSA) 100 kA, Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT RELEASE (IRM) - MAX	186 A

Resources

BROCHURES	eaton-msfs-motor-starter-feeder-system-brochure-br034005en-en-us.pdf eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf
CATALOGUES	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-dol-starter-declaration-of-conformity-uk251161en.pdf eaton-dol-starter-declaration-of-conformity-eu250678en.pdf
DRAWINGS	eaton-manual-motor-starters-starter-msc-d-dol-starter-dimensions-002.eps eaton-manual-motor-starters-starter-msc-d-dol-starter-3d-drawing.eps eaton-manual-motor-starters-mounting-msc-d-dol-starter-3d-drawing.eps eaton-general-ie-ready-dilm-contactor-standards.eps
ECAD MODEL	ETN.121743.edz
INSTALLATION INSTRUCTIONS	eaton-direct-on-line-starter-up-to-15a-il034038zu.pdf
INSTALLATION VIDEOS	WIN-WIN with push-in technology
MCAD MODEL	eaton-motor-starter-mcad-drawings-msc-de-bg1.dwg DA-CS-msc_de_bg1
SALES NOTES	eaton-link-module-for-motor-starters-pkz-flyer-fl034003en-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

