

Specifications



Eaton 125076

Eaton SPX Field bus module BACnet MS/TP RS485 with screw terminals for frequency converter SVX and SPX

General specifications

PRODUCT NAME	Eaton SPX Accessory Fieldbus module
CATALOG NUMBER	125076
MODEL CODE	OPTCJ
EAN	4015081226870
PRODUCT LENGTH/DEPTH	39 mm
PRODUCT HEIGHT	6 mm
PRODUCT WIDTH	22 mm
PRODUCT WEIGHT	0.2 kg
CERTIFICATIONS	Certified by UL for use in Canada IEC/EN61800-5 UL report applies to both US and Canada UL Category Control No.: NMMS, NMMS2, NMMS7, NMMS8 CSA-C22.2 No. 14 UL 508C IEC/EN61800-3 CE UL File No.: E134360 UL
CATALOG NOTES	The field bus module is plugged into the variable- frequency drive.

Communication

PROTOCOL

BACnet MS/TP

Design verification

10.10 TEMPERATURE RISE

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 MECHANICAL FUNCTION

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 CORROSION RESISTANCE

Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES

Meets the product standard's requirements.

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT

Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS

Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION

Meets the product standard's requirements.

10.2.5 LIFTING

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS

Meets the product standard's requirements.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 CLEARANCES AND CREEPAGE DISTANCES

Meets the product standard's requirements.

10.6 INCORPORATION OF

Does not apply, since the

SWITCHING DEVICES AND COMPONENTS	entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

General information

CONNECTION TYPE	Screw terminals
PRODUCT CATEGORY	Accessories
SUITABLE FOR	Branch circuits, (UL/CSA)

Resources

APPLICATION NOTES	eaton-9000x-spi-common-dc-bus-selection-ap040044-en-us.pdf Electromagnetic compatibility (EMC)
CATALOGUES	eaton-drives-soft-starter-catalog-ca04020001zen-us.pdf
DECLARATIONS OF CONFORMITY	eaton-accessory-declaration-of-conformity-uk251333en.pdf eaton-accessory-declaration-of-conformity-eu250850en.pdf
DRAWINGS	eaton-regulating-equipment-options-spx-output-expansion-3d-drawing.eps
INSTALLATION INSTRUCTIONS	IL040054ZU IL04012011Z2021_04.pdf
MULTIMEDIA	Eaton variable frequency drives - Demand more innovation Eaton variable frequency drives - Demand more expertise How does a VFD work to save energy and money? Eaton variable frequency drives - Demand more than good enough

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

