

Specifications



Eaton 125272

Eaton SPX Variable frequency drive, 600 V AC, 3-phase, 11 kW, IP54, Radio interference suppression filter, OLED display, FR6

General specifications

PRODUCT NAME	Eaton SPX variable frequency drive
CATALOG NUMBER	125272
MODEL CODE	SPX010A2-5A4N1
EAN	4015081228782
PRODUCT LENGTH/DEPTH	237 mm
PRODUCT HEIGHT	558 mm
PRODUCT WIDTH	195 mm
PRODUCT WEIGHT	18.5 kg

CUL
UL
IEC/EN61800-5
UL File No.: E134360
IEC/EN 61800-3
IEC/EN61800-3
UL 508C
CE
CSA Class No.: 3211-06
CSA-C22.2 No. 14
Safety: EN 61800-5-1: 2003

CERTIFICATIONS

UL Category Control No.:
NMMS, NMMS2, NMMS7.
NMMS8
UL report applies to both
US and Canada
Certified by UL for use in
Canada
RCM
RoHS, ISO 9001
DNV
Specification for general
requirements: IEC/EN
61800-2

Climatic environmental conditions

ALTITUDE	Max. 1000 m Max. 3000 m Above 1000 m with 1 % performance reduction per 100 m
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-10 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MAX	50 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MIN	-10 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CLIMATIC PROOFING	< 95 % relative humidity, no condensation, no corrosion, no dripping water

Control circuit

NUMBER OF INPUTS (ANALOG)	2 (parameterizable, 0 - 10 V DC, 0/4 - 20 mA)
NUMBER OF INPUTS (DIGITAL)	6 (parameterizable, max. 30 V DC)
NUMBER OF OUTPUTS (ANALOG)	1
NUMBER OF OUTPUTS (DIGITAL)	1 (parameterizable, 48 V DC/50 mA)
NUMBER OF RELAY OUTPUTS	2 (parameterizable, N/O, 8 A (24 V DC) / 8 A (250 V AC) / 0,4 A (125 V DC))
RATED CONTROL VOLTAGE (UC)	24 V DC (external, max. 250 mA)

Communication

COMMUNICATION INTERFACE	LonWorks, optional PROFIBUS-DP DeviceNet, optional CANopen®, optional BACnet/IP, optional Modbus-TCP, optional BACnet MS/TP, optional EtherCAT, optional Ethernet IP, optional Modbus-RTU, optional PROFINET, optional
CONNECTION TO SMARTWIRE-DT	No

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF	Meets the product standard's requirements.

ENCLOSURES	
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	275 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION DETAILS	Operation (with 150 % overload)
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	13.5 A
--	--------

STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
--	-----

General information

DEGREE OF PROTECTION	IP54 NEMA Other
-----------------------------	--------------------

ELECTROMAGNETIC COMPATIBILITY	1st and 2nd environments (according to EN 61800-3)
--	---

FITTED WITH:	Internal DC link OLED display DC link choke Radio interference suppression filter IGBT inverter
---------------------	--

FRAME SIZE	FR6
-------------------	-----

MOUNTING POSITION	Vertical
--------------------------	----------

PRODUCT CATEGORY	Variable frequency drives
-------------------------	---------------------------

PROTECTION	Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
-------------------	--

RADIO INTERFERENCE CLASS	C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
-------------------------------------	--

SUITABLE FOR	Branch circuits, (UL/CSA)
---------------------	---------------------------

Main circuit

MAINS VOLTAGE - MAX	690 V
----------------------------	-------

MAINS VOLTAGE - MIN	525 V
----------------------------	-------

OPERATING MODE	Sensorless vector control (SLV) U/f control Optional: Vector control with feedback (CLV)
-----------------------	--

OUTPUT FREQUENCY - MAX	320 Hz
-----------------------------------	--------

OUTPUT FREQUENCY - MIN	0 Hz
-----------------------------------	------

OUTPUT VOLTAGE (U2)	690 V AC, 3-phase 600 V AC, 3-phase
----------------------------	--

RATED CONTROL SUPPLY VOLTAGE	10 V DC (Us, max. 10 mA)
---	--------------------------

RATED FREQUENCY - MAX	66 Hz
----------------------------------	-------

RATED FREQUENCY - MIN	45 Hz
------------------------------	-------

RATED OPERATIONAL CURRENT (IE) AT 110% OVERLOAD	18 A
--	------

RATED OPERATIONAL CURRENT (IE) AT 150% OVERLOAD	13.5 A
--	--------

RATED OPERATIONAL POWER AT 690 V, 50 HZ	11 kW
--	-------

RATED OPERATIONAL POWER AT 690 V, 50 HZ, 110% OVERLOAD	15 kW
---	-------

RATED OPERATIONAL VOLTAGE	600 V AC, 3-phase 690 V AC, 3-phase
--------------------------------------	--

RESOLUTION	0.01 Hz (Frequency resolution, setpoint value)
-------------------	---

SUPPLY FREQUENCY	50/60 Hz
-------------------------	----------

SWITCHING FREQUENCY	1.5 kHz, 1 - 6 kHz adjustable, fPWM, Power section, Main circuit
----------------------------	--

SYSTEM CONFIGURATION TYPE	AC supply systems with earthed center point
--------------------------------------	--

VOLTAGE RATING - MAX	690 VAC
-----------------------------	---------

Motor rating

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 50
HZ, 110% OVERLOAD** 17 A

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 50
HZ, 150% OVERLOAD** 12.6 A

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 60
HZ, 110% OVERLOAD** 15 A

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 60
HZ, 150% OVERLOAD** 10 A

**ASSIGNED MOTOR
POWER AT 690 V, 60 HZ** 10 HP

**ASSIGNED MOTOR
POWER AT 690 V, 60 HZ,
110% OVERLOAD** 15 HP

Resources

APPLICATION NOTES [eaton-9000x-spi-common-dc-bus-selection-ap040044-en-us.pdf](#)

[Electromagnetic compatibility \(EMC\)](#)

CATALOGUES [eaton-drives-soft-starter-catalog-ca04020001zen-us.pdf](#)

DECLARATIONS OF CONFORMITY [eaton-variable-frequency-drive-declaration-of-conformity-eu260003en.pdf](#)

DRAWINGS [eaton-frequency-inverter-dimensions-032.eps](#)

INSTALLATION INSTRUCTIONS [IL04020008Z](#)

MULTIMEDIA [Eaton variable frequency drives - Demand more than good enough](#)

[How does a VFD work to save energy and money?](#)

[Eaton variable frequency drives - Demand more innovation](#)

[Eaton variable frequency drives - Demand more expertise](#)

PRODUCT NOTIFICATIONS [eaton-drives-ecodesign-directive-mz040046en-en.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

