

Specifications



Eaton 125400

Eaton SPX Variable frequency drive, 600 V AC, 3-phase, 200 kW, IP54, Radio interference suppression filter, OLED display, FR10

General specifications

PRODUCT NAME	Eaton SPX variable frequency drive
---------------------	------------------------------------

CATALOG NUMBER	125400
-----------------------	--------

MODEL CODE	SPX200A2-5A4N1
-------------------	----------------

EAN	4015081230068
------------	---------------

PRODUCT LENGTH/DEPTH	602 mm
-----------------------------	--------

PRODUCT HEIGHT	2018 mm
-----------------------	---------

PRODUCT WIDTH	595 mm
----------------------	--------

PRODUCT WEIGHT	275 kg
-----------------------	--------

UL 508C
CUL
RCM
UL
Certified by UL for use in Canada
IEC/EN61800-3
CSA-C22.2 No. 14
DNV
IEC/EN61800-5
CSA Class No.: 3211-06
RoHS, ISO 9001
UL Category Control No.: NMMS, NMMS2, NMMS7, NMMS8
UL File No.: E134360
Safety: EN 61800-5-1: 2003

Specification for general requirements: IEC/EN 61800-2
UL report applies to both US and Canada
IEC/EN 61800-3
CE

CERTIFICATIONS

Climatic environmental conditions

ALTITUDE	Max. 3000 m Max. 1000 m Above 1000 m with 1 % performance reduction per 100 m
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-10 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MAX	50 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MIN	-10 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CLIMATIC PROOFING	< 95 % relative humidity, no condensation, no corrosion, no dripping water

Control circuit

NUMBER OF INPUTS (ANALOG)	2
NUMBER OF INPUTS (DIGITAL)	6
NUMBER OF OUTPUTS (ANALOG)	1
NUMBER OF OUTPUTS (DIGITAL)	1
NUMBER OF RELAY OUTPUTS	2 (parameterizable, N/O, 8 A (24 V DC) / 8 A (250 V AC) / 0,4 A (125 V DC))
RATED CONTROL VOLTAGE (UC)	24 V DC (external, max. 250 mA)

Communication

COMMUNICATION INTERFACE	PROFIBUS-DP BACnet/IP, optional CANopen®, optional DeviceNet, optional Modbus-TCP, optional LonWorks, optional BACnet MS/TP, optional EtherCAT, optional Ethernet IP, optional Modbus-RTU, optional PROFINET, optional
CONNECTION TO SMARTWIRE-DT	No
PROTOCOL	TCP/IP LON PROFIBUS DeviceNet Data-Highway CAN Other bus systems

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF	Meets the product standard's requirements.

ENCLOSURES	
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	5000 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED	208 A

General information	
DEGREE OF PROTECTION	IP54 NEMA 12
ELECTROMAGNETIC COMPATIBILITY	1st and 2nd environments (according to EN 61800-3)
FITTED WITH:	DC link choke Control unit Internal DC link OLED display Radio interference suppression filter PC connection IGBT inverter
FRAME SIZE	FR10
FUNCTIONS	4-quadrant operation possible
MOUNTING POSITION	Vertical
PRODUCT CATEGORY	Variable frequency drives
PROTECTION	Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
RADIO INTERFERENCE CLASS	C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
SUITABLE FOR	Branch circuits, (UL/CSA)

HEAT DISSIPATION (IN)	
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W

Main circuit	
MAINS VOLTAGE - MAX	690 V
MAINS VOLTAGE - MIN	525 V
OPERATING MODE	Sensorless vector control (SLV) U/f control Optional: Vector control with feedback (CLV)
OUTPUT FREQUENCY - MAX	320 Hz
OUTPUT FREQUENCY - MIN	0 Hz
OUTPUT VOLTAGE (U2)	690 V AC, 3-phase 600 V AC, 3-phase
RATED CONTROL SUPPLY VOLTAGE	10 V DC (Us, max. 10 mA)
RATED FREQUENCY - MAX	66 Hz
RATED FREQUENCY - MIN	45 Hz
RATED OPERATIONAL CURRENT (IE) AT 110% OVERLOAD	261 A
RATED OPERATIONAL CURRENT (IE) AT 150% OVERLOAD	208 A
RATED OPERATIONAL POWER AT 690 V, 50 HZ, 3-PHASE	200 kW
RATED OPERATIONAL POWER AT 690 V, 50 HZ, 3-PHASE, 110% OVERLOAD	250 kW
RATED OPERATIONAL VOLTAGE	600 V AC, 3-phase 690 V AC, 3-phase
RESOLUTION	0.01 Hz (Frequency resolution, setpoint value)
SUPPLY FREQUENCY	50/60 Hz
SWITCHING FREQUENCY	1.5 kHz, 1 - 6 kHz adjustable, fPWM, Power section, Main circuit
SYSTEM CONFIGURATION TYPE	AC supply systems with earthed center point
VOLTAGE RATING - MAX	690 VAC

Motor rating

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 50
HZ, 110% OVERLOAD** 253 A

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 50
HZ, 150% OVERLOAD** 202 A

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 60
HZ, 110% OVERLOAD** 251 A

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 60
HZ, 150% OVERLOAD** 167 A

**ASSIGNED MOTOR
POWER AT 690 V, 60 HZ,
3-PHASE** 200 HP

**ASSIGNED MOTOR
POWER AT 690 V, 60 HZ,
3-PHASE, 110 %
OVERLOAD** 300 HP

Resources

	Electromagnetic compatibility (EMC)
APPLICATION NOTES	eaton-9000x-spi-common-dc-bus-selection-ap040044-en-us.pdf
CATALOGUES	eaton-drives-soft-starter-catalog-ca04020001zen-us.pdf
DECLARATIONS OF CONFORMITY	eaton-variable-frequency-drive-declaration-of-conformity-eu260003en.pdf
DRAWINGS	eaton-frequency-inverter-spx-dimensions-013.eps
INSTALLATION INSTRUCTIONS	IL04020008Z
MULTIMEDIA	Eaton variable frequency drives - Demand more innovation Eaton variable frequency drives - Demand more expertise How does a VFD work to save energy and money? Eaton variable frequency drives - Demand more than good enough
PRODUCT NOTIFICATIONS	eaton-drives-ecodesign-directive-mz040046en-en.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

