

Specifications



Eaton 125434

Eaton SPX Variable frequency drive, 600 V AC, 3-phase, 355 kW, IP21, Radio interference suppression filter, OLED display, FR11

General specifications

PRODUCT NAME	Eaton SPX variable frequency drive
CATALOG NUMBER	125434
MODEL CODE	SPX400A1-5A4N1
EAN	4015081230402
PRODUCT LENGTH/DEPTH	602 mm
PRODUCT HEIGHT	2018 mm
PRODUCT WIDTH	794 mm
PRODUCT WEIGHT	350 kg
	CE UL 508C IEC/EN61800-3 CUL UL Category Control No.: NMMS, NMMS2, NMMS7, NMMS8 UL report applies to both US and Canada Safety: EN 61800-5-1: 2003
CERTIFICATIONS	IEC/EN61800-5 RCM RoHS, ISO 9001 Specification for general requirements: IEC/EN 61800-2 DNV CSA Class No.: 3211-06 UL File No.: E134360 IEC/EN 61800-3 Certified by UL for use in Canada CSA-C22.2 No. 14 UL

Climatic environmental conditions

ALTITUDE	Above 1000 m with 1 % performance reduction per 100 m Max. 1000 m Max. 3000 m
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-10 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MAX	50 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MIN	-10 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
CLIMATIC PROOFING	< 95 % relative humidity, no condensation, no corrosion, no dripping water

Control circuit

NUMBER OF INPUTS (ANALOG)	2
NUMBER OF INPUTS (DIGITAL)	6
NUMBER OF OUTPUTS (ANALOG)	1
NUMBER OF OUTPUTS (DIGITAL)	1
NUMBER OF RELAY OUTPUTS	2 (parameterizable, N/O, 8 A (24 V DC) / 8 A (250 V AC) / 0,4 A (125 V DC))
RATED CONTROL VOLTAGE (UC)	24 V DC (external, max. 250 mA)

Communication

COMMUNICATION INTERFACE	LonWorks, optional BACnet/IP, optional Modbus-TCP, optional PROFIBUS-DP CANopen®, optional DeviceNet, optional BACnet MS/TP, optional EtherCAT, optional Ethernet IP, optional Modbus-RTU, optional PROFINET, optional
CONNECTION TO SMARTWIRE-DT	No
PROTOCOL	TCP/IP PROFIBUS LON DeviceNet CAN Other bus systems Data-Highway

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF	Meets the product standard's requirements.

ENCLOSURES	
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	8875 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION DETAILS	Operation (with 150 % overload)
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	385 A
--	-------

STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0 W
--	-----

General information

DEGREE OF PROTECTION	IP21 NEMA 1
-----------------------------	----------------

ELECTROMAGNETIC COMPATIBILITY	1st and 2nd environments (according to EN 61800-3)
--	---

FITTED WITH:	Control unit DC link choke OLED display PC connection Radio interference suppression filter Internal DC link IGBT inverter
---------------------	---

FRAME SIZE	FR11
-------------------	------

FUNCTIONS	4-quadrant operation possible
------------------	----------------------------------

MOUNTING POSITION	Vertical
--------------------------	----------

PRODUCT CATEGORY	Variable frequency drives
-------------------------	---------------------------

PROTECTION	Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
-------------------	--

RADIO INTERFERENCE CLASS	C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
-------------------------------------	--

SUITABLE FOR	Branch circuits, (UL/CSA)
---------------------	---------------------------

Main circuit

MAINS VOLTAGE - MAX	690 V
----------------------------	-------

MAINS VOLTAGE - MIN	525 V
----------------------------	-------

OPERATING MODE	Sensorless vector control (SLV) U/f control Optional: Vector control with feedback (CLV)
-----------------------	--

OUTPUT FREQUENCY - MAX	320 Hz
-----------------------------------	--------

OUTPUT FREQUENCY - MIN	0 Hz
-----------------------------------	------

OUTPUT VOLTAGE (U2)	600 V AC, 3-phase 690 V AC, 3-phase
----------------------------	--

RATED CONTROL SUPPLY VOLTAGE	10 V DC (Us, max. 10 mA)
---	--------------------------

RATED FREQUENCY - MAX	66 Hz
----------------------------------	-------

RATED FREQUENCY - MIN	45 Hz
------------------------------	-------

RATED OPERATIONAL CURRENT (IE) AT 110% OVERLOAD	460 A
--	-------

RATED OPERATIONAL CURRENT (IE) AT 150% OVERLOAD	385 A
--	-------

RATED OPERATIONAL POWER AT 690 V, 50 HZ, 3-PHASE	355 kW
---	--------

RATED OPERATIONAL POWER AT 690 V, 50 HZ, 3-PHASE, 110% OVERLOAD	450 kW
--	--------

RATED OPERATIONAL VOLTAGE	690 V AC, 3-phase 600 V AC, 3-phase
--------------------------------------	--

RESOLUTION	0.01 Hz (Frequency resolution, setpoint value)
-------------------	---

SUPPLY FREQUENCY	50/60 Hz
-------------------------	----------

SWITCHING FREQUENCY	1.5 kHz, 1 - 6 kHz adjustable, fPWM, Power section, Main circuit
----------------------------	--

SYSTEM CONFIGURATION TYPE	AC supply systems with earthed center point
--------------------------------------	--

VOLTAGE RATING - MAX 690 VAC

Motor rating

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 50
HZ, 110% OVERLOAD** 446 A

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 60
HZ, 110% OVERLOAD** 358 A

**ASSIGNED MOTOR
CURRENT IM AT 690 V, 60
HZ, 150% OVERLOAD** 332 A

**ASSIGNED MOTOR
POWER AT 690 V, 60 HZ,
3-PHASE** 400 HP

**ASSIGNED MOTOR
POWER AT 690 V, 60 HZ,
3-PHASE, 110 %
OVERLOAD** 450 HP

Resources

[Electromagnetic compatibility \(EMC\)](#)

APPLICATION NOTES [eaton-9000x-spi-common-dc-bus-selection-ap040044-en-us.pdf](#)

CATALOGUES [eaton-drives-soft-starter-catalog-ca04020001zen-us.pdf](#)

DECLARATIONS OF CONFORMITY [eaton-variable-frequency-drive-declaration-of-conformity-eu260003en.pdf](#)

DRAWINGS [eaton-frequency-inverter-spx-dimensions-011.eps](#)

INSTALLATION INSTRUCTIONS [IL04020008Z](#)

[Eaton variable frequency drives - Demand more than good enough](#)

[Eaton variable frequency drives - Demand more expertise](#)

[Eaton variable frequency drives - Demand more innovation](#)

[How does a VFD work to save energy and money?](#)

PRODUCT NOTIFICATIONS [eaton-drives-ecodesign-directive-mz040046en-en.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

