

Specifications



Photo is representative



Eaton 134946

Eaton DS7 Soft starter, 9 A, 200 - 480 V AC, 24 V DC, Frame size: FS1, Communication Interfaces: SmartWire-DT

General specifications

PRODUCT NAME	Eaton DS7 Soft starter
---------------------	------------------------

CATALOG NUMBER	134946
-----------------------	--------

MODEL CODE	DS7-34DSX009N0-D
-------------------	------------------

EAN	4015081317615
------------	---------------

PRODUCT LENGTH/DEPTH	103 mm
-----------------------------	--------

PRODUCT HEIGHT	130 mm
-----------------------	--------

PRODUCT WIDTH	45 mm
----------------------	-------

PRODUCT WEIGHT	0.35 kg
-----------------------	---------

CERTIFICATIONS

C-Tick
GB 14048.6
CE
UL 508
IEC/EN 60947-4-2
CSA-C22.2 No 0-M91
UkrSEPRO
CSA
CSA-C22.2 No 14-05
CSA22.2-14
UL

Ambient conditions, mechanical

MOUNTING POSITION	Vertical
SHOCK RESISTANCE	8 g, 11 ms, Mechanical
VIBRATION RESISTANCE	2M2 to EN 60721-3-2

Control circuit

CURRENT CONSUMPTION	1.6 mA, Control circuit, Digital inputs, External 24 V 50 mA, Control circuit, Regulator supply
DROP-OUT TIME	350 ms, Control circuit, Digital Inputs, DC operated
DROP-OUT VOLTAGE	0 - 3 V, DC operated
PICK-UP TIME	250 ms at DC
PICK-UP VOLTAGE	17.3 - 27 V DC
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	24 V

Climatic environmental conditions

ALTITUDE	Above 1000 m with 1 % derating per 100 m Max. 2000 m
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT STORAGE TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-5 °C
AMBIENT STORAGE TEMPERATURE - MIN	-25 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-3 Damp heat, cyclic, to IEC 60068-2-30

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE	Meets the product standard's requirements.

BY INTERNAL ELECT. EFFECTS	
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0.45 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	9 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0.45 W

Features & functions

FAULT MEMORY	8 Faults
FITTED WITH:	Internal bypass Internal bypass contacts
FUNCTIONS	Suppression of DC components for motors Min. ramp time 1 s - fast switching (semiconductor contactor) Current limitation, with PKE Soft start function Potential isolation between power and control sections Suppression of closing transients Single direction
INTERFACES	SmartWire-DT (built-in)

Input/Output

NUMBER OF OUTPUTS	1 Relay Output (TOR)
OUTPUT VOLTAGE	24 V DC
PROTECTION	Finger and back-of-hand proof, Protection against direct contact
RATED CONTROL VOLTAGE (UC)	24 V DC 24 V DC (-15 %/+10 %) or via SmartWire-DT
RATED OPERATIONAL CURRENT (IE) AT AC-11	1 A

General information

CLASS	Other
CONNECTION TO SMARTWIRE-DT	Yes
DEGREE OF PROTECTION	IP20 NEMA 1
FRAME SIZE	FS1
MAINS VOLTAGE - MAX	480 V
MAINS VOLTAGE - MIN	200 V
OVERVOLTAGE CATEGORY	II
POLLUTION DEGREE	2
PRODUCT CATEGORY	SmartWire-DT slave
RADIO INTERFERENCE CLASS	Class B (EN 55011)
SUITABLE FOR	Branch circuits, (UL/CSA)
TYPE	Soft starter for three-phase loads
VOLTAGE TYPE	DC

Main conducting paths

OVERLOAD CYCLE	AC-53a: 3 - 5: 75 - 10
RATED OPERATIONAL CURRENT (IE) AT AC-53	9 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	480 V
RATED OPERATIONAL VOLTAGE (UE) - MIN	230 V
SHORT-CIRCUIT PROTECTION RATING	PKM0-10 (+ CL-PKZ0), Type "1" coordination, Main conducting paths 3 x 170M1362, Type „2" coordination (additional with the fuses for coordination type „1"), Main conducting paths
SUPPLY FREQUENCY	50/60 Hz, fLN, Main circuit
VOLTAGE RATING - MAX	480 V

Motor rating

ASSIGNED MOTOR

POWER AT 200/208 V, 60 HZ, 3-PHASE 2 HP

ASSIGNED MOTOR

POWER AT 220/230 V, 60 HZ, 3-PHASE 3 HP

ASSIGNED MOTOR

POWER AT 460/480 V, 60 HZ, 3-PHASE 5 HP

RATED OPERATIONAL

POWER AT 220/230 V, 50 HZ 2.2 kW

RATED OPERATIONAL

POWER AT 400 V, 50 HZ 4 kW

Terminal capacities

SCREWDRIVER SIZE

0.6 x 5.5 mm/1 x 6 mm, Terminal screws, Control circuit cables
PZ2, 1 x 6 mm, Terminal screw, Standard screwdriver

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)

1 x (0.75 - 2.5) mm², Main cables
1 x (0.75 - 2.5) mm², Control circuit cables
2 x (0.75 - 2.5) mm², Control circuit cables
2 x (0.75 - 2.5) mm², Main cables

TERMINAL CAPACITY (SOLID)

2 x (0.75 - 2.5) mm², Control circuit cables
1 x (0.75 - 4) mm², Control circuit cables
1 x (0.75 - 4) mm², Main cables
2 x (0.75 - 2.5) mm², Main cables

TERMINAL CAPACITY (SOLID/STRANDED AWG)

18 - 10, Main cables
18 - 10, Control circuit cables

TIGHTENING TORQUE

1.2 Nm, Screw terminals, Control circuit cables
1.2 Nm

Soft start function

APPLICATION

- 1-phase motors: No
- 3-phase motors: Yes
- Soft starting of three-phase asynchronous motors

CURRENT LIMITATION

(0 - 8) x I_e, Soft start function

DELAY TIME

0 - 30 s, Soft start function, Ramp times

RAMP/RUN-UP TIME

1 - 30 s

START VOLTAGE

Max. 100 %, Soft start function, Start voltage = turn-off voltage
Min. 30 %, Soft start function, Start voltage = turn-off voltage

Resources

BROCHURES

[eaton-softstarter-s811-ds7-brochure-br039001en-en-us.pdf](#)

CATALOGUES

[eaton-drives-soft-starter-catalog-ca04020001zen-us.pdf](#)

DECLARATIONS OF CONFORMITY

[eaton-soft-starter-declaration-of-conformity-eu250527en.pdf](#)

[eaton-soft-starter-declaration-of-conformity-uk251010en.pdf](#)

DRAWINGS

[eaton-semiconductor-contactors-swd-ds7-soft-starter-dimensions-004.eps](#)

[eaton-semiconductor-contactors-softstarter-ds7-3d-drawing-002.eps](#)

ECAD MODEL

[DA-CE-ETN.DS7-34DSX009N0-D](#)

INSTALLATION INSTRUCTIONS

[IL03902003Z2021_06.pdf](#)

INSTALLATION VIDEOS

[Soft starter DS7 up to 32 A](#)

MANUALS AND USER GUIDES

[eaton-ds7-soft-starter-mn03901001z-en-us.pdf](#)

	MN05006002Z_EN
MCAD MODEL	eaton-soft-starters-mcad-drawings-ds7-1-darwin-100309.dwg
	DA-CS-ds7_1_darwin_100309
SALES NOTES	eaton-rmq-chemical-resistance-flyer-fl047011en-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

