

Specifications



Eaton 135168

Eaton CR Installation contactor, 20A, 24V AC, 2NC

General specifications

PRODUCT NAME	Eaton CR contactor
CATALOG NUMBER	135168
MODEL CODE	CR2002024A
EAN	4015081319794
PRODUCT LENGTH/DEPTH	75 mm
PRODUCT HEIGHT	80 mm
PRODUCT WIDTH	18 mm
PRODUCT WEIGHT	0.138 kg
COMPLIANCES	RoHS conform

Additional information

FEATURES

Additional equipment possible

Technical data - electrical

INCANDESCENT LAMP
LOAD - MAX 1950 W

LOAD FLUORESCENT
LAMP - MAX 910 VA

LOAD FLUORESCENT
LAMP (DUO CIRCUIT) -
MAX 1160 VA

LOAD FLUORESCENT
LAMP (PARALLEL
COMPENSATED) - MAX 232 VA

RATED OPERATING
VOLTAGE (UE) - MAX 400 V

RATED OPERATING
VOLTAGE (UE) - MIN 400 V

VOLTAGE RATING
(EXCITATION) - MAX 26.4 V

VOLTAGE RATING
(EXCITATION) - MIN 20.4 V

VOLTAGE TYPE AC

Delivery programme

AMPERAGE RATING 20 A

Technical data - mechanical

BUILT-IN DEPTH 60 mm

DEGREE OF PROTECTION IP20

NUMBER OF CONTACTS
(NORMALLY CLOSED
CONTACTS) 2

NUMBER OF CONTACTS
(NORMALLY OPEN
CONTACTS) 0

NUMBER OF MODULAR
SPACINGS 1

UTILITY CATEGORY 1

UTILIZATION CATEGORY
(ACCORDING TO EN IEC
60947-4-1) AC-1

Resources

DECLARATIONS OF
CONFORMITY

[eaton-contactor-
declaration-of-conformity-
eu250193en.pdf](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

