

Specifications

Eaton 135695



Eaton Moeller® series E58 Thru-beam photoelectric sensor, receiver, Sn=250m, 4L, 10-30VDC, light, NPN, PNP, M30, metal E58-30TD250-HLP

General specifications

PRODUCT NAME	Eaton Moeller® series E58 Thru-beam photoelectric sensor
CATALOG NUMBER	135695
MODEL CODE	E58-30TD250-HLP
EAN	4015081324880
PRODUCT LENGTH/DEPTH	228.6 mm
PRODUCT HEIGHT	44.45 mm
PRODUCT WIDTH	165.1 mm
PRODUCT WEIGHT	0.2 kg
CERTIFICATIONS	CSA-C22.2 No. 14 CE UL File No.: E166051 Certified by UL for use in Canada IEC/EN 60947-5-2 UL UL 508 UL Category Control No.: NRKH, NRKH7 CSA File No.: UL report applies to both US and Canada



Powering Business Worldwide

Product specifications

TYPE	Optical sensors
DEVICE TYPE	Receiver
ELECTRIC CONNECTION TYPE	Connector M12
ENCLOSURE MATERIAL	Metal
ENCLOSURE TYPE	Cylinder, screw-thread
OPERATING MODE	Switching principle: Light switching
EXPLOSION SAFETY CATEGORY FOR DUST	None
EXPLOSION SAFETY CATEGORY FOR GAS	None
FUNCTIONS	Short-circuit protection Protection against polarity reversal Protection against wire breakage Detector (for combination with source) Thru-light beam
VOLTAGE TYPE	DC
WIRE SIZE	0
CONNECTION TYPE	Plug-in connection M12 x 1 4-wire
CABLE SHEATH MATERIAL	Polyvinyl chloride (PVC)
LIGHT TYPE	Other
DEGREE OF PROTECTION	NEMA 6P IP68
INTERFACE TYPE	Other
LED INDICATOR	Status indication of Switching state: Red LED
SWITCH FUNCTION TYPE	Other
LOAD CURRENT	Max. 100 mA (I _e)
LASER PROTECTION CLASS	None
OPERATION AGENT-SAFETY CLASS	Safety class 2
SHOCK RESISTANCE	100 g, Mechanical, Shock duration 3 ms
OPTICAL SURFACE MATERIAL	Glass
OUTPUT CURRENT (MA) - MAX	100 mA
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	30 V

Resources

DECLARATIONS OF CONFORMITY	eaton-proximity-sensor-declaration-of-conformity-eu251572en.pdf
DRAWINGS	eaton-proximity-switches-e58-diffuse-reflective-sensor-dimensions-002.eps eaton-proximity-switches-e58-3d-drawing.eps
INSTALLATION INSTRUCTIONS	IL05305003Z

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	10 V
RATED SWITCHING DISTANCE (SN)	250000 mm
SENSOR LENGTH	111 mm
SWITCHING VOLTAGE OF OSSD AT STATE HIGH	30 V
VOLTAGE RATING - MAX	30 V
SAFETY TYPE (IEC 61496-1)	1
SWITCHING FREQUENCY	312 Hz
SENSING MODE	Light switching
SWITCHING OUTPUT TYPE	PNP
SENSOR MATERIAL	Stainless steel
PRODUCT CATEGORY	E58 Harsh Duty Series
RESPONSE TIME	1 ms
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-40 °C
DIAMETER SENSOR	30 mm
NUMBER OF CONTACT ENERGIZED OUTPUTS WITH SIGNALLING FUNCTION	0
NUMBER OF OUTPUTS (PROTECTED CONTACT ENERGIZED)	0
NUMBER OF OUTPUTS (PROTECTED SEMICONDUCTOR)	0
NUMBER OF OUTPUTS (SEMICONDUCTOR WITH SIGNALING FUNCTION)	2
ADJUSTMENT TYPE	Other

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

