

Specifications



Eaton 135733

Eaton Moeller® series E65 Thru-beam photoelectric sensor, receiver, Sn=15m, 4L, 10-30VDC, light, NPN, PNP, quad 40, insulated material E65-SMTD15-HLD

General specifications

PRODUCT NAME	Eaton Moeller® series E65 Thru-beam photoelectric sensor
CATALOG NUMBER	135733
MODEL CODE	E65-SMTD15-HLD
EAN	4015081325269
PRODUCT LENGTH/DEPTH	139.7 mm
PRODUCT HEIGHT	139.7 mm
PRODUCT WIDTH	38.1 mm
PRODUCT WEIGHT	0.11 kg
CERTIFICATIONS	Certified by UL for use in Canada UL CE CSA File No.: UL report applies to both US and Canada UL 508 UL File No.: E166051 CSA-C22.2 No. 14 IEC/EN 60947-5-2 UL Category Control No.: NRKH, NRKH7
CATALOG NOTES	Yellow



Powering Business Worldwide

Product specifications

TYPE	Optical sensors
DEVICE TYPE	Receiver
ELECTRIC CONNECTION TYPE	Plug-in connection
FITTED WITH:	Transmitter (for combination with detector)
ENCLOSURE MATERIAL	Plastic
ENCLOSURE TYPE	Cuboid
OPERATING MODE	Switching principle: Light switching
EXPLOSION SAFETY CATEGORY FOR DUST	None
EXPLOSION SAFETY CATEGORY FOR GAS	None
FUNCTIONS	Protection against polarity reversal Protection against wire breakage Thru-light beam For combination with transmitter Short-circuit protection
VOLTAGE TYPE	DC
WIRE SIZE	0
CONNECTION TYPE	Plug-in connection M12 x 1 4-wire
CABLE SHEATH MATERIAL	Polyvinyl chloride (PVC)
LIGHT TYPE	Polarity free red light
DEGREE OF PROTECTION	NEMA 6 IP68
INTERFACE TYPE	Other
LED INDICATOR	Status indication of Operating voltage: Green LED Status indication of Switching state: Red LED
SWITCH FUNCTION TYPE	Other
LOAD CURRENT	Max. 100 mA (Ie)
LASER PROTECTION CLASS	None
OPERATION AGENT-SAFETY CLASS	Safety class 2
SHOCK RESISTANCE	50 g, Mechanical, Shock duration 10 ms
OPTICAL SURFACE	Plastic

Resources

DECLARATIONS OF CONFORMITY	eaton-proximity-sensor-declaration-of-conformity-eu251572en.pdf
DRAWINGS	eaton-proximity-switches-dimensions-012.eps eaton-proximity-switches-e65-diffuse-reflective-sensor-dimensions.eps eaton-proximity-switches-e65-3d-drawing.eps
INSTALLATION INSTRUCTIONS	IL05305004Z
MCAD MODEL	eaton-photoelectric-sensors-mcad-drawings-90-28290-012.dwg DA-CS-90_28290_012

MATERIAL	
OUTPUT CURRENT (MA) - MAX	100 mA
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	30 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	10 V
RATED SWITCHING DISTANCE (SN)	15000 mm
SENSOR HEIGHT	55 mm
SENSOR LENGTH	41 mm
SWITCHING DISTANCE - MAX	15000 mm
SWITCHING VOLTAGE OF OSSD AT STATE HIGH	30 V
VOLTAGE RATING - MAX	30 V
SAFETY TYPE (IEC 61496-1)	1
SWITCHING FREQUENCY	500 Hz
SENSING MODE	Light switching
SWITCHING OUTPUT TYPE	NPN
SENSOR MATERIAL	Insulated material
WAVELENGTH OF THE SENSOR	660 nm
WIDTH SENSOR	33 mm
PRODUCT CATEGORY	E65 SM Series
RESPONSE TIME	1 ms
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MIN	-25 °C
NUMBER OF CONTACT ENERGIZED OUTPUTS WITH SIGNALLING FUNCTION	0
NUMBER OF OUTPUTS (PROTECTED CONTACT ENERGIZED)	0
NUMBER OF OUTPUTS (PROTECTED SEMICONDUCTOR)	0
NUMBER OF OUTPUTS	2

(SEMICONDUCTOR WITH SIGNALING FUNCTION)	
OPERATING TEMPERATURE - MAX	55 °C
OPERATING TEMPERATURE - MIN	-25 °C
OPERATIONAL CURRENT (IB) IN THE SWITCHED STATE AT 24 V DC	20 A
ADJUSTMENT TYPE	Other

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

