

Specifications

Eaton 136292



Eaton Moeller® series CSDS Connection cable, 4p, DC current, coupling M12 flat, open end, L=2m

General specifications

PRODUCT NAME	Eaton Moeller® series CSDS Accessory Connection cable
CATALOG NUMBER	136292
MODEL CODE	CSDS4A4CY2202
EAN	4015081330805
PRODUCT LENGTH/DEPTH	165.1 mm
PRODUCT HEIGHT	12.7 mm
PRODUCT WIDTH	165.1 mm
PRODUCT WEIGHT	0.09 kg
CERTIFICATIONS	CE



Powering Business Worldwide

Product specifications

TYPE	Connecting cables
NUMBER OF POLES	Four-pole
CABLE TYPE	Coupling, straight, Input side Multi-core Cable end, open, Output side
CONTACT SURFACE MATERIAL	Other
PRODUCT CATEGORY	Accessories
VOLTAGE TYPE	DC
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
CABLE LENGTH	2 m
CABLE SHEATH MATERIAL	Other
DEGREE OF PROTECTION	Other
COLOR CABLE SHEATH	Yellow
ELECTRICAL CONNECTION TYPE (BOX-SIDED)	Other
ELECTRICAL CONNECTION TYPE (FIELD-SIDED)	M12
CONTACT BODY MATERIAL	Other
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLED) WITHOUT VIBRATION - MAX	70 °C
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLED) WITHOUT VIBRATION - MIN	40 °C
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLING/HANDLING) - MAX	70 °C
PERMITTED TEMPERATURE OF OUTER CABLE (ASSEMBLING/HANDLING) - MIN	40 °C
PLUG-IN CONTACT TYPE	Male (plug)

Resources

CATALOGUES	Product Range Catalog Sensors – products, basic information, applications
DECLARATIONS OF CONFORMITY	eaton-proximity-switch-declaration-of-conformity-eu251573en.pdf
DRAWINGS	eaton-proximity-switches-csds-connecting-cable-3d-drawing.eps
MULTIMEDIA	We make what matters
WIRING DIAGRAMS	eaton-proximity-switches-csdr-connecting-cable-wiring-diagram-002.eps

(BOX-SIDED)	
PLUG-IN CONTACT TYPE (FIELD-SIDED)	Female (bus)
POSITIONING CABLE FEED (BOX-SIDED)	Other
POSITIONING CABLE FEED (FIELD-SIDED)	Straight

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

