

Specifications



Eaton 136501

Eaton Moeller® series ZEB Overload relay,
Separate mounting, Earth-fault protection:
with, $I_r = 9 - 45 \text{ A}$, 1 N/O, 1 N/C

General specifications

PRODUCT NAME	Eaton Moeller® series ZEB Electronic overload relay
CATALOG NUMBER	136501
MODEL CODE	ZEB32-45-GF/KK
EAN	4015081332816
PRODUCT LENGTH/DEPTH	108 mm
PRODUCT HEIGHT	110 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.359 kg
CERTIFICATIONS	CE UL File No.: E1230 CSA File No.: 2290956 CSA Class No.: 3211-03 UL UL 508 CSA-C22.2 No. 14 IEC/EN 60947 VDE 0660 CSA UL Category Control No.: NKCR IEC/EN 60947-4-1
CATALOG NOTES	Rated operational current: Switch-on and switch-off conditions based on DC- 13, time constant as specified.

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	65 °C
--	-------

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	65 °C
---	-------

CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
--------------------------	--

Contacts

NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
--	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
--	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	1
--	---

NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
--	---

NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
--	---

Design verification

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Electrical rating

CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	5 A
RATED FREQUENCY - MAX	60 Hz
RATED FREQUENCY - MIN	50 Hz
RATED OPERATIONAL CURRENT (IE) AT AC-15, 120 V	1.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	1.5 A
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	0.9 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.4 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.2 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	0.9 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	0.75 A
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
SAFE ISOLATION	240 V AC, Between auxiliary contacts, According to EN 61140 600 V AC, Between main circuits, According to EN 61140 440 V, Between auxiliary contacts and main contacts, According to EN 61140
SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	100 kA, Fuse, SCCR (UL/CSA) 60 A, Class J, max. Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT PROTECTION RATING	Max. 6 A gG/gL, fuse, Without welding, Auxiliary and control circuits
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	R300, DC operated (UL/CSA) B600, AC operated (UL/CSA)

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	4.3 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.43 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	45 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

Features & functions	
EARTH FAULT PROTECTION	Yes Trip at approx. $> 0.5 \times I_r$ in 2 s Trip at approx. $> 1.5 \times I_r$ in 1 s
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947, VDE 0660 Part 102)
FUNCTIONS	Filament bulb (24 V)

VOLTAGE RATING - MAX	600 V
-----------------------------	-------

General information	
CLASS	Adjustable
DEGREE OF PROTECTION	IP20
MOUNTING METHOD	Separate positioning Separate mounting
OVERLOAD RELEASE CURRENT SETTING - MAX	45 A
OVERLOAD RELEASE CURRENT SETTING - MIN	9 A
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Electronic overload relays ZEB
PROTECTION	Finger and back-of-hand proof, Protection against

	direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V (auxiliary circuits) 6000 V AC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Shock duration 10 ms Mechanical, According to IEC/EN 60068-2-27
SUITABLE FOR	Branch circuits, (UL/CSA)
VOLTAGE TYPE	Self powered AC

Terminal capacities

SCREW SIZE	M3.5, Terminal screw, Control circuit cables
SCREWDRIVER SIZE	2, Terminal screw, Pozidriv screwdriver 1 x 6 mm, Terminal screw, Standard screwdriver
STRIPPING LENGTH (CONTROL CIRCUIT CABLE)	8 mm
STRIPPING LENGTH (MAIN CABLE)	13 mm
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.75 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID)	1 x (1.5 - 16) mm ² , Main cables 2 x (0.75 - 4) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	2 x (18 - 12), Control circuit cables 1 x (14 - 4), Main cables
TIGHTENING TORQUE	0.8 - 1.2 Nm, Screw terminals, Control circuit cables 7 lb-in, Screw terminals

Resources

BROCHURES	eaton-motor-starters-system-xstart-brochure-br03407001en-en-us.pdf Electronic overload relay ZEB
DECLARATIONS OF CONFORMITY	eaton-electronic-overload-relay-declaration-of-conformity-eu260060en.pdf
DRAWINGS	eaton-tripping-devices-relay-zeb-overload-relay-dimensions.eps eaton-tripping-devices-zeb-overload-relay-characteristic-curve.eps eaton-tripping-devices-relay-zeb-overload-relay-3d-drawing.eps
ECAD MODEL	ETN.136501.edx
INSTALLATION INSTRUCTIONS	IL04210002E
MCAD MODEL	eaton-electronic-overload-relays-mcad-drawings-zeb32-kk.dwg zeb32_kk.stp
WIRING DIAGRAMS	eaton-general-release-zeb-overload-relay-wiring-diagram.eps eaton-tripping-devices-overload-relay-zeb-overload-relay-wiring-diagram.eps

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

