

Specifications



Photo is representative



Eaton 139554

Eaton Moeller® series DILM Contactor, 380 V 400 V 160 kW, 2 N/O, 2 NC, RDC 48: 24 - 48 V DC, DC operation, Screw connection

General specifications

PRODUCT NAME	Eaton Moeller® series DILM Contactor
---------------------	--------------------------------------

CATALOG NUMBER	139554
-----------------------	--------

MODEL CODE	DILM300A/22(RDC48)
-------------------	--------------------

EAN	4015081363322
------------	---------------

PRODUCT LENGTH/DEPTH	208 mm
-----------------------------	--------

PRODUCT HEIGHT	189 mm
-----------------------	--------

PRODUCT WIDTH	140 mm
----------------------	--------

PRODUCT WEIGHT	7.1 kg
-----------------------	--------

UL File No.: E29096
IEC/EN 60947-4-1
VDE 0660
UL 60947-4-1
UL Category Control No.: NLDX
CSA Class No.: 3211-04
UL/CSA
CSA File No. 1017510
North America (UL listed, CSA certified)
EN 45545: Fire protection on railway vehicles
IEC 61373: Vibration and shock, tested for category 1 class B
CE marking

CERTIFICATIONS

CATALOG NOTES

- Contacts according to EN 50012
- EN 45545 - Fire protection on railway vehicles: Fire protection class of all plastics according to UL94: V-0 / plastic weight in total: 1.872 kg
- Conventional thermal current Ith

AC-1/Conventional thermal current Ith

**CONVENTIONAL
THERMAL CURRENT ITH
(1-POLE, ENCLOSED)** 788 A

**CONVENTIONAL
THERMAL CURRENT ITH
(3-POLE, ENCLOSED)** 315 A

**CONVENTIONAL
THERMAL CURRENT ITH
AT 40°C (3-POLE, OPEN)** 490 A

**CONVENTIONAL
THERMAL CURRENT ITH
AT 50°C (3-POLE, OPEN)** 438 A

**CONVENTIONAL
THERMAL CURRENT ITH
AT 55°C (3-POLE, OPEN)** 418 A

**CONVENTIONAL
THERMAL CURRENT ITH
AT 60°C (3-POLE, OPEN)** 400 A

**CONVENTIONAL
THERMAL CURRENT ITH
OF MAIN CONTACTS (1-
POLE, OPEN)** 1000 A

Contacts

**NUMBER OF AUXILIARY
CONTACTS (NORMALLY
CLOSED CONTACTS)** 2

**NUMBER OF AUXILIARY
CONTACTS (NORMALLY
OPEN CONTACTS)** 2

**NUMBER OF CONTACTS
(NORMALLY CLOSED
CONTACTS)** 2

**NUMBER OF CONTACTS
(NORMALLY OPEN
CONTACTS)** 2

of main contacts (1-
pole, open) at 60°

Climatic environmental conditions

ALTITUDE Max. 2000 m

**AMBIENT OPERATING
TEMPERATURE - MAX** 60 °C

**AMBIENT STORAGE
TEMPERATURE - MAX** 80 °C

**AMBIENT OPERATING
TEMPERATURE - MIN** -40 °C

**AMBIENT OPERATING
TEMPERATURE
(ENCLOSED) - MAX** 40 °C

**AMBIENT OPERATING
TEMPERATURE
(ENCLOSED) - MIN** -40 °C

**AMBIENT STORAGE
TEMPERATURE - MIN** -40 °C

CLIMATIC PROOFING Damp heat, cyclic, to IEC
60068-2-30
Damp heat, constant, to
IEC 60068-2-78

Design verification

10.10 TEMPERATURE RISE The panel builder is
responsible for the
temperature rise
calculation. Eaton will
provide heat dissipation
data for the devices.

**10.11 SHORT-CIRCUIT
RATING** Is the panel builder's
responsibility. The
specifications for the
switchgear must be
observed.

**10.12 ELECTROMAGNETIC
COMPATIBILITY** Is the panel builder's
responsibility. The
specifications for the
switchgear must be
observed.

**10.13 MECHANICAL
FUNCTION** The device meets the
requirements, provided
the information in the
instruction leaflet (IL) is
observed.

**10.2.2 CORROSION
RESISTANCE** Meets the product
standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W

HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	7 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	300 A
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	4.6 W

Electrical rating

INRUSH CURRENT	Max. 30 x I _e (peak)
RATED BREAKING CAPACITY AT 1000 V	950 A
RATED BREAKING CAPACITY AT 220/230 V	3000 A
RATED BREAKING CAPACITY AT 380/400 V	3000 A
RATED BREAKING CAPACITY AT 500 V	3000 A
RATED BREAKING CAPACITY AT 660/690 V	3000 A
RATED INSULATION VOLTAGE (UI)	1000 V
RATED MAKING CAPACITY (COS PHI TO IEC/EN 60947)	3000 A
RATED OPERATIONAL CURRENT (IE)	177 A at 690 V (Individual compensation, three-phase capacitors, open) 307 A at up to 525 V (Individual compensation, three-phase capacitors, open)
RATED OPERATIONAL CURRENT (IE) AT AC-3, 1000 V	95 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V	300 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V	300 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 440 V	300 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 500 V	300 A
RATED OPERATIONAL CURRENT (IE) AT AC-3, 660 V, 690 V	185 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 1000 V	76 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 220 V, 230 V, 240 V	240 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 440 V	240 A

General information

ACCESSORIES	Fitting options auxiliary contacts: on the side: 2 x DILM820-XHI11(V)-SI; 2 x DILM820-XHI11-SA
APPLICATION	Contactors for Motors
CONNECTION	Screw terminals
DEGREE OF PROTECTION	IP00
ELECTROMAGNETIC COMPATIBILITY	Designed for operation in industrial environments. Its use in residential environments may cause radio-frequency interference, requiring additional noise suppression.
FITTED WITH:	Suppressor circuit in actuating electronics
LIFESPAN, ELECTRICAL	100,000 Operations (at Condensor operation)
LIFESPAN, MECHANICAL	10,000,000 Operations (DC operated)
OPERATING FREQUENCY	3000 mechanical Operations/h (DC operated) 200 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Contactors
PROTECTION	Finger and back-of-hand proof with terminal shroud or terminal block, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	8000 V AC
RESISTANCE	500 mΩ (Admissible transitional contact resistance - of the external control circuit device when actuating A11)
SHOCK RESISTANCE	10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 8 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-

RATED OPERATIONAL CURRENT (IE) AT AC-4, 500 V	240 A
RATED OPERATIONAL CURRENT (IE) AT AC-4, 660 V, 690 V	150 A
RATED OPERATIONAL POWER AT AC-3, 1000 V, 50 HZ	132 kW
RATED OPERATIONAL POWER AT AC-3, 240 V, 50 HZ	100 kW
RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	160 kW
RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ	175 kW
RATED OPERATIONAL POWER AT AC-3, 440 V, 50 HZ	185 kW
RATED OPERATIONAL POWER AT AC-3, 500 V, 50 HZ	210 kW
RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	170 kW
RATED OPERATIONAL POWER AT AC-4, 1000 V, 50 HZ	108 kW
RATED OPERATIONAL POWER AT AC-4, 220/230 V, 50 HZ	75 kW
RATED OPERATIONAL POWER AT AC-4, 240 V, 50 HZ	82 kW
RATED OPERATIONAL POWER AT AC-4, 415 V, 50 HZ	142 kW
RATED OPERATIONAL POWER AT AC-4, 440 V, 50 HZ	150 kW
RATED OPERATIONAL POWER AT AC-4, 500 V, 50 HZ	170 kW
RATED OPERATIONAL POWER AT AC-4, 660/690 V, 50 HZ	137 kW
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	1000 V
SAFE ISOLATION	1000 V AC, Between coil and contacts, According to

	sinusoidal shock 10 ms 10 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
SIGNAL LEVEL	5 V - 15 V, PLC signal level (A3 - A4) to IEC/EN 61131-2 (type 2), Magnet systems
UTILIZATION CATEGORY	AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running
VOLTAGE TYPE	DC

	EN 61140
SPECIAL PURPOSE RATING OF DEFINITE PURPOSE RATING	300 A, FLA 600 V 60 Hz 3- ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 2160 A, LRA 480 V 60 Hz 3- ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 1800 A, LRA 600 V 60 Hz 3- ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 360 A, FLA 480 V 60 Hz 3- ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

Magnet system

BEHAVIOR IN MARGINAL AND TRANSITIONAL CONDITIONS

Sealing - Voltage drops (0.2 - 0.6 x U_c min $\leq$ 12 ms: Time is bridged successfully
 Sealing - Voltage drops (0.6 - 0.7 x U_c min: Contactor remains switched on
 Sealing - Voltage interruptions (0 - 0.2 x U_c min $\leq$ 10 ms: Time is bridged successfully
 Sealing - Voltage drops (0.2 - 0.6 x U_c min) > 12 ms: Drop-out of the contactor
 Sealing - Excess voltage (1.15 - 1.3 x U_c max): Contactor remains switched on
 Sealing - Voltage interruptions 0 - 0.2 x U_c min) > 10 ms: Drop-out of the contactor
 Sealing - Pick-up phase (0.7 x U_c min - 1.15 x U_c max): Contactor switches on with certainty
 Sealing - Pick-up phase (0 - 0.7 x U_c min: Contactor does not switch on

DROP-OUT VOLTAGE

DC operated: 0.2 x U_S max - 0.6 U_S min, DC operated
 DC operated: 0.15 x U_S min - 0.6 U_S max, DC operated

DUTY FACTOR

100 %

PICK-UP VOLTAGE

0.7 - 1.15 V DC x U_S

POWER CONSUMPTION

Control transformer with $u_k \leq 6\%$

POWER CONSUMPTION (PICK-UP) AT DC

380 VA

POWER CONSUMPTION (SEALING) AT DC

4.6 W

POWER CONSUMPTION, PICK-UP, 50 HZ

240 VA, Pull-in power, Coil in a cold state and 1.0 x U_S

POWER CONSUMPTION, PICK-UP, 60 HZ

240 VA, Pull-in power, Coil in a cold state and 1.0 x U_S

POWER CONSUMPTION, SEALING, 50 HZ

4.6 W, Coil in a cold state and 1.0 x U_S

POWER CONSUMPTION, SEALING, 60 HZ

4.6 W, Coil in a cold state and 1.0 x U_S

RATED CONTROL SUPPLY

48 V

Motor rating

ASSIGNED MOTOR

POWER AT 200/208 V, 60 HZ, 3-PHASE 100 HP

ASSIGNED MOTOR

POWER AT 230/240 V, 60 HZ, 3-PHASE 125 HP

ASSIGNED MOTOR

POWER AT 460/480 V, 60 HZ, 3-PHASE 250 HP

ASSIGNED MOTOR

POWER AT 575/600 V, 60 HZ, 3-PHASE 300 HP

VOLTAGE (US) AT DC - MAX	
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	24 V
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, CLOSING DELAY) - MAX	100 ms
SWITCHING TIME (AC OPERATED, MAKE CONTACTS, OPENING DELAY) - MAX	110 ms

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (BASIC RATING)	600 A, max. CB, SCCR (UL/CSA)
	700 A, max. Fuse, SCCR (UL/CSA)
	18 kA, SCCR (UL/CSA)

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 480 V)	700 A, Class L, max. Fuse, SCCR (UL/CSA)
	65 kA, CB, SCCR (UL/CSA)
	250 A, max. CB, SCCR (UL/CSA)
	18 kA, Fuse, SCCR (UL/CSA)

700 A, Class L/450 A, Class J, max. Fuse, SCCR (UL/CSA)
18/100 kA, Fuse, SCCR (UL/CSA)

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	700 A, Class J, max. Fuse, SCCR (UL/CSA)
	18 kA, Fuse, SCCR (UL/CSA)
	600 A, max. CB, SCCR (UL/CSA)

18 kA, CB, SCCR (UL/CSA)
700 A, Class L/450 A, Class J, max. Fuse, SCCR (UL/CSA)
18/100 kA, Fuse, SCCR (UL/CSA)

SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 1000 V	200 A gG/gL
--	-------------

SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 400 V	400 A gG/gL
---	-------------

SHORT-CIRCUIT PROTECTION RATING (TYPE 1 COORDINATION) AT 690 V	400 A gG/gL
---	-------------

SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 1000 V	160 A gG/gL
--	-------------

SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 400 V	400 A gG/gL
---	-------------

SHORT-CIRCUIT PROTECTION RATING (TYPE 2 COORDINATION) AT 690 V	315 A gG/gL
---	-------------

Switching capacity

SWITCHING CAPACITY (AUXILIARY CONTACTS, GENERAL USE)	15 A, 600 V AC, (UL/CSA)
	1 A, 250 V DC, (UL/CSA)

SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	A600, AC operated (UL/CSA) P300, DC operated (UL/CSA)
--	--

SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)	350 A, Maximum motor rating (UL/CSA)
--	--------------------------------------

Terminal capacities

SCREW SIZE	M3.5, Terminal screw, Control circuit cables M10, Terminal screw, Main connections
SCREWDRIVER SIZE	2, Terminal screw, Control circuit cables, Pozidriv screwdriver
TERMINAL CAPACITY (BUSBAR)	25 mm width, Main connection
TERMINAL CAPACITY (COPPER BAND)	Fixing with flat cable terminal or cable terminal blocks; See terminal capacity for cable terminal blocks
TERMINAL CAPACITY (FLEXIBLE WITH CABLE LUG)	50 - 240 mm ²
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.75 - 2.5) mm ² , Control circuit cables 2 x (0.75 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID)	2 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 14, Control circuit cables 2/0 - 500 MCM, Main cables
TERMINAL CAPACITY (STRANDED WITH CABLE LUG)	70 - 240 mm ²
TIGHTENING TORQUE	24 Nm, Main cable connection screw/bolt 1.2 Nm, Screw terminals, Control circuit cables
WIDTH ACROSS FLATS	16 mm

Resources

BROCHURES	eaton-product-brochure-dilmdilh-power-contactors-brochure-br034010en-en-us.pdf
CATALOGUES	Product Range Catalog Switching and protecting motors
CHARACTERISTIC CURVE	eaton-contactors-short-time-loading-dilm-characteristic-curve-002.eps eaton-contactors-component-dilm-characteristic-curve-003.eps eaton-contactors-component-dilm-characteristic-curve-002.eps eaton-contactors-component-dilm-characteristic-curve.eeps
DECLARATIONS OF CONFORMITY	eaton-contactor-declaration-of-conformity-uk251102en.pdf eaton-contactor-declaration-of-conformity-eu250619en.pdf
DRAWINGS	eaton-contactors-mounting-dilm-dimensions-002.eps eaton-contactors-dilm-dimensions-007.eps eaton-contactors-mounting-dilm-dimensions.eps eaton-contactors-mounting-dilm-3d-drawing-002.eps
ECAD MODEL	DA-CE-ETN.DILM300A_22(RDC48)
INSTALLATION INSTRUCTIONS	eaton-contactors-dilm250-to-dilm500-il03406002z.pdf
MCAD MODEL	eaton-iec-contactors-mcad-3d-models-dilm250-300-s22.stp

	eaton-iec-contactors-mcad-drawings-dilm250-300-s22.dwg
WIRING DIAGRAMS	eaton-contactors-contact-dilm-wiring-diagram-004.eps

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

