

Specifications



Eaton 139560

Eaton Moeller® series DILM Terminal shroud, for DILM185A-225A

General specifications

PRODUCT NAME	Eaton Moeller® series DILM terminal cover
CATALOG NUMBER	139560
MODEL CODE	DILM225A-XHB
EAN	4015081363384
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	112 mm
PRODUCT WIDTH	126 mm
PRODUCT WEIGHT	0.158 kg
CERTIFICATIONS	UL/CSA certification not required
CATALOG NOTES	To provide terminals with busbar tag shroud vertical from the front

Climatic environmental conditions

**AMBIENT OPERATING
TEMPERATURE - MAX** 60 °C

**AMBIENT OPERATING
TEMPERATURE - MIN** -40 °C

Design verification

10.10 TEMPERATURE RISE Not applicable.

**10.11 SHORT-CIRCUIT
RATING** Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.12 ELECTROMAGNETIC
COMPATIBILITY** Is the panel builder's responsibility. The specifications for the switchgear must be observed.

**10.13 MECHANICAL
FUNCTION** The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

**10.2.2 CORROSION
RESISTANCE** Meets the product standard's requirements.

**10.2.3.1 VERIFICATION OF
THERMAL STABILITY OF
ENCLOSURES** Meets the product standard's requirements.

**10.2.3.2 VERIFICATION OF
RESISTANCE OF
INSULATING MATERIALS
TO NORMAL HEAT** Meets the product standard's requirements.

**10.2.3.3 RESIST. OF
INSUL. MAT. TO
ABNORMAL HEAT/FIRE
BY INTERNAL ELECT.
EFFECTS** Meets the product standard's requirements.

**10.2.4 RESISTANCE TO
ULTRA-VIOLET (UV)
RADIATION** Meets the product standard's requirements.

10.2.5 LIFTING Does not apply, since the entire switchgear needs to be evaluated.

**10.2.6 MECHANICAL
IMPACT** Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS Meets the product standard's requirements.

**10.3 DEGREE OF
PROTECTION OF
ASSEMBLIES** Does not apply, since the entire switchgear needs to be evaluated.

**10.4 CLEARANCES AND
CREEPAGE DISTANCES** Meets the product standard's requirements.

**10.5 PROTECTION
AGAINST ELECTRIC
SHOCK** Does not apply, since the entire switchgear needs to be evaluated.

**10.6 INCORPORATION OF
SWITCHING DEVICES AND
COMPONENTS** Does not apply, since the entire switchgear needs to be evaluated.

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W

General information

ACCESSORY/SPARE PART TYPE	Cover
PRODUCT CATEGORY	Accessories
USED WITH	DILM185A-225A Z5-... FF225A DILM185A and DILM225A

Resources

BROCHURES	eaton-product-brochure-dilmdilh-power-contactors-brochure-br034010en-en-us.pdf
DRAWINGS	eaton-contactors-terminals-dilm-terminal-shroud-dimensions.eps eaton-contactors-terminals-dilm-terminal-shroud-3d-drawing.eps eaton-contactors-dilm-terminal-shroud-3d-drawing.eps
INSTALLATION INSTRUCTIONS	eaton-contactor-accessories-dilm-x-il03406009z.pdf
MCAD MODEL	eaton-contactors-starters-accessories-3d-models-dilm225a-xhb.stp

	eaton-accessories-mcad-drawings-dil-m225a-xhb.dwg
SYSTEM OVERVIEW	eaton-contactors-system55-dilm-explosion-drawing.eps

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

