

# Specifications



## Eaton 142464

Eaton xEnergy Basic base element, Cable interconnect frame IP55, HxWxD=100 x 350 x 250 mm

### General specifications

|                             |                                  |
|-----------------------------|----------------------------------|
| <b>PRODUCT NAME</b>         | Eaton xEnergy Basic base element |
| <b>CATALOG NUMBER</b>       | 142464                           |
| <b>MODEL CODE</b>           | BPZ-KR3.51/250                   |
| <b>EAN</b>                  | 4015081391950                    |
| <b>PRODUCT LENGTH/DEPTH</b> | 250 mm                           |
| <b>PRODUCT HEIGHT</b>       | 110 mm                           |
| <b>PRODUCT WIDTH</b>        | 350 mm                           |
| <b>PRODUCT WEIGHT</b>       | 3.5 kg                           |
| <b>COMPLIANCES</b>          | RoHS conform                     |

## Additional information

|                   |                      |
|-------------------|----------------------|
| <b>FUNCTIONS</b>  | Additional equipment |
| <b>RAL-NUMBER</b> | 7035                 |

## Technical data - mechanical

|                                                     |                                   |
|-----------------------------------------------------|-----------------------------------|
| <b>HOUSING MATERIAL</b>                             | Sheet steel                       |
| <b>MATERIAL</b>                                     | Metal                             |
| <b>MOUNTING METHOD</b>                              | Floor standing distribution board |
| <b>SUITABLE FOR ENCLOSURE BUILDING LENGTH/DEPTH</b> | 250 mm                            |
| <b>SUITABLE FOR ENCLOSURE BUILDING WIDTH</b>        | 350 mm                            |
| <b>SUITABLE FOR LENGTH/DEPTH</b>                    | 250 mm                            |
| <b>SUITABLE FOR WIDTH</b>                           | 350 mm                            |
| <b>SURFACE FINISHING</b>                            | With powder coating               |
| <b>DEGREE OF PROTECTION</b>                         | IP54                              |

## Delivery programme

|              |                      |
|--------------|----------------------|
| <b>COLOR</b> | Gray                 |
| <b>MODEL</b> | Other                |
| <b>TYPE</b>  | Additional equipment |

## Resources

|                    |                                                                                      |
|--------------------|--------------------------------------------------------------------------------------|
| <b>BROCHURES</b>   | <a href="#">eaton-xenergy-basic-light-brochure-br014024-en-us.pdf</a>                |
| <b>CATALOGUES</b>  | <a href="#">eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf</a> |
| <b>FLYERS</b>      | <a href="#">eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf</a>             |
| <b>SALES NOTES</b> | <a href="#">eaton-f3a-flange-flyer-fl019005en-en-us.pdf</a>                          |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

