


Specifications



Eaton 144113

Eaton Moeller series NZM - Molded Case Circuit Breaker. Tunnel terminal, 3p, 6x35mm², +cover

General specifications

PRODUCT NAME	Eaton Moeller series NZM connection type
CATALOG NUMBER	144113
MODEL CODE	NZM2-XKAM
EAN	4015081406296
PRODUCT LENGTH/DEPTH	81 mm
PRODUCT HEIGHT	87 mm
PRODUCT WIDTH	105 mm
PRODUCT WEIGHT	0.42 kg
COMPLIANCES	IEC UL/CSA RoHS conform

Additional information

MODEL

Other

Delivery programme

AMPERAGE RATING

□ 250 A

FRAME

NZM2

NUMBER OF POLES

Three-pole

SUITABLE FOR

Three-pole
Copper cable

TYPE

Tunnel terminal

USED WITH

NZM2, PN2, N(S)2

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Technical data - electrical

AMPERAGE RATING

□ 250 A

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - mechanical - terminals

TERMINAL CAPACITY (STRANDED CABLE)	14 - 2 AWG/kcmil (6x) 2.5 mm ² - 35 mm ² (6x) at digital input of supply connection
---	--

Resources

BROCHURES	eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf eaton-digital-nzm-brochure-br013003en-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
DRAWINGS	eaton-circuit-breaker-terminals-nzm-tunnel-terminal-dimensions-004.eps eaton-circuit-breaker-terminals-nzm-tunnel-terminal-3d-drawing-002.eps
ECAD MODEL	DA-CE-ETN.NZM2-XKAM
INSTALLATION INSTRUCTIONS	eaton-circuit-breakers-nzm2-tunnel-terminal-nzm2-4-xkam-instruction-leaflet-il01206001z.pdf
INSTALLATION VIDEOS	Introduction of the new digital circuit breaker NZM The new digital NZM Range DA-CS-nzm2_xkam
MCAD MODEL	eaton-mccb-terminals-mcad-drawings-nzm2-xkam.dwg

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

