

Specifications

Eaton 144717



Eaton xEnergy Basic LV systems Low voltage switchgear. Top or bottom panel for surface-mounted service distribution boards with opening for cable entry, W x D = 1000 x 249 mm, white

General specifications

PRODUCT NAME	Eaton xEnergy Basic top-/floor cover element
CATALOG NUMBER	144717
MODEL CODE	BP-TBP1-1000-CE-W
EAN	4015081412174
PRODUCT LENGTH/DEPTH	250 mm
PRODUCT HEIGHT	55 mm
PRODUCT WIDTH	1000 mm
PRODUCT WEIGHT	2.3 kg
COMPLIANCES	RoHS conform

Additional information

FITTED WITH:	Cable entry
RAL-NUMBER	9016
SPECIAL FEATURES	With opening for cable entry
SUITABLE FOR	Roof planking Bottom planking

Technical data - mechanical

CABLE ENTRY TYPE	Open
HOUSING MATERIAL	Sheet steel
MATERIAL	Steel
MOUNTING METHOD	Surface mounting
SUITABLE FOR ENCLOSURE BUILDING LENGTH/DEPTH	249 mm
SUITABLE FOR ENCLOSURE BUILDING WIDTH	1000 mm
SUITABLE FOR LENGTH/DEPTH	249 mm
SUITABLE FOR WIDTH	1000 mm
SURFACE FINISHING	With powder coating Powder coating
DEGREE OF PROTECTION	IP30

Delivery programme

COLOR	White Traffic white (RAL 9016)
TYPE	Additional equipment

Resources

BROCHURES	eaton-xenergy-basic-light-brochure-br014024-en-us.pdf
CATALOGUES	eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf
FLYERS	eaton-xenergy-basic-profisnap-flyer-fl019008en-en-us.pdf
SALES NOTES	eaton-f3a-flange-flyer-fl019005en-en-us.pdf

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

