

Specifications

Eaton 158306

Eaton Moeller series xPole - SPBT12 Surge Protection Device. Lightning current and surge arresters, 12, 5 kA, L-(SU) N

General specifications

PRODUCT NAME	Eaton Moeller series xPole - SPBT12 Surge protection device
CATALOG NUMBER	158306
MODEL CODE	SPBT12-280/1
EAN	4015081548842
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	65 mm
PRODUCT WIDTH	17.5 mm
PRODUCT WEIGHT	0.137 kg
COMPLIANCES	RoHS conform

Additional information

SYSTEM CONFIGURATION TYPE	TN
	Other
TEST CLASS	TN-S
	Type 1 + 2

Technical data - electrical

CONTINUOUS VOLTAGE AT AC - MAX 280 V

LIGHTNING IMPULSE CURRENT (10/350 MS) 12.5 kA

NOMINAL VOLTAGE AT AC 280 V

SIGNALLING AT THE DEVICE Optic

SPECIFIC ENERGY (W/R) 39.1 kJ/Ohm

VOLTAGE PROTECTION LEVEL 1.5 kV

VOLTAGE PROTECTION LEVEL (L-PE) 1.5 kV

Delivery programme

APPLICATION

- Open areas
- Residential buildings
- Utility buildings

NUMBER OF POLES Single-pole

TYPE Surge arrester

Technical data - mechanical

CONDUCTOR CROSS SECTION (FLEXIBLE, FINE-STRAND) - MAX 35 mm²

CONDUCTOR CROSS SECTION (SOLID, SOLID-STRAND) - MAX 25 mm²

DEGREE OF PROTECTION IP20

FRAME 1 modular spacing

MOUNTING METHOD DIN rail (top hat rail) 35 mm

Resources

CATALOGUES [eaton-surge-protection-catalog-ca010001en-en-us.pdf](#)

DECLARATIONS OF CONFORMITY [eaton-surge-protection-device-declaration-of-conformity-eu250062en.pdf](#)

INSTALLATION INSTRUCTIONS [IL019217ZU](#)

MCAD MODEL [eaton-t2-arrestor-mcad-drawings-sp-1p.dwg](#)
[eaton-t2-arrestor-mcad-3d-models-sp-1p.stp](#)

PEP ECO-PASSPORT [eaton-t2-arrestor-pep-eato-00260-v0101-en.pdf](#)

WIRING DIAGRAMS [eaton-xpole-spct2-surge-protection-device-wiring-diagram-003.jpg](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

