

Specifications



Eaton 158331

Eaton Moeller series xPole - SPBT12 Surge Protection Device. Lightning current and surge arresters kit, TN-S kit, 4p

General specifications

PRODUCT NAME	Eaton Moeller series xPole - SPBT12 Surge protection device
CATALOG NUMBER	158331
MODEL CODE	SPBT12-280/4
EAN	4015081548897
PRODUCT LENGTH/DEPTH	86 mm
PRODUCT HEIGHT	69 mm
PRODUCT WIDTH	70 mm
PRODUCT WEIGHT	0.574 kg
COMPLIANCES	RoHS conform

Additional information

SYSTEM CONFIGURATION TYPE	Other TN TN-S TT
TEST CLASS	Type 1 + 2

Technical data - electrical

CONTINUOUS VOLTAGE AT AC - MAX 280 V

LIGHTNING IMPULSE CURRENT (10/350 MS) 12.5 kA

NOMINAL VOLTAGE AT AC 280 V

SIGNALLING AT THE DEVICE Optic

SPECIFIC ENERGY (W/R) 39.1 kJ/Ohm

VOLTAGE PROTECTION LEVEL 1.5 kV

VOLTAGE PROTECTION LEVEL (L-PE) 1.5 kV

Delivery programme

APPLICATION	• Open areas • Residential buildings • Utility buildings
--------------------	--

NUMBER OF POLES Four-pole

TYPE Surge arrester

Technical data - mechanical

CONDUCTOR CROSS SECTION (FLEXIBLE, FINE-STRAND) - MAX 35 mm²

CONDUCTOR CROSS SECTION (SOLID, SOLID-STRAND) - MAX 25 mm²

DEGREE OF PROTECTION IP20

FRAME 4 modular spacing

MOUNTING METHOD DIN rail (top hat rail) 35 mm

Resources

CATALOGUES [eaton-surge-protection-catalog-ca010001en-en-us.pdf](#)

CHARACTERISTIC CURVE [eaton-dimensions-mas_spbt12.jpg](#)

DECLARATIONS OF CONFORMITY [eaton-surge-protection-device-declaration-of-conformity-eu250062en.pdf](#)

INSTALLATION INSTRUCTIONS [IL019217ZU](#)

MCAD MODEL [eaton-t2-arrestor-mcad-3d-models-sp-4p.stp](#)
[eaton-modular-i-o-system-analog-mcad-drawings-sp-4p.dwg](#)

PEP ECO-PASSPORT [eaton-t2-arrestor-pep-eato-00260-v0101-en.pdf](#)

WIRING DIAGRAMS [eaton-xpole-spct2-surge-protection-device-wiring-diagram-003.jpg](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

