

Specifications



Eaton 168545

Eaton Moeller series NZM - Molded Case Circuit Breaker. Switch-disconnector 3p + plug-in contacts, 630A

General specifications

PRODUCT NAME	Eaton Moeller series NZM switch-disconnector
CATALOG NUMBER	168545
MODEL CODE	N3-630-SVE
EAN	4015081650200
PRODUCT LENGTH/DEPTH	335 mm
PRODUCT HEIGHT	215.2 mm
PRODUCT WIDTH	140 mm
PRODUCT WEIGHT	5.42 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC 60947-3



Powering Business Worldwide

Additional information

FUNCTIONS

Voltage release optional
Interlockable

Delivery programme

AMPERAGE RATING

630 A

FEATURES

Version as maintenance-
/service switch
Motor drive optional
Version as emergency stop
installation
Version as main switch

NUMBER OF POLES

Three-pole

SPECIAL FEATURES

- Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113.
- Busbar tag shroud to VDE 0160 Part 100.
- Rated current = rated uninterrupted current: 630 A

Design verification to IEC/EN 61439

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION	Does not apply, since the

Design verification to IEC/EN 61439 - technical data

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	40 °C
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	107.16 W

AGAINST ELECTRIC SHOCK	entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

Technical data - electrical

AMPERAGE RATING	630 A
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
HANDLE TYPE	Rocker lever
RATED OPERATING POWER AT AC-23, 400 V	315 kW
RATED OPERATING VOLTAGE (UE) AT AC - MAX	690 V
RATED OPERATIONAL CURRENT	630 A (415 V AC-22A, making and breaking capacity) 500 A (415 V AC-23A, making and breaking capacity) 630 A (690 V AC-22A, making and breaking capacity) 500 A (690 V AC-23A, making and breaking capacity)
RATED SHORT-TIME WITHSTAND CURRENT (ICW)	12 kA
SHORT-CIRCUIT PROTECTIVE DEVICE FUSES - MAX	630 A gL
VOLTAGE RATING	690 V - 690 V

Technical data - mechanical

DEGREE OF PROTECTION	IP20
DEGREE OF PROTECTION (IP), FRONT SIDE	IP20
HANDLE COLOR	Black
MOUNTING METHOD	Ground mounting Distribution board installation Intermediate mounting Built-in device plug-in technique
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
NUMBER OF SWITCHES	1

SPECIAL FEATURES

- Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113.
- Busbar tag shroud to VDE 0160 Part 100.
- Rated current = rated

Resources

BROCHURES	eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf
CATALOGUES	eaton-digital-nzm-catalog-ca013003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-switch-disconnector-declaration-of-conformity-eu250127en.pdf
ECAD MODEL	DA-CE-ETN.N3-630-SVE
INSTALLATION VIDEOS	The new digital NZM Range Introduction of the new digital circuit breaker NZM
MCAD MODEL	nzmh3 me220 sve.stp eaton-motor-protector-mcad-drawings-nzmh3-me220-sve.dwg
PEP ECO-PASSPORT	eaton-switch-disconnectors-pep-eato-00198-v0101-en.pdf
TECHNICAL DATA SHEETS	eaton-nzm-technical-information-sheet

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:
