

Specifications



Eaton 171299

Eaton Moeller® series SL4 Base module; 400-mm aluminum tube and foot

General specifications

PRODUCT NAME	Eaton Moeller® series SL4 Base module
CATALOG NUMBER	171299
MODEL CODE	SL4-PIB-400
EAN	4015081678426
PRODUCT LENGTH/DEPTH	72 mm
PRODUCT HEIGHT	452 mm
PRODUCT WIDTH	72 mm
PRODUCT WEIGHT	0.214 kg
CERTIFICATIONS	Certified by UL for use in Canada UL 508 UL Category Control No.: NKCR CSA Class No.: NKCR7 UL report applies to both US and Canada CSA-C22.2 No. 14-10 CE UL File No.: E29184 IEC/EN 60947-5-1 CSA-C22.2 No. 94-91 UL IEC/EN 60529

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Features & functions

COLOR	Other
FITTED WITH:	Aluminum tube Plastic foot Cover
NUMBER OF MODULES	Max. 5 Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)

Terminal capacities

TERMINAL CAPACITY (AWG)	24 - 16
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE AND PLASTIC COLLAR)	0.25 - 0.75 mm²
TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE)	0.25 - 1.5 mm²
TERMINAL CAPACITY (SOLID/FLEXIBLE)	0.2 - 1.5 mm²

Electrical rating

RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL VOLTAGE	110/120 V AC ± 10 % 230/240 V AC ± 10 % 24 V AC/DC ± 10 %

General information

CONNECTION TO SMARTWIRE-DT	No
DEGREE OF PROTECTION	IP66 NEMA 4X NEMA 4 NEMA 13
MOUNTING METHOD	Horizontal Floor Bracket
MOUNTING POSITION	As required
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	SL signal towers
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
TUBE LENGTH	400 mm
TYPE	Base module

Resources

BROCHURES	SL4, SL7, SLC Stack light overview brochure BR047017
CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf eaton-rmq-titan-brochure-br047004en-en-us.pdf

DECLARATIONS OF CONFORMITY	eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf
	eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf
DRAWINGS	eaton-operating-sl4-base-module-dimensions-010.eps
	eaton-operating-sl4-base-module-3d-drawing.eps
	eaton-operating-button-sl7-base-module-symbol.eps
ECAD MODEL	DA-CE-ETN.SL4-PIB-400
INSTALLATION INSTRUCTIONS	IL047001ZU IL047002ZU
INSTALLATION VIDEOS	Signal towers SL4 and SL7
MCAD MODEL	eaton-base-modules-mcad-drawings-sl4-pib-400.dwg
	DA-CS-sl4_pib_400

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

