

Specifications



Eaton 171304

Eaton Moeller® series SL4 Base module; for vertical mounting on both sides

General specifications

PRODUCT NAME	Eaton Moeller® series SL4 Base module
---------------------	---------------------------------------

CATALOG NUMBER	171304
-----------------------	--------

MODEL CODE	SL4-PIB-D
-------------------	-----------

EAN	4015081679195
------------	---------------

PRODUCT LENGTH/DEPTH	56 mm
-----------------------------	-------

PRODUCT HEIGHT	118 mm
-----------------------	--------

PRODUCT WIDTH	62 mm
----------------------	-------

PRODUCT WEIGHT	0.11 kg
-----------------------	---------

CERTIFICATIONS	CE UL 508 CSA Class No.: NKCR7 UL UL File No.: E29184 Certified by UL for use in Canada UL report applies to both US and Canada UL Category Control No.: NKCR CSA-C22.2 No. 94-91 CSA-C22.2 No. 14-10 IEC/EN 60947-5-1 IEC/EN 60529
-----------------------	--



Powering Business Worldwide

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Features & functions

COLOR	Other
FITTED WITH:	Cover External fixing holes
NUMBER OF MODULES	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base) Max. 2 x 5

Terminal capacities

TERMINAL CAPACITY (AWG)	24 - 16
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE AND PLASTIC COLLAR)	0.25 - 0.75 mm²
TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE)	0.25 - 1.5 mm²
TERMINAL CAPACITY (SOLID/FLEXIBLE)	0.2 - 1.5 mm²

Electrical rating

RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL VOLTAGE	230/240 V AC ± 10 % 24 V AC/DC ± 10 % 110/120 V AC ± 10 %

General information

CONNECTION TO SMARTWIRE-DT	No
DEGREE OF PROTECTION	NEMA 4X IP66 NEMA 4 NEMA 13
MOUNTING METHOD	Floor Bracket Vertical
MOUNTING POSITION	As required
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	SL signal towers
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
TYPE	Base module

Resources

BROCHURES	SL4, SL7, SLC Stack light overview brochure BR047017
CATALOGUES	eaton-rmq-titan-brochure-br047004en-en-us.pdf eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

DECLARATIONS OF CONFORMITY	eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf
	eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf
DRAWINGS	eaton-operating-sl4-base-module-dimensions-011.eps
	eaton-operating-sl4-base-module-3d-drawing-002.eps
	eaton-operating-button-sl7-base-module-symbol.eps
ECAD MODEL	DA-CE-ETN.SL4-PIB-D
INSTALLATION INSTRUCTIONS	IL047001ZU IL047002ZU
INSTALLATION VIDEOS	Signal towers SL4 and SL7
MCAD MODEL	DA-CS-sl4_pib_d
	eaton-base-modules-mcad-drawings-sl4-pib-d.dwg

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

