

Specifications



Eaton 171306

Eaton Moeller® series SL4 Base module, 250 mm aluminum tube

General specifications

PRODUCT NAME	Eaton Moeller® series SL4 Base module
---------------------	---------------------------------------

CATALOG NUMBER	171306
-----------------------	--------

MODEL CODE	SL4-PIB-T-250
-------------------	---------------

EAN	4015081678471
------------	---------------

PRODUCT LENGTH/DEPTH	43 mm
-----------------------------	-------

PRODUCT HEIGHT	334 mm
-----------------------	--------

PRODUCT WIDTH	43 mm
----------------------	-------

PRODUCT WEIGHT	0.167 kg
-----------------------	----------

CERTIFICATIONS

Certified by UL for use in Canada
UL
CSA-C22.2 No. 14-10
IEC/EN 60947-5-1
UL report applies to both US and Canada
IEC/EN 60529
UL File No.: E29184
CSA-C22.2 No. 94-91
CSA Class No.: NKCR7
CE
UL 508
UL Category Control No.: NKCR

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
--	-------

AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
--	--------

CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
--------------------------	--

Features & functions

COLOR	Other
--------------	-------

FITTED WITH:	Cover Banjo bolt Aluminum tube
---------------------	--------------------------------------

NUMBER OF MODULES	Max. 5 (with standard base) Max. 5 Max. 10 (with base for mounting on both sides)
--------------------------	---

Electrical rating

RATED INSULATION VOLTAGE (UI)	250 V
--------------------------------------	-------

RATED OPERATIONAL VOLTAGE	110/120 V AC ± 10 % 230/240 V AC ± 10 % 24 V AC/DC ± 10 %
----------------------------------	---

General information

CONNECTION TO SMARTWIRE-DT	No
-----------------------------------	----

DEGREE OF PROTECTION	NEMA 13 NEMA 4 IP66 NEMA 4X
-----------------------------	--------------------------------------

MOUNTING METHOD	Floor Bracket Horizontal Tube
------------------------	--

MOUNTING POSITION	As required
--------------------------	-------------

OVERVOLTAGE CATEGORY	III
-----------------------------	-----

POLLUTION DEGREE	3
-------------------------	---

PRODUCT CATEGORY	SL signal towers
-------------------------	------------------

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
---	-----------

SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
-------------------------	--

TUBE LENGTH	250 mm
--------------------	--------

TYPE	Base module
-------------	-------------

Terminal capacities

TERMINAL CAPACITY (AWG)	24 - 16
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE AND PLASTIC COLLAR)	0.25 - 0.75 mm ²
TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE)	0.25 - 1.5 mm ²
TERMINAL CAPACITY (SOLID/FLEXIBLE)	0.2 - 1.5 mm ²

Resources

BROCHURES	SL4, SL7, SLC Stack light overview brochure BR047017
CATALOGUES	eaton-rmq-titan-brochure-br047004en-en-us.pdf eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf
DRAWINGS	eaton-operating-sl4-base-module-dimensions-016.eps eaton-operating-sl4-base-module-3d-drawing-006.eps eaton-operating-button-sl7-base-module-symbol.eps
ECAD MODEL	DA-CE-ETN.SL4-PIB-T-250
INSTALLATION INSTRUCTIONS	IL047001ZU
INSTALLATION VIDEOS	Signal towers SL4 and SL7
MCAD MODEL	DA-CS-sl4 pib t 250 eaton-base-modules-mcad-drawings-sl4-pib-t-250.dwg

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

