

Specifications



Photo is representative



Eaton 171314

Eaton Moeller® series SL4 Continuous light module, green, LED, 24 V

General specifications

PRODUCT NAME	Eaton Moeller® series SL4 Continuous light module
CATALOG NUMBER	171314
MODEL CODE	SL4-L24-G
EAN	4015081678549
PRODUCT LENGTH/DEPTH	43 mm
PRODUCT HEIGHT	75 mm
PRODUCT WIDTH	43 mm
PRODUCT WEIGHT	0.042 kg

CERTIFICATIONS	UL 508 IEC/EN 60529 UL CSA Class No.: NKCR7 UL Category Control No.: NKCR Certified by UL for use in Canada UL report applies to both US and Canada CSA-C22.2 No. 14-10 IEC/EN 60947-5-1 UL File No.: E29184 CE CSA-C22.2 No. 94-91
-----------------------	--



Powering Business Worldwide

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-30 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Features & functions

COLOR	Green
ENCLOSURE COLOR	Black
FUNCTIONS	Continuous light
LIGHT MODULES	LED
NUMBER OF MODULES	Max. 10 (with base for mounting on both sides) Max. 5 (with standard base)

Electrical rating

LEAKAGE CURRENT	0.003 A
RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	24 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	24 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	24 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	24 V

General information

CONNECTION TO SMARTWIRE-DT	No
CURRENT CONSUMPTION	50 mA at 24 V AC/DC
DEGREE OF PROTECTION	NEMA 4X IP66
LIFESPAN, ELECTRICAL	100,000 h
LIGHT TYPE	Continuous light
MATERIAL	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
MOUNTING POSITION	As required
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	SL signal towers
RADIATION ANGLE	360 °
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
TYPE	Continuous light module
VOLTAGE TYPE	AC/DC

Resources

BROCHURES	SL4, SL7, SLC Stack light overview brochure BR047017
CATALOGUES	eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf eaton-rmq-titan-brochure-br047004en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-continuous-light-module-declaration-of-conformity-eu250556en.pdf eaton-continuous-light-module-declaration-of-conformity-uk251039en.pdf
DRAWINGS	eaton-operating-sl4-continuous-light-dimensions.eps eaton-operating-sl7-continuous-light-symbol-002.eps eaton-operating-button-sl7-continuous-light-symbol-002.eps
ECAD MODEL	ETN.171314.edz
INSTALLATION INSTRUCTIONS	IL047001ZU
INSTALLATION VIDEOS	Signal towers SL4 and SL7
MCAD MODEL	eaton-light-modules-mcad-drawings-sl4-bfl4.dwg DA-CS-sl4_bfl4

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

